

DuPont™ Cyrel® DRC

Economical Analog Printing Plate for the Corrugated Board Industry

Applications

- Corrugated board
- Paper substrates



Cyrel® DRC is the robust plate for printing line work & solids on any corrugated board substrate. Cyrel® DRC is used for line work, solid printing and limited halftone printing on all kinds of corrugated board substrates from coarse C to fine E and F -flutings.

Product Features

- Good platemaking latitude – no masking necessary
- Shore hardness adapted to use with different board flutings

Printing Ink and Solvent Compatibility

Cyrel® DRC offers excellent compatibility with water- based inks.

Process of use

Expose the plate through the back to establish the floor and maximize sensitivity. Back exposure varies according to relief required. Remove the protective coversheet and expose the front of the plate. Process the plate in the Cyrel® plate processor. Finish the plate in a light finisher to eliminate surface tackiness. Post -expose the plate to ensure complete polymerisation.

Storage – Raw Material

Store unexposed plates in a cool area (40-90°F, 4-32° C), away from direct sources of heat. Humidity control is not required. Cyrel® DRC is foam interleaved to provide maximum protection of the plate after manufacture, and

during transportation and storage. Plates should be stacked flat. Plates should not be exposed to direct sunlight or excessive white light. Continuous exposure to very high ozone concentrations should be avoided.

Handling – Raw Material

Cyrel® DRC plates should be handled under UV free light; e.g. fluorescent tubes covered with amber sleeves.

Storage – Finished Plates

After printing, plates should be thoroughly cleaned with compatible solvent before storing. They may be stored on cylinders, sleeves or demounted and stored flat.

Availability

Cyrel® DRC is available in thickness 125, 155, 170, 185, 197, 217 237 and 250 inches.

Formats available are 42 x 60 inches (106.7 x 152.4cm) and 52 x 80 inches (132.0 x 203.2 cm).

DuPont™ Cyrel® DRC

Economical Analog Printing Plate for the Corrugated Board Industry

Technical Data

| | Thickness | Durometer | Image Reproduction | Min. Positive Line Width | Min. Isolated Dot Size | Relief Depth |
|-----------------------|------------------|-----------|--------------------|--------------------------|------------------------|-------------------------------|
| Cyrel® DRC 125 | 3.18 mm / 0.125" | 38 Sh A | 3 – 95% / 42 L/cm | 0.175 mm / 7 mil | 250 µm | 1.0 – 1.5 mm / 0.039 – 0.059" |
| Cyrel® DRC 155 | 3.94 mm / 0.155" | 37 Sh A | 3 – 95% / 36 L/cm | 0.35 mm / 14 mil | 500 µm | 1.5 – 2.0 mm / 0.059 – 0.079" |
| Cyrel® DRC 170 | 4.32 mm / 0.170" | 36 Sh A | 3 – 95% / 28 L/cm | 0.35 mm / 14 mil | 500 µm | 1.5 – 2.0 mm / 0.059 – 0.079" |
| Cyrel® DRC 185 | 4.70 mm / 0.185" | 36 Sh A | 3 – 95% / 28 L/cm | 0.35 mm / 14 mil | 500 µm | 1.5 – 2.5 mm / 0.059 – 0.098" |
| Cyrel® DRC 197 | 5.00 mm / 0.197" | 36 Sh A | 3 – 95% / 28 L/cm | 0.35 mm / 14 mil | 500 µm | 2.5 mm – 0.098" |
| Cyrel® DRC 217 | 5.51 mm / 0.217" | 35 Sh A | 3 – 95% / 28 L/cm | 0.35 mm / 14 mil | 500 µm | 2.5 mm – 0.098" |
| Cyrel® DRC 237 | 6.02 mm / 0.237" | 35 Sh A | 3 – 95% / 28 L/cm | 0.35 mm / 14 mil | 500 µm | 2.5 mm – 0.098" |
| Cyrel® DRC 250 | 6.35 mm / 0.250" | 34 Sh A | 3 – 95% / 28 L/cm | 0.35 mm / 14 mil | 500 µm | 2.5 mm – 0.098" |

DuPont Advanced Printing brings together leading technologies and products for the printing and package printing industries. DuPont™ Cyrel® is one of the world's leading flexographic platemaking systems in digital and conventional formats, including DuPont™ Cyrel® brand photopolymer plates (analog and digital), Cyrel® platemaking equipment, Cyrel® round sleeves, Cyrel® plate mounting systems and the revolutionary Cyrel® FAST thermal system.



cyrel.com/na

For more information on DuPont™ Cyrel® or other DuPont products, please visit our website.

The information provided in this data sheet corresponds to our knowledge on the subject at the date of its publication. It may be subject to revision as new knowledge and experience becomes available. This information is not intended to substitute for any testing you may need to conduct to determine for yourself the suitability of our products for your particular purposes. Since we cannot anticipate all variations in end-use and disposal conditions, DuPont makes no warranties and assumes no liability in connection with any use of this information. It is intended for use by persons having technical skill, at their own discretion and risk. Nothing in this publication is to be considered as a license to operate under or a recommendation to infringe any patent right.

DuPont™, the DuPont Oval Logo, and all products, unless otherwise noted, denoted with ™, SM or ® are trademarks, service marks or registered trademarks of affiliates of DuPont de Nemours, Inc. Copyright © 2020 DuPont de Nemours, Inc. All rights reserved

PDS-NA0051-EN (10/20)