

BETASEAL™ 1585



High-viscosity, 30-minute minimum drive away adhesive

Perfect choice for ADAS-equipped vehicles

- Excellent link-up strength allows for 30-minute minimum drive-away time in temperatures from -10°C to 40°C
- Can be applied directly to freshly trimmed, cut-back PU bead with no need for primer – for increased productivity
- High-modulus formula helps maintain structural integrity at original equipment levels
- Simple, three-step glass replacement solution – clean, prime, bond
- Non-conductive formula – reduces interference with radio, mobile phone, GPS or additional driver aid technologies
- No heating required for improved work efficiency
- Choice of two sizes – 420 ml or 600 ml sausage packs. Also available in kits that include cleaning sponges and primer.





BETASEAL™ 1585 – Next-generation, high viscosity, 30-minute minimum drive away, primerless to aperture formula

Designed to complement vehicles equipped with ADAS

BETASEAL™ 1585 has outstanding decking performance, resulting in less auto glass movement during static recalibration for a more accurate reading.

30-minute minimum drive away — exclusive AINS technology

BETASEAL™ 1585 is a cold-applied adhesive with a 30-minute minimum drive away. The exclusive Accelerated Isotropic Network Structure (AINS) technology creates outstanding link-up strength while the adhesive is still partially cured, making for a faster minimum drive-away time.

Primerless to aperture

BETASEAL™ 1585 can be directly applied to a fresh-cut polyurethane bead without the need for a primer – saving you time and money.

High-modulus formula promotes structural integrity

The high-modulus formula helps promote the car's structural integrity and stabilization to improve the ride and reduce rattles, vibrations and other vehicle noises. It's also non-conductive to reduce interference with radio, mobile phone, GPS or additional driver aid technologies.

More information

For more information on how BETASEAL™ 1585 and AINS technology can help your customers get back on the road, visit www.dupont.com/aftermarket.

Physical Properties	BETASEAL™ 1585*
Minimum Drive-Away Time	30 minutes
G Modulus	>2 MPa
Conductivity	Non-conductive
Bulk Resistivity	1 x 10 ¹⁰ Ωcm
Working Time	10 minutes
Material Temperature Range	-5°C to 40°C
Ambient Temperature Range	-10°C to 40°C
Extrudability	Easy with 18v professional dispenser
Storage Stability	9-month shelf life

*Results based on DuPont internal testing.

www.dupont.com/aftermarket



Easy-to-use: Clean, Prime and Bond

Clean

Bonding surfaces must be clean of dirt, dust, water, oil, silicone and grease prior to priming and adhesive application. Use BETACLEAN™ Easy-Go Sponge to help remove contaminants from glass and BETACLEAN™ 3300 to inspect and clean glass before installation.

Prime

Priming of the glass and ceramic frit is required before application of BETASEAL™ 1585. BETAPRIME™ 5504G is an all-in-one primer suitable for all surfaces: cut-back PU bead, aperture, glass and ceramic frit.

Bond

BETASEAL™ adhesives are easy to gun in most weather conditions and do not require heating.



DuPont™, the DuPont Oval Logo, and all trademarks and service marks denoted with ™, SM or ® are owned by affiliates of DuPont de Nemours, Inc. unless otherwise noted. © 2023 DuPont.

The information set forth herein is furnished free of charge and is based on technical data that DuPont believes to be reliable and falls within the normal range of properties. It is intended for use by persons having technical skill, at their own discretion and risk. This data should not be used to establish specification limits nor used alone as the basis of design. Handling precaution information is given with the understanding that those using it will satisfy themselves that their particular conditions of use present no health or safety hazards. Since conditions of product use and disposal are outside our control, we make no warranties, express or implied, and assume no liability in connection with any use of this information. As with any product, evaluation under end-use conditions prior to specification is essential. Nothing herein is to be taken as a license to operate or a recommendation to infringe on patents.