



SAFETY DATA SHEET
DDP SPECIALTY ELECTRONIC MATERIALS US,
INC.

**Product name: BETACLEAN™ GC800 GLASS AND SURFACE
CLEANER**

Issue Date: 10/18/2018

Print Date: 10/08/2020

DDP SPECIALTY ELECTRONIC MATERIALS US, INC. encourages and expects you to read and understand the entire (M)SDS, as there is important information throughout the document. We expect you to follow the precautions identified in this document unless your use conditions would necessitate other appropriate methods or actions.

1. IDENTIFICATION

Product name: BETACLEAN™ GC800 GLASS AND SURFACE CLEANER

Recommended use of the chemical and restrictions on use

Identified uses: A glass cleaner -- For use in automotive applications.

COMPANY IDENTIFICATION

DDP SPECIALTY ELECTRONIC MATERIALS US,
INC.
400 ARCOLA ROAD
COLLEGEVILLE PA 19426-2914
UNITED STATES

Customer Information Number:

833-338-7668
SDSQuestion-NA@dupont.com

EMERGENCY TELEPHONE NUMBER

24-Hour Emergency Contact: 1-800-424-9300

Local Emergency Contact: 1-800-424-9300

2. HAZARDS IDENTIFICATION

Hazard classification

This product is not hazardous under the criteria of the Hazardous Products Regulation (HPR) as implemented under the Workplace Hazardous Materials Information System (WHMIS 2015).

Other hazards

No data available

3. COMPOSITION/INFORMATION ON INGREDIENTS

This product is a mixture.

Component	CASRN	Concentration
Water	7732-18-5	> 85.0 - < 95.0 %
Butane	106-97-8	> 1.0 - < 5.0 %
Ethylene glycol monobutyl ether	111-76-2	> 1.0 - < 5.0 %
Propane	74-98-6	> 1.0 - < 5.0 %

4. FIRST AID MEASURES

Description of first aid measures

General advice: First Aid responders should pay attention to self-protection and use the recommended protective clothing (chemical resistant gloves, splash protection). If potential for exposure exists refer to Section 8 for specific personal protective equipment.

Inhalation: Move person to fresh air. If not breathing, give artificial respiration; if by mouth to mouth use rescuer protection (pocket mask, etc). If breathing is difficult, oxygen should be administered by qualified personnel. Call a physician or transport to a medical facility.

Skin contact: Immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Obtain medical attention without delay. Wash clothing before reuse. Properly dispose of contaminated leather items, such as shoes, belts, and watchbands. Suitable emergency safety shower facility should be immediately available.

Eye contact: Flush eyes thoroughly with water for several minutes. Remove contact lenses after the initial 1-2 minutes and continue flushing for several additional minutes. If effects occur, consult a physician, preferably an ophthalmologist. Suitable emergency eye wash facility should be available in work area.

Ingestion: No emergency medical treatment necessary.

Most important symptoms and effects, both acute and delayed: Aside from the information found under Description of first aid measures (above) and Indication of immediate medical attention and special treatment needed (below), any additional important symptoms and effects are described in Section 11: Toxicology Information.

Indication of any immediate medical attention and special treatment needed

Notes to physician: Maintain adequate ventilation and oxygenation of the patient. If hemolysis is suspected, monitor hemoglobin, hematocrit, plasma free hemoglobin, and urinalysis. Whole blood or packed RBC transfusion may be required in severe cases. Alkalinization of urine with bicarbonate may prevent renal damage. Exposure may increase "myocardial irritability". Do not administer sympathomimetic drugs such as epinephrine unless absolutely necessary. No specific antidote. Treatment of exposure should be directed at the control of symptoms and the clinical condition of the patient.

5. FIREFIGHTING MEASURES

Suitable extinguishing media: This material does not burn. If exposed to fire from another source, use suitable extinguishing agent for that fire.

Unsuitable extinguishing media: No data available

Special hazards arising from the substance or mixture

Hazardous combustion products: Not applicable

Unusual Fire and Explosion Hazards: Container may vent and/or rupture due to fire. Expelled material will not burn.

Advice for firefighters

Fire Fighting Procedures: Keep people away. Isolate fire and deny unnecessary entry. This material does not burn. Fight fire for other material that is burning.

Special protective equipment for firefighters: Wear positive-pressure self-contained breathing apparatus (SCBA) and protective fire fighting clothing (includes fire fighting helmet, coat, trousers, boots, and gloves). If protective equipment is not available or not used, fight fire from a protected location or safe distance.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures: Isolate area. Keep unnecessary and unprotected personnel from entering the area. Keep upwind of spill. Ventilate area of leak or spill. Refer to section 7, Handling, for additional precautionary measures. Use appropriate safety equipment. For additional information, refer to Section 8, Exposure Controls and Personal Protection.

Environmental precautions: Prevent from entering into soil, ditches, sewers, waterways and/or groundwater. See Section 12, Ecological Information.

Methods and materials for containment and cleaning up: Contain spilled material if possible. Absorb with materials such as: Cat litter. Sand. Sawdust. Collect in suitable and properly labeled containers. See Section 13, Disposal Considerations, for additional information.

7. HANDLING AND STORAGE

Precautions for safe handling: Avoid contact with eyes, skin and clothing. Avoid breathing vapor. Wash thoroughly after handling. Keep container closed. Use only with adequate ventilation. See Section 8, EXPOSURE CONTROLS AND PERSONAL PROTECTION.

Conditions for safe storage: Store in accordance with good manufacturing practices.

Storage stability

Storage temperature:

> 5 - < 35 °C

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Exposure limits are listed below, if they exist.

Component	Regulation	Type of listing	Value/Notation
Butane	ACGIH	STEL	1,000 ppm
	CA AB OEL	TWA	1,000 ppm
	CA BC OEL	TWA	600 ppm
	CA BC OEL	STEL	750 ppm
	CA QC OEL	TWAEV	1,900 mg/m3 800 ppm
	CA ON OEL	TWA	800 ppm
Ethylene glycol monobutyl ether	ACGIH	TWA	20 ppm
	ACGIH	TWA	BEI
	CA AB OEL	TWA	97 mg/m3 20 ppm
	CA BC OEL	TWA	20 ppm
	CA QC OEL	TWAEV	97 mg/m3 20 ppm
	Propane	ACGIH	
Propane	CA AB OEL	TWA	1,000 ppm
	CA BC OEL	TWA	1,000 ppm
	CA QC OEL	TWAEV	1,800 mg/m3 1,000 ppm
	CA ON OEL	TWA	1,000 ppm

Consult local authorities for recommended exposure limits.

Exposure controls

Engineering controls: Use engineering controls to maintain airborne level below exposure limit requirements or guidelines. If there are no applicable exposure limit requirements or guidelines, use only with adequate ventilation. Local exhaust ventilation may be necessary for some operations.

Individual protection measures

Eye/face protection: Use chemical goggles.

Skin protection

Hand protection: Use gloves chemically resistant to this material. Examples of preferred glove barrier materials include: Butyl rubber. Neoprene. Natural rubber ("latex"). Nitrile/butadiene rubber ("nitrile" or "NBR"). Ethyl vinyl alcohol laminate ("EVAL"). Examples of acceptable glove barrier materials include: Polyvinyl chloride ("PVC" or "vinyl"). Avoid gloves made of: Polyvinyl alcohol ("PVA"). NOTICE: The selection of a specific glove for a particular application and duration of use in a workplace should also take into account all relevant workplace factors such as, but not limited to: Other chemicals which may be handled, physical requirements (cut/puncture protection, dexterity, thermal protection), potential body reactions to glove materials, as well as the instructions/specifications provided by the glove supplier.

Other protection: Use protective clothing chemically resistant to this material. Selection of specific items such as face shield, boots, apron, or full body suit will depend on the task.

Respiratory protection: Respiratory protection should be worn when there is a potential to exceed the exposure limit requirements or guidelines. If there are no applicable exposure limit requirements or guidelines, use an approved respirator. Selection of air-purifying or positive-pressure supplied-air will depend on the specific operation and the potential airborne

concentration of the material. For emergency conditions, use an approved positive-pressure self-contained breathing apparatus. In confined or poorly ventilated areas, use an approved self-contained breathing apparatus or positive pressure air line with auxiliary self-contained air supply.

The following should be effective types of air-purifying respirators: Organic vapor cartridge with a particulate pre-filter.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance

Physical state	aerosol
Color	Colorless
Odor	Odorless
Odor Threshold	No test data available
pH	No test data available
Melting point/range	No test data available
Freezing point	No test data available
Boiling point (760 mmHg)	No test data available
Flash point	closed cup > 93.3 °C <i>Pensky-Martens Closed Cup ASTM D 93</i>
Evaporation Rate (Butyl Acetate = 1)	No test data available
Flammability (solid, gas)	The product is not flammable.
Lower explosion limit	No test data available
Upper explosion limit	No test data available
Vapor Pressure	No test data available
Relative Vapor Density (air = 1)	No test data available
Relative Density (water = 1)	0.9527 <i>ASTM D1475</i>
Water solubility	No test data available
Partition coefficient: n-octanol/water	No data available
Auto-ignition temperature	No test data available
Decomposition temperature	No test data available
Kinematic Viscosity	No test data available
Explosive properties	No test data available
Oxidizing properties	No test data available
Molecular weight	No data available
Volatile Organic Compounds	0.78 lb/gln <i>EPA Method No. 24</i> (typical value)

NOTE: The physical data presented above are typical values and should not be construed as a specification.

10. STABILITY AND REACTIVITY

Reactivity: No data available

Chemical stability: Stable.

Possibility of hazardous reactions: Polymerization will not occur.

Conditions to avoid: Elevated temperatures can cause container to vent and/or rupture.

Incompatible materials: Avoid contact with oxidizing materials.

Hazardous decomposition products: Does not decompose.

11. TOXICOLOGICAL INFORMATION

Toxicological information appears in this section when such data is available.

Acute toxicity

Acute oral toxicity

Harmful effects not anticipated from swallowing small amounts.
Single dose oral LD50 has not been determined.

Acute dermal toxicity

Repeated skin contact may result in absorption of harmful amounts. Excessive exposure may cause hemolysis, thereby impairing the blood's ability to transport oxygen.
The dermal LD50 has not been determined.

Acute inhalation toxicity

Vapor concentrations are attainable which could be hazardous on single exposure. Intentional misuse by concentrating and inhaling vapors may be harmful or fatal. Excessive exposure to solvent(s) may cause respiratory irritation and central nervous system depression. Symptoms may include headache, dizziness and drowsiness, progressing to incoordination and unconsciousness. Symptoms of excessive exposure may be anesthetic or narcotic effects; dizziness and drowsiness may be observed. Excessive exposure may increase sensitivity to epinephrine and increase myocardial irritability (irregular heartbeats).
The LC50 has not been determined.

Skin corrosion/irritation

Prolonged contact may cause skin irritation with local redness.

Serious eye damage/eye irritation

May cause moderate eye irritation.

Sensitization

For skin sensitization:

No relevant data found.

For respiratory sensitization:

No relevant data found.

Specific Target Organ Systemic Toxicity (Single Exposure)

Available data are inadequate to determine single exposure specific target organ toxicity.

Specific Target Organ Systemic Toxicity (Repeated Exposure)

For the minor component(s):

In animals, effects have been reported on the following organs: blood (hemolysis) and secondary effects on the kidney and liver.

Carcinogenicity

In long-term animal studies with ethylene glycol butyl ether, small but statistically significant increases in tumors were observed in mice but not rats. The effects are not believed to be relevant to humans. If the material is handled in accordance with proper industrial handling procedures, exposures should not pose a carcinogenic risk to man.

Teratogenicity

Contains component(s) which did not cause birth defects in animals; other fetal effects occurred only at doses toxic to the mother.

Reproductive toxicity

In animal studies on component(s), effects on reproduction were seen only at doses that produced significant toxicity to the parent animals.

Mutagenicity

For the component(s) tested: In vitro genetic toxicity studies were predominantly negative.

Aspiration Hazard

Based on physical properties, not likely to be an aspiration hazard.

COMPONENTS INFLUENCING TOXICOLOGY:

Butane

Acute oral toxicity

Single dose oral LD50 has not been determined.

Acute dermal toxicity

The dermal LD50 has not been determined.

Acute inhalation toxicity

Symptoms of excessive exposure may be anesthetic or narcotic effects; dizziness and drowsiness may be observed. Excessive exposure may increase sensitivity to epinephrine and increase myocardial irritability (irregular heartbeats). In confined or poorly ventilated areas, vapor can easily accumulate and can cause unconsciousness and death due to displacement of oxygen.

LC50, Rat, 4 Hour, vapour, 280000 ppm

Ethylene glycol monobutyl ether

Acute oral toxicity

In animals, effects have been reported on the following organs: blood (hemolysis) and secondary effects on the kidney and liver. Human red blood cells have been shown to be

significantly less sensitive to hemolysis than those of rodents and rabbits. LD50, Guinea pig, 1,400 mg/kg

LD50, Rat, 1,300 mg/kg

Acute dermal toxicity

Humans and guinea pigs are resistant to blood effects that are seen for rodents and rabbits. For this reason, the guinea pig data is used as the basis for the acute toxicity classification as it is a better model to assess acute toxicity to humans. LD50, Guinea pig, > 2,000 mg/kg

Acute inhalation toxicity

In animals, effects have been reported on the following organs: blood (hemolysis) and secondary effects on the kidney and liver. Human red blood cells have been shown to be significantly less sensitive to hemolysis than those of rodents and rabbits. LC0, Guinea pig, 1 Hour, vapour, > 3.1 mg/l No deaths occurred at this concentration.

Propane

Acute oral toxicity

Single dose oral LD50 has not been determined.

Acute dermal toxicity

The dermal LD50 has not been determined.

Acute inhalation toxicity

In confined or poorly ventilated areas, vapor can easily accumulate and can cause unconsciousness and death due to displacement of oxygen. Excessive exposure may increase sensitivity to epinephrine and increase myocardial irritability (irregular heartbeats). May cause central nervous system effects. At air concentrations <1000 ppm, propane exerts very little physiological action; at 100,000 ppm and above it may produce dizziness or other central nervous system effects. Excessive exposure may cause headache, dizziness, anesthesia, drowsiness, unconsciousness and other central nervous system effects, including death. Based on the available data, respiratory irritation was not observed.

LC50, Rat, male and female, 4 Hour, vapour, > 425000 ppm

Carcinogenicity

Component	List	Classification
Ethylene glycol monobutyl ether	ACGIH	A3: Confirmed animal carcinogen with unknown relevance to humans.

12. ECOLOGICAL INFORMATION

Ecotoxicological information appears in this section when such data is available.

Toxicity

Butane

Acute toxicity to fish

Material is moderately toxic to aquatic organisms on an acute basis (LC50/EC50 between 1 and 10 mg/L in the most sensitive species tested).

Ethylene glycol monobutyl ether

Acute toxicity to fish

Material is practically non-toxic to aquatic organisms on an acute basis (LC50/EC50/EL50/LL50 >100 mg/L in the most sensitive species tested).
LC50, Oncorhynchus mykiss (rainbow trout), static test, 96 Hour, 1,474 mg/l, OECD Test Guideline 203

Acute toxicity to aquatic invertebrates

EC50, Daphnia magna (Water flea), static test, 48 Hour, 1,550 mg/l, OECD Test Guideline 202

Acute toxicity to algae/aquatic plants

EbC50, Pseudokirchneriella subcapitata (green algae), static test, 72 Hour, Biomass, 911 mg/l, OECD Test Guideline 201

Toxicity to bacteria

IC50, Bacteria, Growth inhibition, > 1,000 mg/l

Chronic toxicity to fish

NOEC, Danio rerio (zebra fish), semi-static test, 21 d, > 100 mg/l

Chronic toxicity to aquatic invertebrates

NOEC, Daphnia magna (Water flea), semi-static test, 21 d, Other, 100 mg/l

Propane

Acute toxicity to fish

No relevant data found.

Persistence and degradability

Butane

Biodegradability: Material is expected to be readily biodegradable.

Theoretical Oxygen Demand: 3.58 mg/mg

Photodegradation

Test Type: Half-life (indirect photolysis)

Sensitizer: OH radicals

Atmospheric half-life: 49 Hour

Method: Estimated.

Ethylene glycol monobutyl ether

Biodegradability: Material is readily biodegradable. Passes OECD test(s) for ready biodegradability. Material is ultimately biodegradable (reaches > 70% mineralization in OECD test(s) for inherent biodegradability).

10-day Window: Pass

Biodegradation: 90.4 %

Exposure time: 28 d

Method: OECD Test Guideline 301B or Equivalent

Theoretical Oxygen Demand: 2.30 mg/mg

Chemical Oxygen Demand: 2.21 mg/g Dichromate

Biological oxygen demand (BOD)

Incubation Time	BOD
5 d	5.2 %
10 d	57 %
20 d	72.2 %

Propane

Biodegradability: No relevant data found.

Theoretical Oxygen Demand: 3.64 mg/mg

Photodegradation

Test Type: Half-life (indirect photolysis)

Sensitizer: OH radicals

Atmospheric half-life: 8.4 d

Method: Estimated.

Bioaccumulative potential

Butane

Bioaccumulation: Bioconcentration potential is low (BCF < 100 or Log Pow < 3).

Partition coefficient: n-octanol/water(log Pow): 2.89 Measured

Ethylene glycol monobutyl ether

Bioaccumulation: Bioconcentration potential is low (BCF < 100 or Log Pow < 3).

Partition coefficient: n-octanol/water(log Pow): 0.81 Measured

Bioconcentration factor (BCF): 3.2

Propane

Bioaccumulation: Bioconcentration potential is low (BCF < 100 or Log Pow < 3).

Partition coefficient: n-octanol/water(log Pow): 2.36 Measured

Mobility in soil

Butane

Potential for mobility in soil is very high (Koc between 0 and 50).

Partition coefficient (Koc): 44 - 900 Estimated.

Ethylene glycol monobutyl ether

Potential for mobility in soil is high (Koc between 50 and 150).

Partition coefficient (Koc): 67 Estimated.

Propane

Potential for mobility in soil is very high (Koc between 0 and 50).

Partition coefficient (Koc): 24 - 460 Estimated.

13. DISPOSAL CONSIDERATIONS

Disposal methods: DO NOT DUMP INTO ANY SEWERS, ON THE GROUND, OR INTO ANY BODY OF WATER. All disposal practices must be in compliance with all Federal, State/Provincial and local laws and regulations. Regulations may vary in different locations. Waste characterizations and compliance with applicable laws are the responsibility solely of the waste generator. AS YOUR SUPPLIER, WE HAVE NO CONTROL OVER THE MANAGEMENT PRACTICES OR MANUFACTURING PROCESSES OF PARTIES HANDLING OR USING THIS MATERIAL. THE INFORMATION PRESENTED HERE PERTAINS ONLY TO THE PRODUCT AS SHIPPED IN ITS INTENDED CONDITION AS DESCRIBED IN MSDS SECTION: Composition Information. FOR UNUSED & UNCONTAMINATED PRODUCT, the preferred options include sending to a licensed, permitted: Incinerator or other thermal destruction device.

Treatment and disposal methods of used packaging: Empty containers should be recycled or otherwise disposed of by an approved waste management facility. Waste characterizations and compliance with applicable laws are the responsibility solely of the waste generator. Do not re-use containers for any purpose.

14. TRANSPORT INFORMATION

TDG

Proper shipping name	AEROSOLS
UN number	UN 1950
Class	2.2
Packing group	

Classification for SEA transport (IMO-IMDG):

Proper shipping name	AEROSOLS
UN number	UN 1950
Class	2.2
Packing group	
Marine pollutant	No
Transport in bulk according to Annex I or II of MARPOL 73/78 and the IBC or IGC Code	Consult IMO regulations before transporting ocean bulk

Classification for AIR transport (IATA/ICAO):

Proper shipping name	Aerosols, non-flammable
UN number	UN 1950
Class	2.2
Packing group	

This information is not intended to convey all specific regulatory or operational requirements/information relating to this product. Transportation classifications may vary by container volume and may be influenced by regional or country variations in regulations. Additional transportation system information can be obtained through an authorized sales or customer service

representative. It is the responsibility of the transporting organization to follow all applicable laws, regulations and rules relating to the transportation of the material.

15. REGULATORY INFORMATION

Canadian Domestic Substances List (DSL)

All substances contained in this product are listed on the Canadian Domestic Substances List (DSL) or are not required to be listed.

16. OTHER INFORMATION

Hazard Rating System

NFPA

Health	Fire	Reactivity
1	0	0

Revision

Identification Number: 101198890 / A749 / Issue Date: 10/18/2018 / Version: 11.0

Most recent revision(s) are noted by the bold, double bars in left-hand margin throughout this document.

Legend

ACGIH	USA. American Conference of Governmental Industrial Hygienists (ACGIH) Threshold Limit Values (TLV)
Asphyxiant	Asphyxiant
BEI	Biological Exposure Indices
CA AB OEL	Canada. Alberta, Occupational Health and Safety Code (table 2: OEL)
CA BC OEL	Canada. British Columbia OEL
CA ON OEL	Ontario Table of Occupational Exposure Limits made under the Occupational Health and Safety Act.
CA QC OEL	Québec. Regulation respecting occupational health and safety, Schedule 1, Part 1: Permissible exposure values for airborne contaminants
STEL	short-term exposure limit
TWA	8-hour time weighted average
TWAEV	Time-weighted average exposure value

Information Source and References

This SDS is prepared by Product Regulatory Services and Hazard Communications Groups from information supplied by internal references within our company.

DDP SPECIALTY ELECTRONIC MATERIALS US, INC. urges each customer or recipient of this (M)SDS to study it carefully and consult appropriate expertise, as necessary or appropriate, to become aware of and understand the data contained in this (M)SDS and any hazards associated with the product. The information herein is provided in good faith and believed to be accurate as of the effective date shown above. However, no warranty, express or implied, is given. Regulatory

requirements are subject to change and may differ between various locations. It is the buyer's/user's responsibility to ensure that his activities comply with all federal, state, provincial or local laws. The information presented here pertains only to the product as shipped. Since conditions for use of the product are not under the control of the manufacturer, it is the buyer's/user's duty to determine the conditions necessary for the safe use of this product. Due to the proliferation of sources for information such as manufacturer-specific (M)SDSs, we are not and cannot be responsible for (M)SDSs obtained from any source other than ourselves. If you have obtained an (M)SDS from another source or if you are not sure that the (M)SDS you have is current, please contact us for the most current version.