



BETAPRIME™ 5504G All-in-One Primer

No shake means one less worry

- Advanced formulation BETAPRIME™ 5504G no longer requires shaking. However, shaking won't have a negative effect on the performance.
- One primer for all your priming needs, including glass, frit, bare metal, paint, any nicks and scratches in the paint, large areas of bare metal and encapsulations (RIM, PVC and PAAS)
- Simplifies the installation process and ensures the correct primer is used every time
- Reduces cost and optimizes inventory by eliminating redundant products
- Effective in treating larger bare metal areas – allows for corrosion treatment in the field
- Fast flash-off time and 14-day open life
- Works in a wide range of weather and temperatures from 0°F to 115°F (-18°C to 46°C)



BETAPRIME™ 5504G All-in-One Primer – optimizes and simplifies installation process

Replacing windshields is simpler with BETAPRIME™ 5504G All-in-One Primer. BETAPRIME™ 5504G can be used for priming auto glass and pinchwelds. Use on all common aftermarket substrates: glass, paint, nicks and scratches in the paint, large areas of bare metal and RIM, PVC and PAAS encapsulations.

Saves time and money

BETAPRIME™ 5504G All-in-One Primer saves material costs and reduces installation time because you only need to buy and apply one product. Because BETAPRIME™ 5504G can be used on virtually all substrates, it can reduce costly mistakes, such as applying the wrong primer to the wrong part.

Other time-saving advantages include that it no longer requires shaking and reduces steps for priming nicks/scratches. Priming painted bonding surfaces and nicks/scratches under 1/4" by 1/4" requires just one coat of BETAPRIME™ 5504G. It also has a fast flash off (dry) time: 2 minutes in temperatures 20°F (-7°C) and above and 6 minutes in temperatures from 20°F (-7°C) down to 0°F (-18°C). It also has a 14-day open life.

Use in a wide range of temperatures and weather

Inclement weather is much less of a problem with BETAPRIME™ 5504G All-in-One Primer. It works in both cold and warm temperatures, 0°F to 115°F (-18°C to 46°C).

Promotes strong, long-lasting bonds


Using an all-in-one, no-shake primer is not a compromise. BETAPRIME™ 5504G All-in-One Primer has been tested in thousands of applications on a wide range of windshields and with all BETASEAL™ Adhesives.



Use in a wide range of temperatures and weather

Use in a wide range of temperatures and weather. Inclement weather is much less of a problem with BETAPRIME™ 5504G All-in-One Primer. It works in both cold and warm temperatures, 0°F to 115°F (-18°C to 46°C), making it the ideal system for mobile installations.

BETAPRIME™ 5504G All-in-One Primer drying time



Easy-to-use:
Clean, prime and bond
BETAPRIME™ 5504G All-in-One Primer is part of a simple, superior system that employs BETACLEAN™ GC-800 Glass and Surface Cleaner, BETACLEAN™ Easy-Go Cleaning Sponges and all BETASEAL™ Adhesives. Just three easy steps: clean, prime and bond.

BETASEALarg.com | 1.800.453.3779 | Email: betasealarg@dupont.com



DuPont™, the DuPont Oval Logo, and all products, unless otherwise noted, denoted with ™, SM or ® are trademarks, service marks or registered trademarks of affiliates of DuPont de Nemours, Inc. © 2021 DuPont de Nemours, Inc. All rights reserved.

Form Number 001-20141-OIA1121