



Ion Exchange

Stator Cooling Circuit

The stator cooling circuit requires careful control of its chemistry (pH, dissolved oxygen, dissolved copper) in order to provide efficient cooling, little corrosion, and no deposition of corrosion products in the cooling elements. Ion exchange resins are used to control the chemistry of the loop by increasing or decreasing pH, lowering conductivity, and removing dissolved copper.

PRODUCT	FEATURES AND RECOMMENDED USES	TYPE	MATRIX	MINIMUM TOTAL VOLUME CAPACITY (eq/L)	IONIC FORM AS SHIPPED
INDIVIDUAL RESINS FOR CUSTOMIZED CHEMISTRY CONTROL¹					
DuPont™ AmberLite™ HPR550 OH	High capacity uniform particle size gel type anion resin. Paired best with AmberLite™ HPR650 H or AmberLite™ HPR1300 Na depending on the preferred operational method.	SBA	GEL	1.10	OH-
DuPont™ AmberLite™ HPR1300 Na	High capacity uniform particle size gel type cation resin.. Paired best with AmberLite™ HPR550 OH, sodium form cation is used to increase the pH of the purification loop while still removing copper and other cation impurities.	SAC	GEL	2.20	Na+
DuPont™ AmberLite™ HPR650 H	A high capacity uniform gel cation resin for removal of copper and other cation impurities and pH control. Paired best with AmberLite™ HPR550 OH and used when neutral pH is targeted.	SAC	GEL	2.00	H+
READY TO USE MIXED BEDS					
DuPont™ AmberLite™ IRN150 H/OH	Nuclear grade mixed bed composed of uniform particle size AmberLite™ IRN77 H and IRN78 OH on a 1:1 equivalent basis for full demineralization.	MB	GEL/ GEL	1.90/1.20	H+/OH-
DuPont™ AmberLite™ IRN160 H/OH	High capacity nuclear grade mixed bed composed of uniform particle size AmberLite™ IRN97 H and IRN78 OH on a 1:1 equivalent basis. Designed to minimize separation of anion and cation during installation and transfer in stator cooling applications.	MB	GEL/ GEL	2.10/1.20	H+/OH-
DuPont™ AmberLite™ IRN170 H/OH	Premium nuclear grade mixed bed composed of uniform particle size AmberLite™ IRN99 H and IRN78 OH on a 1:1 equivalent basis. Offers maximum oxidative stability and highest operating capacity to achieve the lowest ionic leakage and longest resin life.	MB	GEL/ GEL	2.50/1.20	H+/OH-
DuPont™ AmberLite™ IRN9840 Na/OH	High kinetics nuclear grade mixed bed composed of macroporous resins on a 1:1 equivalent basis. Designed to minimize separation of anion and cation during installation and provide alkaline pH control to minimize the corrosion of copper heat exchangers.	MB	MR/MR	1.70/0.85	Na+/OH-

Key:

- ¹ = The individual cation and anion must be prepared in-situ.
- SBA = Strong Base Anion
- SAC = Strong Acid Cation
- MB = Mixed Bed

Powering performance worldwide.

With a large global manufacturing footprint, strong R&D expertise and technical support services and systems, we supply high market volumes with high quality. DuPont partners with you, our customer, to understand unmet needs and develop tailored solutions.

TECHNICAL SERVICE, RESEARCH & DEVELOPMENT

Chauny, France*
Edina, MN, USA
Huzhou, China
Hyderabad, India
KAUST Jeddah, KSA
Midland, MI, USA
Shanghai, China Singapore
Tarragona, Spain*
Wilmington, DE, USA

COMMERCIAL OPERATIONS

Astana, Kazakhstan
Bangkok, Thailand
Beijing, China
Bogota, Colombia
Buenos Aires, Argentina
Budapest, Hungary
Dubai, UAE
Chengdu, China
Delhi, India
Edina, MN, USA
Guangzhou, China
HCM City, Vietnam
Hong Kong, China
Jakarta, Indonesia
Johannesburg, South Africa
Kuala Lumpur, Malaysia
Madrid, Spain

Manila, Philippine
Melbourne, Australia
Mexico City, Mexico
Midland, MI, USA
Moscow, Russia
Mumbai, India Nairobi,
Kenya
Paris, France São
Paulo, Brazil
Seoul, Republic of Korea
Pfaeffikon, Switzerland
Shanghai, China Singapore
Surubya, Indonesia Taipei,
Taiwan Tokyo, Japan
Warsaw, Poland

MANUFACTURING

Chauny, France
Edina, MN, USA
Fombio, Italy
Huzhou, China
Jubail Industry
City, Saudi
Arabia Midland,
MI, USA
Qingpu, China
Soma, Japan



Have a question? Contact us at:

www.dupont.com/water/contact-us

All information set forth herein is for informational purposes only. This information is general information and may differ from that based on actual conditions. Customer is responsible for determining whether products and the information in this document are appropriate for Customer's use and for ensuring that Customer's workplace and disposal practices are in compliance with applicable laws and other government enactments. The product shown in this literature may not be available for sale and/or available in all geographies where DuPont is represented. The claims made may not have been approved for use in all countries. Please note that physical properties may vary depending on certain conditions and while operating conditions stated in this document are intended to lengthen product lifespan and/or improve product performance, it will ultimately depend on actual circumstances and is in no event a guarantee of achieving any specific results. DUPONT ASSUMES NO OBLIGATION OR LIABILITY FOR THE INFORMATION IN THIS DOCUMENT. References to "DuPont" or the "Company" mean the DuPont legal entity selling the products to Customer unless otherwise expressly noted. NO WARRANTIES ARE GIVEN; ALL IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE ARE EXPRESSLY EXCLUDED. No freedom from infringement of any patent or trademark owned by DuPont or others is to be inferred.

DuPont™, the DuPont Oval Logo, and all trademarks and service marks denoted with ™, SM or ® are owned by affiliates of DuPont de Nemours, Inc. unless otherwise noted. © 2023 DuPont. All right reserved