

## Product Information

## High Performance

## Lubricants

# MOLYKOTE<sup>®</sup> HP-800 Grease

### Electrically conductive PFPE grease

#### FEATURES

- ◆ Good compatibility with plastics and rubber
- ◆ Wide temperature range from -30 to 250°C
- ◆ Good electric conductivity
- ◆ No negative effect on electrical contacts

#### BENEFITS

- ◆ Good electric conductivity will aid in dissipating static electricity from lubricated components

#### COMPOSITION

- ◆ Perfluoropolyether oil
- ◆ Additives

#### APPLICATIONS

Lubrication of plastic parts in automobiles, electric equipment, audio-visual equipment, precision equipment, office equipment, etc. where electrical conductivity is desired.

#### TYPICAL PROPERTIES

Specifications writers: These values are not intended for use in preparing specifications. Please contact your local Dow Corning sales representative prior to writing specifications on this product.

CTM*	ASTM/FTM/JIS*	Property	Unit	Value
		Appearance	Color	Black
	ASTM D445	Viscosity (40°C)	mm <sup>2</sup> /S	420
	JIS K 2220	Penetration (un-worked)	mm/10	230
		NLGI Class		3
		Service temperature range	°C	From -30 to 250
	JIS K 2220	Dropping point	°C	None
	FTM 791-321	Bleed (200°C/24 hours)	%	7.5
	FTM 791-321	Evaporation (200°C/24 hours)	%	0.5
		Volume resistivity (DCAL method)	Ω · cm	4x10 <sup>2</sup>

\* CTM : Corporate Test Method, copies of CTM's are available on request.

ASTM: American Society for Testing and Materials

FTM: Fed. Test Method Standard

JIS: Japanese Industrial Standards

#### HOW TO USE

Clean point of lubrication. As is usual with lubricating grease, apply or fill by means of brush, spatula, or automatic dispensing equipment.

#### HANDLING PRECAUTIONS

This product is chemically inert and non-toxic. However, decomposed gas at over 250°C is hazardous. Ventilation is required when decomposition is expected.

Product safety information required for safe use is not included. Before handling, read product and safety data sheets and container labels for safe use, physical and health hazard information. The material safety data sheet is available on the Dow Corning website at [www.molykote.com](http://www.molykote.com). You can also obtain a copy from your local Dow Corning sales representative or Distributor or by calling your local Dow Corning Global Connection.

## **USABLE LIFE AND STORAGE**

When stored in unopened containers, this product has a usable life of 36 months from the date of production.

## **PACKAGING**

This product is available in 500g

## **LIMITATIONS**

This product is neither tested nor represented as suitable for medical or pharmaceutical uses.

## **HEALTH AND ENVIRONMENTAL INFORMATION**

To support Customers in their product safety needs, Dow Corning has an extensive Product Stewardship organization and a team of Product Safety and Regulatory Compliance (PS&RC) specialists available in each area.

For further information, please see our website, [www.dowcorning.com](http://www.dowcorning.com) or consult your local Dow Corning representative.

## **LIMITED WARRANTY INFORMATION - PLEASE READ CAREFULLY**

The information contained herein is offered in good faith and is believed to be accurate. However, because conditions and methods of use of our products are beyond our control, this information should not be used in substitution for customer's tests to ensure that Dow Corning's products are safe, effective, and fully satisfactory for the intended end use. Suggestions of use shall not be taken as inducements to infringe any patent.

Dow Corning's sole warranty is that the product will meet the Dow Corning sales specifications in effect at the time of shipment.

Your exclusive remedy for breach of such warranty is limited to refund of purchase price or replacement of any product shown to be other than as warranted.

**DOW CORNING SPECIFICALLY DISCLAIMS ANY OTHER EXPRESS OR IMPLIED WARRANTY OF FITNESS FOR A PARTICULAR PURPOSE OR MERCHANTABILITY.**

**DOW CORNING DISCLAIMS LIABILITY FOR ANY INCIDENTAL OR CONSEQUENTIAL DAMAGES.**

## **WEBSITE GUIDE**

For more information on our company and how to contact us, visit our website, [www.molykote.com](http://www.molykote.com).

*We help you invent the future.™*