



Home Innovation
NGBS GREEN CERTIFIED™

THIS IS TO SIGNIFY THAT THE FOLLOWING
PRODUCTS FOR RESIDENTIAL CONSTRUCTION

**DUPONT™ FLEXWRAP™ NF, STRAIGHTFLASH™,
STRAIGHTFLASH™ VF, DUPONT™ FLASHING TAPE**

MANUFACTURED BY

DUPONT BUILDING INNOVATIONS

HAVE BEEN CERTIFIED FOR POINTS TOWARD NGBS GREEN
CERTIFICATION TO THE ICC 700 NATIONAL GREEN BUILDING
STANDARD AS DETAILED IN NGBS GREEN CERTIFIED PRODUCT
REPORT #NGBSGCP-00042.

Thomas M. Kenney, P.E. – VP Research & Engineering

June 17, 2009

Approval Date

May 31, 2017

Expiration Date

CERTIFICATE #00042

This certificate is not a representation, warranty, or guarantee of product performance or certification of code compliance. For details of the product warranty, consult the product manufacturer.



Home Innovation
NGBS GREEN CERTIFIED™

NGBS Green Certified Product Report #NGBSGCP-00042

Products: DuPont™ Flexwrap™ NF, StraightFlash™, StraightFlash™ VF, DuPont™ Flashing Tape

Manufacturer: DuPont Building Innovations

The product(s) shown on this report have been independently verified as eligible products for use in achieving points toward project certification under ICC-700 National Green Building Standard. Home Innovation Research Labs authorizes accredited verifiers to award points toward certification without additional documentation when the product(s) is used as noted below.

2008 NATIONAL GREEN BUILDING STANDARD			
PRACTICE #	PRACTICE DESCRIPTION	POTENTIAL POINTS AVAILABLE	ADDITIONAL CONDITIONS OF USE TO AWARD POINTS
2008 NGBS 602.12	Flashing details on plans & installed at ALL as applicable: exterior fenestrations/doors; roof valleys; deck/balcony intersections; roof/wall & roof/chimney intersections; drip cap above windows/doors not flashed or protected by overhangs.	6	Flashing details must be shown on plans and product installed per plans.
2008 NGBS 701.4.3.3(1)	Windows and doors: Caulking, gasketing, flashing tape, foam sealant, or weatherstripping forms a complete air barrier. Mandatory for certification.	Mandatory	Product must be installed per manufacturer's instructions and building plans.

2012 NATIONAL GREEN BUILDING STANDARD			
PRACTICE #	PRACTICE DESCRIPTION	POTENTIAL POINTS AVAILABLE	ADDITIONAL CONDITIONS OF USE TO AWARD POINTS
2012 NGBS 602.1.9(2)	All window head and jamb flashing is self-adhered flashing complying with AAMA 711-07.	2	Flashing details must be shown on plans and product installed per plans.
2012 NGBS 701.4.3.1.(c)	The building envelope is durably sealed to limit air infiltration at openings between window and door assemblies and their respective jambs and framing.	Mandatory	Product must be installed per manufacturer's instructions and building plans.