



DUPONT™ TYVEK®  
FLUID APPLIED WB

BUMP OUT FRAMING

DUPONT™ TYVEK® FLUID  
APPLIED FLASHING AND  
JOINT COMPOUND  
(FILLET BREAD, 1/2" ONTO  
EACH SURFACE) \*

CAVITY SEAL

BRICK VENEER

BACKER ROD AND  
SEALANT BY OTHERS

WINDOW FRAME

DUPONT™ TYVEK® FLUID APPLIED  
FLASHING AND JOINT COMPOUND  
(2" ONTO FACE OF WALL)

DUPONT™ SEALANT FOR TYVEK®  
FLUID APPLIED SYSTEM  
(USE BACKER ROD AS NECESSARY)

GYPSUM BOARD

CMU WALL

**NOTE**

- 1) INTERIOR VAPOR RETARDER MAY BE REQUIRED IN SOME REGIONS.
- 2) THIS INFORMATION IS PROVIDED BY DUPONT AS REFERENCE ONLY; PLEASE CONSULT LOCAL BUILDING CODES, REGULATIONS AND LAWS TO DETERMINE THE APPROPRIATE CONSTRUCTION METHODS AND MATERIALS NEEDED.

\* DUPONT™ SEALANT FOR TYVEK® FLUID APPLIED SYSTEM OR  
DUPONT™ TYVEK® FLUID APPLIED FLASHING AND JOINT COMPOUND MAY BE USED.



**Tyvek.**  
FLUID APPLIED WB

SCALE: NOT TO SCALE

REVISION DATE: 4/28/10

DRAWING: FA-B-W104j

**BUMP OUT WINDOW JAMB - METHOD 1**  
BRICK VENEER / CMU WALL / FLUID APPLIED FLASHING