



DUPONT™ TYVEK® FLUID APPLIED FLASHING AND JOINT COMPOUND (2" ONTO FACE OF WALL)

DUPONT™ SEALANT FOR TYVEK® FLUID APPLIED SYSTEM (USE BACKER ROD AS NECESSARY)

WINDOW FRAME

BACKER ROD AND SEALANT BY OTHERS

DUPONT™ STRAIGHTFLASH™

DUPONT™ TYVEK® FLUID APPLIED WB

STEEL STUD WALL

EXTERIOR GYPSUM BOARD

BRICK VENEER

GYPSUM BOARD

BATT INSULATION

NOTE

- 1) INTERIOR VAPOR RETARDER MAY BE REQUIRED IN SOME REGIONS.
- 2) THIS INFORMATION IS PROVIDED BY DUPONT AS REFERENCE ONLY; PLEASE CONSULT LOCAL BUILDING CODES, REGULATIONS AND LAWS TO DETERMINE THE APPROPRIATE CONSTRUCTION METHODS AND MATERIALS NEEDED.



Tyvek.
FLUID APPLIED WB

SCALE: NOT TO SCALE

REVISION DATE: 4/28/10

DRAWING: FA-B-W200s

STOREFRONT WINDOW SILL - METHOD 1
BRICK VENEER / STEEL STUD WALL / FLUID APPLIED FLASHING