



DUPONT™ SEALANT FOR TYVEK®  
 FLUID APPLIED SYSTEM  
 (USE BACKER ROD AS NECESSARY)

DUPONT™ TYVEK® FLUID APPLIED  
 FLASHING AND JOINT COMPOUND  
 (2" ONTO FACE OF WALL)

WINDOW FRAME

SEALANT  
 BY OTHERS

GYPSUM BOARD

BATT INSULATION

STEEL STUD WALL

DUPONT™  
 STRAIGHTFLASH™

DUPONT™ TYVEK®  
 FLUID APPLIED WB

BRICK VENEER

EXTERIOR GYPSUM  
 BOARD

**NOTE**

- 1) INTERIOR VAPOR RETARDER MAY BE REQUIRED IN SOME REGIONS.
- 2) THIS INFORMATION IS PROVIDED BY DUPONT AS REFERENCE ONLY; PLEASE CONSULT LOCAL BUILDING CODES, REGULATIONS AND LAWS TO DETERMINE THE APPROPRIATE CONSTRUCTION METHODS AND MATERIALS NEEDED.



**Tyvek.**  
 FLUID APPLIED WB

SCALE: NOT TO SCALE  
 REVISION DATE: 4/28/10  
 DRAWING: FA-B-W202s

**FLANGED WINDOW SILL - METHOD 1**  
 BRICK VENEER / STEEL STUD WALL / FLUID APPLIED FLASHING