



GYPSUM BOARD
 BATT INSULATION
 STEEL STUD WALL

BRICK VENEER
 MINERAL FIBER INSULATION (VAPOR PERMEABLE)
 EXTERIOR GYPSUM BOARD
 DUPONT™ SEALANT FOR TYVEK® FLUID APPLIED SYSTEM *
 MECHANICAL FASTENER
 DUPONT™ TYVEK® FLUID APPLIED WB
 DUPONT™ TYVEK® FLUID APPLIED FLASHING AND JOINT COMPOUND (1" MIN. ONTO EACH SURFACE)
 END DAM
 DUPONT™ THRU-WALL FLASHING WITH 1/4" DRIP EDGE
 LOOSE-LAID STEEL LINTEL
 SEALANT BY OTHERS
 WINDOW FRAME

DUPONT™ TYVEK® FLUID APPLIED FLASHING AND JOINT COMPOUND (2" ONTO FACE OF WALL)
 DUPONT™ SEALANT FOR TYVEK® FLUID APPLIED SYSTEM (USE BACKER ROD AS NECESSARY)

NOTE
 1) INTERIOR VAPOR RETARDER MAY BE REQUIRED IN SOME REGIONS.
 2) THIS INFORMATION IS PROVIDED BY DUPONT AS REFERENCE ONLY; PLEASE CONSULT LOCAL BUILDING CODES, REGULATIONS AND LAWS TO DETERMINE THE APPROPRIATE CONSTRUCTION METHODS AND MATERIALS NEEDED.
 * DUPONT™ SEALANT FOR TYVEK® FLUID APPLIED SYSTEM OR DUPONT™ TYVEK® FLUID APPLIED FLASHING AND JOINT COMPOUND MAY BE USED.

SCALE: NOT TO SCALE
 REVISION DATE: 4/28/10
 DRAWING: FA-BX-W202h

FLANGED WINDOW HEAD - METHOD 1
 BRICK VENEER / EXTERIOR INSULATION / STEEL STUD WALL / FLUID APPLIED FLASHING

