



GYPSUM BOARD

BATT INSULATION

STEEL STUD WALL

BRICK VENEER

MINERAL FIBER INSULATION (VAPOR PERMEABLE)

EXTERIOR GYPSUM BOARD

DUPONT™ SEALANT FOR TYVEK® FLUID APPLIED SYSTEM *

MECHANICAL FASTENER

DUPONT™ TYVEK® FLUID APPLIED WB

DUPONT™ TYVEK® FLUID APPLIED FLASHING AND JOINT COMPOUND (1" MIN. ONTO EACH SURFACE)

END DAM

DUPONT™ THRU-WALL FLASHING WITH 1/4" DRIP EDGE

LOOSE-LAID STEEL LINTEL

SEALANT BY OTHERS

WINDOW FRAME

DUPONT™ FLEXWRAP™ NF or DUPONT™ STRAIGHTFLASH™ (2" ONTO FACE OF WALL)

DUPONT™ SEALANT FOR TYVEK® FLUID APPLIED SYSTEM (USE BACKER ROD AS NECESSARY)

NOTE

1) INTERIOR VAPOR RETARDER MAY BE REQUIRED IN SOME REGIONS.
 2) THIS INFORMATION IS PROVIDED BY DUPONT AS REFERENCE ONLY; PLEASE CONSULT LOCAL BUILDING CODES, REGULATIONS AND LAWS TO DETERMINE THE APPROPRIATE CONSTRUCTION METHODS AND MATERIALS NEEDED.

* DUPONT™ SEALANT FOR TYVEK® FLUID APPLIED SYSTEM OR DUPONT™ TYVEK® FLUID APPLIED FLASHING AND JOINT COMPOUND MAY BE USED.



Tyvek.
 FLUID APPLIED WB

SCALE: NOT TO SCALE
 REVISION DATE: 4/28/10
 DRAWING: FA-BX-W203h

FLANGED WINDOW HEAD - METHOD 2
 BRICK VENEER / EXTERIOR INSULATION / STEEL STUD WALL / SELF-ADHERED FLASHING