



DUPONT™ TYVEK®

DUPONT™ TYVEK®
STUCCOWRAP®

WOOD SHEATHING

BATT INSULATION

GYPSUM BOARD

WOOD STUD WALL

WOOD TRIM

STUCCO

WIRE LATH

DUPONT™ STRAIGHTFLASH™
(2" ONTO STUCCOWRAP®)

DUPONT™ TYVEK®
FLUID APPLIED FLASHING -
BRUSH FORMULATION

SEALANT
BY OTHERS

CASING BEAD

DUPONT™ SEALANT FOR
TYVEK® FLUID APPLIED SYSTEM

WINDOW FRAME

DUPONT™ SEALANT FOR TYVEK®
FLUID APPLIED SYSTEM
(USE BACKER ROD AS NECESSARY)

NOTE

- 1) INTERIOR VAPOR RETARDER MAY BE REQUIRED IN SOME REGIONS.
- 2) THIS INFORMATION IS PROVIDED BY DUPONT AS REFERENCE ONLY; PLEASE CONSULT LOCAL BUILDING CODES, REGULATIONS AND LAWS TO DETERMINE THE APPROPRIATE CONSTRUCTION METHODS AND MATERIALS NEEDED.

SCALE: NOT TO SCALE
REVISION DATE: 9/14/10
DRAWING: FA-S-W300j

RECESSED WINDOW JAMB
STUCCO / WOOD STUD WALL / FLUID APPLIED FLASHING



Tyvek.
FLUID APPLIED WB