



DUPONT™ TYVEK®

DUPONT™ TYVEK®  
STUCCOWRAP®

WOOD SHEATHING

BATT INSULATION

GYPSUM BOARD

WOOD STUD WALL

WOOD TRIM

STUCCO

WIRE LATH

DUPONT™ STRAIGHTFLASH™  
(2" ONTO STUCCOWRAP®)

DUPONT™ TYVEK®  
FLUID APPLIED FLASHING -  
BRUSH FORMULATION

SEALANT  
BY OTHERS

CASING BEAD

DUPONT™ SEALANT FOR  
TYVEK® FLUID APPLIED SYSTEM

WINDOW FRAME

DUPONT™ SEALANT FOR TYVEK®  
FLUID APPLIED SYSTEM  
(USE BACKER ROD AS NECESSARY)

**NOTE**

- 1) INTERIOR VAPOR RETARDER MAY BE REQUIRED IN SOME REGIONS.
- 2) THIS INFORMATION IS PROVIDED BY DUPONT AS REFERENCE ONLY; PLEASE CONSULT LOCAL BUILDING CODES, REGULATIONS AND LAWS TO DETERMINE THE APPROPRIATE CONSTRUCTION METHODS AND MATERIALS NEEDED.

SCALE: NOT TO SCALE  
 REVISION DATE: 9/14/10  
 DRAWING: FA-S-W300j

**RECESSED WINDOW JAMB**  
 STUCCO / WOOD STUD WALL / FLUID APPLIED FLASHING



**Tyvek.**  
 FLUID APPLIED WB