

DuPont™ Cyrel® DVS

Solvent Process Digital Plate for Varnishing



DuPont™ Cyrel® DVS

[DuPont Packaging Graphics](#) continues to be a global technology leader in the development and supply of flexographic printing systems. Our R&D team continues to develop innovative new solutions to help our customers expand their business by taking advantage of new and profitable opportunities in the growing flexographic packaging market. The DuPont Packaging Graphics portfolio of products includes DuPont™ Cyrel® brand photopolymer plates ([analog](#) and [digital](#)), [Cyrel® platemaking equipment](#), [Cyrel® round sleeves](#), Cyrel® plate mounting systems and the revolutionary [Cyrel® FAST thermal system](#).

DuPont™ Cyrel® Systems: Higher quality at high speed.

The DuPont™ Cyrel® DVS plates are ideal for varnishing and special effect ink and coatings applications.

DuPont™ Cyrel® DVS

Applications

These photopolymer plates offer high quality print finishing on folding cartons, such as food packaging, cigarettes, cosmetics, etc. They are also used in commercial printing for spot coating of catalogs, calendars, books and brochures.

Cyrel® DVS plates can be used for inline and offline coating of:

- Aqueous coating
- UV-Lacquer
- Metallic ink
- DuPont™ Iriodin® pigmented ink

Product Features

- Excellent coating and ink transfer permits superior coating
- High resolution and exact register results in fine detail and complex forms can be spot coated and printed in the coating tower
- High durability for long print runs
- Image relief is clean and sharp
- Can be used again and again without any loss of registration

Printing Ink and Solvent Compatibility

Cyrel® DVS plates offer excellent compatibility with UV-lacquers and water-based inks. The enforced polyester base will maintain accurate registration even with large plates.



Download latest version

DuPont™ Cyrel® DVS

Solvent Process Digital Plate for Varnishing

Process of Use

Expose the plate through the back to establish the floor and maximize sensitivity. Back exposure varies according to relief required. Remove the protective coversheet, and image the plate with the Cyrel® Digital Imager (CDI). Expose the front of the plate surface. Process the plate in the Cyrel® solvent processor to remove unexposed polymer. Finish the plate in a light finisher to eliminate surface tackiness.

Mounting

Cyrel® Microflex mounting devices are recommended for mounting Cyrel® DVS plates. The double sided adhesive should first be applied to the cylinder or sleeve – not the plate – to ensure easier and precise laydown. The polyester base will maintain accurate register even with large plates.

Storage – Raw Material

Store unexposed plates in a cool area (4–32°C, 40–90°F), away from direct sources of heat. Humidity control is not required. Cyrel® DVS is foam interleaved to provide maximum protection of the plate after manufacture, and during transportation and storage. Plates should be stacked flat. Plates should not be exposed to direct sunlight or excessive white light. Continuous exposure to very high ozone concentrations should be avoided.

www.cyrel.dupont/na

Handling – Raw Material

Like all photopolymer plates, Cyrel® DVS plates should be handled under UV free light; e.g. fluorescent tubes covered with amber sleeves.

Technical Data	
	Cyrel® DVS Thickness 1,14 mm / 0,045"
Durometer	73 Sh A
Image Reproduction	1–98% / 60 L/cm
Minimum Positive Line Width	0,050 mm / 2 mil
Minimum Isolated Dot Size	200 µm
Relief Depth	0,55 mm / 0,022"
Processing	Solvent / Digital

Storage – Finished Plates

After printing, plates should be thoroughly cleaned with a compatible solvent before storing. They may be stored on cylinders, sleeves or demounted and stored flat.

For more information on DuPont™ Cyrel® or other DuPont Packaging Graphics products, please contact your local representative:

United States

DuPont Packaging Graphics
Chestnut Run Plaza, Bldg. 702
974 Centre Road
Wilmington, DE 19805
800-345-9999

Canada

DuPont Packaging Graphics
1919 Minnesota Court
Mississauga, ON L5N 0C9
Canada
905-816-3238