

DuPont Automotive

Innovation Spotlight: DuPont™ Hytrel®



Six-speed Transmission Baffle Assembly

Application

A thermoplastic elastomer (TPE) single-assembly, six-speed transmission baffle assembly, replacing the incumbent cast aluminum and rubber baffle material. Developed by the Ford Motor Company for use on its 2018 Ford Focus.

Unmet Need

Material improvements to transmission baffle assembly components offer opportunities for weight reduction, cost reduction and improved fuel efficiency, as well as noise, vibration and harshness (NVH) improvements.

Challenges

- Ability to seal against cast aluminum surfaces.
- Improved ease of assembly.
- Significant design constraints, including tight dimensional tolerances.

Solution

The part was produced using a one-step injection molding process, enabling integrated seal elements capable of sealing with a cast surface. Snap-fit assembly behavior allows the part to effectively seal five areas.

The baffle assembly:

- Enables reduced chain and gear sprocket drag
- Improves fuel economy
- Enhances fluid passage to the sump for reduced pump whine noise
- Reduces costs by approximately \$1.00 per vehicle versus incumbent material
- Reduces weight by 220g (> 50%) over current design

DuPont Material Chosen and Why

DuPont™ Hytrel® was chosen for this application because it offers:

- Toughness and resilience
- Creep resistance
- Wide temperature range
- Resistance to transmission chemicals



For more information on the Assisted Positive Locking Junction Box and other SPE award winners and finalists, visit the [SPE Automotive Innovation Awards website](#).

Contact DuPont at the following regional locations:

North America

800-222-8377

Europe, Middle East, Africa

+41-22-717-51-11

ASEAN

+65-6586-3688

Latin America

+0800-17-17-15

Greater China

+86-400-8851-888

Japan

+81-3-5521-2801

Visit us at automotive.dupont.com

The information provided in this data sheet corresponds to our knowledge on the subject at the date of its publication. This information may be subject to revision as new knowledge and experience become available. The data provided fall within the normal range of product properties and relate only to the specific material designated; these data may not be valid for such material used in combination with any other materials, additives or pigments or in any process, unless expressly indicated otherwise.

The data provided should not be used to establish specification limits or used alone as the basis of design; they are not intended to substitute for any testing you may need to conduct to determine for yourself the suitability of a specific material for your particular purposes. Since DuPont cannot anticipate all variations in actual end-use and disposal conditions, DuPont does not guarantee favorable results, makes no warranties and assumes no liability in connection with any use of this information. All such information is given and accepted at the buyer's risk. It is intended for use by persons having technical skill, at their own discretion and risk. Nothing in this publication is to be considered as a license to operate under or a recommendation to infringe any patent. DuPont advises you to seek independent counsel for a freedom to practice opinion on the intended application or end-use of our products.

CAUTION: Do not use DuPont materials in medical applications involving implantation in the human body or contact with internal body fluids or tissues unless the material has been provided from DuPont under a written contract that is consistent with DuPont policy regarding medical applications and expressly acknowledges the contemplated use. For further information, please contact your DuPont representative. You may also request a copy of DuPont POLICY Regarding Medical Applications H-50103-5 and DuPont CAUTION Regarding Medical Applications H-50102-5.

Copyright © 2017 DuPont. All rights reserved. The DuPont Oval Logo, DuPont™ and Hytrel® are trademarks or registered trademarks of E.I. du Pont de Nemours and Company or its affiliates. (12/17) GNE-A11226-00-A0217