

# DuPont 7082

CARBON CONDUCTOR

## Technical Data Sheet

### Product Description

DuPont 7082 carbon conductor may be used as a polymer thick film resistor. It can also function as a conductor in designs that tolerate high resistivity. Its major benefits include low cost and excellent screen life. It can be used with semiautomatic and manual printers. DuPont 7082 Carbon conductor has been designed for applications requiring small resistance changes.

### Product Benefits

- High resistance

### Processing

- **Screen Printing Equipment**  
Semiautomatic or manual
- **Screen Types**  
Polyester, stainless steel
- **Typical Cure Conditions**  
Box Oven: 120°C for 10 minutes
- **Typical Circuit Line Thickness Printed with 325-mesh stainless steel screen**  
7 - 14 microns
- **Clean-up Solvent**  
Ethylene glycol diacetate

### Storage and Shelf Life

Containers should be stored, tightly sealed, in a clean, stable environment at room temperature (<25°C). Shelf life of material in unopened containers is six months from date of shipment. Some settling of solids may occur and compositions should be thoroughly mixed prior to use.

**Table 1**  
**Typical Physical Properties**


Test	Properties
Sheet Resistivity (k $\Omega$ /sq/0.4 mil) or (ohm/sq/mil)	1.0 400
Adhesion/Tape Pull (3M Scotch Tape #600)	No material transfer
Abrasion Resistance, Pencil Hardness (ASTM D3363-74) (H)	> 2
<b>Table 2</b> <b>Composition Properties</b>	
Viscosity (Pa.S) [Brookfield HBTD, 5rp, #14 spindle, 25°C)	210 - 260
Thinner	DuPont 3610

Table 1 & 2 show anticipated typical physical properties for DuPont 7082 based on specific controlled experiments in our labs and are not intended to represent the product specifications, details of which are available upon request.

### Safety and Handling

For Safety and Handling information pertaining to this product, read the Material Safety Data Sheet (MSDS).

**Blending for Value**  
**7082/5036 Blend Curve**  
**(1,000  $\Omega$ – 550,000  $\Omega$ /sq@14ums)**



Copyright © 2009 DuPont. All rights reserved. The DuPont Oval, DuPont™, The miracles of science™, Green Tape™ and all products or words denoted with © or ™ are registered trademarks or trademarks of E. I. du Pont de Nemours and Company or its affiliates (“DuPont”). NO PART OF THIS MATERIAL MAY BE REPRODUCED, STORED IN A RETRIEVAL SYSTEM OR TRANSMITTED IN ANY FORM OR BY ANY MEANS ELECTRONIC, MECHANICAL, PHOTOCOPYING, RECORDING OR OTHERWISE WITHOUT THE PRIOR WRITTEN PERMISSION OF DUPONT.

Caution: Do not use in medical applications involving implantation in the human body or contact with internal body fluids or tissue unless the product is provided by DuPont under a formal written contract consistent with the DuPont Policy Regarding Medical Applications of DuPont Materials H-50103-2 (“Medical Applications Policy”) and which expressly acknowledges the contemplated use. For additional information, please request a copy of DuPont Medical Caution Statement H-50102-2 and the DuPont Medical Applications Policy.

The information provided herein is offered for the product user’s consideration and examination. While the information is based on data believed to be reliable, DuPont makes no warranties, expressed or implied as to the data’s accuracy or reliability and assumes no liability arising out of its use. The data shown are the result of DuPont laboratory experiments and are intended to illustrate potential product performance within a given experimental design under specific, controlled laboratory conditions. While the data provided herein falls within anticipated normal range of product properties based on such experiments, it should not be used to establish specification limits or used alone as the basis of design. It is the product user’s responsibility to satisfy itself that the product is suitable for the user’s intended use. Because DuPont neither controls nor can anticipate the many different end-uses and end-use and processing conditions under which this information and/or the product described herein may be used, DuPont does not guarantee the usefulness of the information or the suitability of its products in any given application. Users should conduct their own tests to determine the appropriateness of the products for their particular purpose.

The product user must decide what measures are necessary to safely use the product, either alone or in combination with other products, also taking into consideration the conditions of its facilities, processes, operations, and its environmental, health and safety compliance obligations under any applicable laws.

This information may be subject to revision as new knowledge and experience become available. This publication is not to be taken as a license to operate under, or recommendation to infringe any patent.



*The miracles of science™*

For more information on DuPont 7082 or other DuPont Microcircuit Materials products, please contact your local representative:

Americas

DuPont Microcircuit Materials  
 14 T.W. Alexander Drive  
 Research Triangle Park, NC 27709  
 Tel.: 800-284-3382

Europe

Du Pont (U.K.) Limited  
 Coldharbour Lane  
 Bristol BS16 1QD  
 U.K.  
 Tel.: 44-117-931-3191

Asia

DuPont Kabushiki Kaisha  
 Sanno Park Tower, 11-1  
 Nagata-cho 2-chome  
 Chiyoda-ku, Tokyo 100-611  
 Japan  
 Tel.: 81-3-5521-8650

DuPont Taiwan Ltd  
 45, Hsing-Pont Road,  
 Taoyuan, Taiwan 330  
 Tel.: 886-3-377-3616

DuPont China Holding Co. Ltd  
 Bldg 11, 399 Keyuan Rd., Zhangji Hi-Tech Park,  
 Pudong New District, Shanghai 201203, China  
 Tel.: 86-21-6386-6366 ext.2202

DuPont Korea Inc.  
 3~5th Floor, Asia tower #726,  
 Yeoksam-dong, Gangnam-gu  
 Seoul 135-719, Korea  
 Tel.: 82-10-6385-5399

E. I. DuPont India Private Limited  
 7th Floor, Tower C, DLF Cyber Greens,  
 Sector-25A, DLF City, Phase-III,  
 Gurgaon 122 002 Haryana, India  
 Tel.: 91-124-4091818

Du Pont Company (Singapore) Pte Ltd  
 1 HarbourFront Place, #11-01  
 HarbourFront Tower One,  
 Singapore 098633  
 Tel.: 65-6586-3022

<http://mcm.dupont.com>