

DuPont™ LuxPrint® 8153

ELECTROLUMINESCENT MATERIAL

Technical Data Sheet

Product Description

DuPont™ LuxPrint® 8153 electroluminescent material is designed for use with the DuPont Electroluminescent (EL) system for manufacturing screen-printed EL lamps. Barium titanate-filled LuxPrint® 8153 provides reliable electrical isolation and high dielectric constant to isolate EL Phosphors from the rear electrode. Its low affinity for moisture facilitates high light output.

Product Benefits

- Reliable electrical insulation
- Compatible with the DuPont™ Luxprint® EL System
- Low affinity for moisture
- High dielectric constant for high light output

Processing

Screen Printing Equipment

Semi-automatic and manual printers

Substrates

Polyester Film, ITO-Polyester, DuPont EL conductors and Phosphors, Glass

Screen Types

Stainless steel: 230 mesh
Polyester: 77T-62T
20 - 25µm emulsion

Typical Cure Conditions

Box oven: 130°C/10 min

Residence Time on Screen

2 hours

Clean up Solvent

Ethylene diacetate

Table 1
Exemplary Physical Properties
on 125µm Polyester Film

Test	Properties
Dry Layer Thickness (µm)	18 - 20
Breakdown Voltage (V/25µm)	> 500
Dielectric Constant (including phosphor)	8
Dielectric Constant (8153 only)	35
Coverage (cm ² /g/2 layers)*	> 120
Table 2 Composition Properties	
Viscosity (Pa.s) [Brookfield ½RVT/spindle #14 @ 10rpm, 25°C]	10 - 20
Solids (150°C)(%)	65 - 69
Thinner	DuPont 8210
* A minimum of 2 prints is recommended	

Table 1 & 2 show anticipated typical physical properties for LuxPrint® 8153 based on specific controlled experiments in our labs and are not intended to represent the product specifications, details of which are available upon request.

General

Yield and performance will depend to a large degree on the care exercised during processing, particularly in screen printing. Scrupulous care should be taken to keep the composition, printing screens and other tools free of metal contamination. Dust, lint and other particulate matter may also contribute to poor yields.

* For further information, please see Luxprint® Processing guide

Printing

Lay-down of the dielectric layer is critical to the integrity and quality of the EL lamps. The process should aim for total dry film thickness of at least 12µm per print over the thickest phosphor particle, and at least two printing passes should be employed to achieve a total minimum thickness of 25µm. Optimization of this process step will provide best reliability and light output. Printing should be performed in a clean and well ventilated area. Note: optimum printing characteristics are generally achieved in the room temperature range of 20° C-23°C. It is therefore important that the composition, in its container, is at this temperature prior to commencement of printing.

Thinner

This composition is optimized for printing, thinning is not normally required. Use the DuPont recommended thinner for slight adjustments to viscosity or to replace evaporation losses. The use of too much thinner or the use of a non recommended thinner may affect the rheological behavior of the material and its printing characteristics.

Compatibility

DuPont™ LuxPrint® 8153 electroluminescent material is fully compatible with other members of the DuPont LuxPrint® System and should be employed together with the recommended phosphors and conductors. While DuPont has tested this composition with the specified materials and under the recommended processing conditions, it is impossible or impractical to cover every combination of materials, customer processing conditions and circuit layouts. It is therefore essential that customers thoroughly evaluate the material in their specific situations in order to completely satisfy themselves with the overall quality and suitability of the composition for its intended application (s).

Storage and Shelf Life

Containers should be stored, tightly sealed, in a clean, stable environment at room temperature (<25°C). Shelf life of material in unopened containers is six months from date of shipment. Some settling of solids may occur and compositions should be thoroughly mixed prior to use.

Safety and Handling

For Safety and Handling information pertaining to this product, read the Material Safety Data Sheet (MSDS).

For more information on DuPont™ LuxPrint® 8153 or other DuPont Microcircuit Materials products, please contact your local representative:

Americas

DuPont Microcircuit Materials
14 T.W. Alexander Drive
Research Triangle Park, NC 27709
Tel.: 800-284-3382

Europe

Du Pont (U.K.) Limited
Coldharbour Lane
Bristol BS16 1QD
U.K.
Tel.: 44-117-931-3191

Asia

DuPont Kabushiki Kaisha
Sanno Park Tower, 11-1
Nagata-cho 2-chome
Chiyoda-ku, Tokyo 100-611
Japan
Tel.: 81-3-5521-8650

DuPont Taiwan Ltd
45, Hsing-Pont Road,
Taoyuan, Taiwan 330
Tel.: 886-3-377-3616

DuPont China Holding Co. Ltd
Bldg 11, 399 Keyuan Rd., Zhangji Hi-Tech Park,
Pudong New District, Shanghai 201203, China
Tel.: 86-21-6386-6366 ext.2202

DuPont Korea Inc.
3~5th Floor, Asia tower #726,
Yeoksam-dong, Gangnam-gu
Seoul 135-719, Korea
Tel.: 82-10-6385-5399

E. I. DuPont India Private Limited
7th Floor, Tower C, DLF Cyber Greens,
Sector-25A, DLF City, Phase-III,
Gurgaon 122 002 Haryana, India
Tel.: 91-124-4091818

Du Pont Company (Singapore) Pte Ltd
1 HarbourFront Place, #11-01
HarbourFront Tower One,
Singapore 098633
Tel.: 65-6586-3022

<http://www.mcm.dupont.com>



The miracles of science™

Copyright © 2009 DuPont. All rights reserved. The DuPont Oval, DuPont™, The miracles of science™, Green Tape™ and all products or words denoted with ® or ™ are registered trademarks or trademarks of E. I. du Pont de Nemours and Company or its affiliates (“DuPont”).
NO PART OF THIS MATERIAL MAY BE REPRODUCED, STORED IN A RETRIEVAL SYSTEM OR TRANSMITTED IN ANY FORM OR BY ANY MEANS ELECTRONIC, MECHANICAL, PHOTOCOPYING, RECORDING OR OTHERWISE WITHOUT THE PRIOR WRITTEN PERMISSION OF DUPONT.

Caution: Do not use in medical applications involving implantation in the human body or contact with internal body fluids or tissue unless the product is provided by DuPont under a formal written contract consistent with the DuPont Policy Regarding Medical Applications of DuPont Materials H-50103-2 (“Medical Applications Policy”) and which expressly acknowledges the contemplated use. For additional information, please request a copy of DuPont Medical Caution Statement H-50102-2 and the DuPont Medical Applications Policy.

The information provided herein is offered for the product user’s consideration and examination. While the information is based on data believed to be reliable, DuPont makes no warranties, expressed or implied as to the data’s accuracy or reliability and assumes no liability arising out of its use. The data shown are the result of DuPont laboratory experiments and are intended to illustrate potential product performance within a given experimental design under specific, controlled laboratory conditions. While the data provided herein falls within anticipated normal range of product properties based on such experiments, it should not be used to establish specification limits or used alone as the basis of design. It is the product user’s responsibility to satisfy itself that the product is suitable for the user’s intended use. Because DuPont neither controls nor can anticipate the many different end-uses and end-use and processing conditions under which this information and/or the product described herein may be used, DuPont does not guarantee the usefulness of the information or the suitability of its products in any given application. Users should conduct their own tests to determine the appropriateness of the products for their particular purpose.

The product user must decide what measures are necessary to safely use the product, either alone or in combination with other products, also taking into consideration the conditions of its facilities, processes, operations, and its environmental, health and safety compliance obligations under any applicable laws.

This information may be subject to revision as new knowledge and experience become available. This publication is not to be taken as a license to operate under, or recommendation to infringe any patent.



The miracles of science™

MCM8153 (10/2009)