

DUPONT™ VESPEL® SF

HIGH TEMPERATURE POLYIMIDE FOAM IMPROVES PERFORMANCE AND REDUCES FUEL CONSUMPTION IN AEROSPACE APPLICATIONS

Applications

Vespel® SF custom parts are ideal candidates for aerospace applications in which temperature resistance, weight, dampening, and sealing are of concern. Due to the unique properties of Vespel® SF, it has been used in the aerospace industry to solve an array of problems including specific applications in stator vane seals, variable bushing packing, nacelle insulation, abrasable seals, and reinforced composite panels.

Challenges

- Isolating systems of varying pressures
- Insulation from temperature variations
- Environments where operating temperatures can exceed 300 °C (572 °F)
- Weight reduction
- Acoustic and dampening isolation
- Provide light weight structural stability
- Seals/coating systems that are easily maintained in the field, thus extending MTBR and reducing cost

Solution

- Vespel® SF is a unique open-cell high performance custom densified polyimide foam which has been produced at varying densities ranging from approximately 0.16–0.56 g/cc (10–35 lb/ft³) to suit the most demanding aerospace applications. (Figure 4)
- Customizable Vespel® SF densification allows for “tailoring” of mechanical properties to meet appropriate structural application needs. (Figure 3) Three standard grades (SF-0920, SP-0930, SF-0940) are available with respective datasheets.
- Vespel® SF can be pre-formed and machined into complex geometries to suit varying customer requirements. (Figures 1 and 2)

- Vespel® SF is a durable material with a high degree of chemical stability as well as thermal and acoustic insulation.
- Vespel® SF offers high temperature continuous use at 300 °C (572 °F) with the added benefits of being flame resistant as well as safe to handle when exposed to open flames with no off gas or release of toxic fumes.
- Vespel® SF can be easily bonded to various mating surfaces thus making them suitable for field repairs.

Features and Benefits

• Sealing properties

Vespel® SF seals offer a unique balance of properties including durability, high temperature resistance, low CTE, abrasable properties, and low weight (PCF) without compromising structural integrity making it a material of choice when it comes to sealing applications.

• Tensile strength

Ultimate tensile strength varying from approximately 425 to over 26,000 kPa (61–3,700 psi) depending on the design density.

• Safety and environmental stewardship

Fire resistant by design, Vespel® SF polyimide foam emits virtually no off gas and does not release toxic fumes when exposed to open flames. Its non-fibrous composition promotes safe handling during processing and final assembly.

• Design flexibility

Vespel® SF can be molded and machined to match unique geometries of both common and complex designs. Parts can be easily bonded at initial assembly or in the field. (Figures 1 and 2)




Figure 1.




Figure 2.

• Improves efficiency by reducing fuel consumption and increasing payload capacity

Vespel® SF polyimide foam can be manufactured to meet density requirements in the range of approximately 0.16–0.56 g/cc (10–35 lb/ft³).

• Solving a variety of problems

From abrasable seals, stator vane seals, variable bushing packing, and nacelle insulation to composite paneling in structural applications, the versatility and durability of Vespel® SF products allows you to think out of the box to solve an array of problems where temperature resistance, weight, dampening, or sealing are of concern.




Figure 3. DuPont™ Vespel® SF Compressive Strength




Figure 4. DuPont™ Vespel® SF Customizable Densification at Varying Part Thickness

Visit us at vespel.dupont.com

Contact DuPont at the following regional locations:

North America

800-222-8377

Latin America

+0800 17 17 15

Europe, Middle East, Africa

+41 22 717 51 11

Greater China

+86-400-8851-888

ASEAN

+65-6586-3688

Japan

+81-3-5521-8484

The information provided in this data sheet corresponds to our knowledge on the subject at the date of its publication. This information may be subject to revision as new knowledge and experience becomes available. The data provided fall within the normal range of product properties and relate only to the specific material designated; these data may not be valid for such material used in combination with any other materials, additives or pigments or in any process, unless expressly indicated otherwise.

The data provided should not be used to establish specification limits or used alone as the basis of design; they are not intended to substitute for any testing you may need to conduct to determine for yourself the suitability of a specific material for your particular purposes. Since DuPont cannot anticipate all variations in actual end-use and disposal conditions, DuPont does not guarantee favorable results, makes no warranties and assumes no liability in connection with any use of this information. All such information is given and accepted at the buyer's risk. It is intended for use by persons having technical skill, at their own discretion and risk. Nothing in this publication is to be considered as a license to operate under or a recommendation to infringe any patent. DuPont advises you to seek independent counsel for a freedom to practice opinion on the intended application or end-use of our products.

CAUTION: Do not use DuPont materials in medical applications involving implantation in the human body or contact with internal body fluids or tissues unless the material has been provided from DuPont under a written contract that is consistent with DuPont policy regarding medical applications and expressly acknowledges the contemplated use. For further information, please contact your DuPont representative. You may also request a copy of DuPont POLICY Regarding Medical Applications H-50103-5 and DuPont CAUTION Regarding Medical Applications H-50102-5.

Copyright © 2017 DuPont. The DuPont Oval Logo, DuPont™, and Vespel® are trademarks or registered trademarks of E.I. du Pont de Nemours and Company or its affiliates. All rights reserved.

VPE-A40046-00-A0217 (3/17)

