

Styrofoam™ Brand Panel Core 30 Extruded Polystyrene Foam Insulation

High Performance Insulation for Composite Panel Applications

FEATURES/BENEFITS

Description

Styrofoam™ Brand Panel Core 30 Insulation* is a closed-cell, high performance core material featuring a proprietary extrusion process facilitating precise control of parameters like density, cell size and cell orientation. This process yields foam boards that can stand up to the most demanding and extensive array of composite panel applications.

Styrofoam™ Brand Panel Core 30 is supplied in sheets that have been carefully engineered and planed to precise tolerances for an exceptional bonding surface. The closed-cell structure of **Styrofoam™ Brand Panel Core 30** resists absorption of water, which helps maintain panel integrity and insulating properties in low temperature applications and other environments with high humidity and moisture conditions. The foam also resists absorption of adhesives, so less glue is required for effective, long-lasting adhesion of facer materials.

Typical applications for **Styrofoam™ Brand Panel Core 30** include:

- Architectural building panels
- Walk-in coolers
- Modular structures
- Incubators
- Conservatories
- Sunrooms
- Recreational vehicle sidewalls
- Exterior door panels
- Insulated roof panels
- Clean-room panels
- Garage and entry doors

Ease of Use

Styrofoam™ Brand Panel Core 30 is strong, yet lightweight and easy to fabricate into various sizes and shapes to meet specific design needs. **Styrofoam™ Brand Panel Core 30** sheets:

- Have been carefully engineered and planed to precise tolerances
- Provide an exceptional bond surface
- Resist water absorption
- Help maintain panel integrity and insulating properties in low-temperature, high-humidity and high-moisture conditions
- Consist of foam that resists absorption of adhesives, meaning they require less glue

Available Sizes

Styrofoam™ Brand Panel Core 30 is available with straight edge treatment in nominal board thicknesses up to 4", board lengths up to 216" and board widths up to 50". Not all product sizes are available in all regions.

Sustainable Solutions

Styrofoam™ Brand Panel Core 30 is reusable in many applications and is hydrochlorofluorocarbon (HCFC) free** with zero ozone depletion potential. Styrofoam™ Brand insulation products produced in North America contain an average of 20% pre-consumer recycled content certified by UL Environment Inc.

* Styrofoam™ Brand Panel Core 30 is a former product of The Dow Chemical Company

** manufactured without hydrochlorofluorocarbon

PROPERTIES

Styrofoam™ Brand Panel Core 30 Insulation exhibits physical properties as indicated in Table 1 when tested as represented. Review all instructions and (Material) Safety Data Sheet ((M)SDS) before use. Please contact DuPont at 1-866-583-2583 when additional guidance is required for writing specifications that include this product.

TABLE 1: Typical Physical Properties of Styrofoam™ Panel Core 30 Extruded Polystyrene Foam Insulation

Test Method	Property	Typical Value	Units
ASTM D1621	Compressive Strength ¹	30	psi, min., vertical
ASTM D1623	Tensile Strength	65	lb/in ² , min., vertical
ASTM C273	Shear Strength	35	lb/in ² (kPa)
ASTM C273	Shear Modulus	400	lb/in ² (kPa)
ASTM C203	Flexural Strength	55	lb/in ² (kPa), extruded
ASTM C203	Flexural Modulus	1,600	lb/in ² (kPa), extruded
ASTM C272	Water Absorption	0.3	% by vol., max.
ASTM E96	Water Vapor Permeance ²	1.5	perm, max.
ASTM C518	R-Value ³ per inch (25 mm), °F·ft ² ·h/Btu, 180 days aged @ 75°F (24°C) min.	5.0	-
ASTM E84	Surface burning characteristics ⁴ Flame Spread Index Smoke Developed Index	15 165	- -

¹ Vertical compressive strength measured at 10 percent deformation or at yield, whichever occurs first. Adequate design safety factors should be used to prevent long-term creep. Contact DuPont for design recommendations. When placing a load over the surface of the product, the compressive strength should be multiplied by 0.52 to account for the surface area lost due to channels cut into the foam surface.

² Based on 1" thickness

³ R means resistance to heat flow. The higher the R-value, the greater the insulating power.

⁴ This numerical flame spread rating is not intended to reflect hazards presented by this or any other material under actual fire conditions.

TESTING

Applicable Standards

Styrofoam™ Brand Panel Core 30 Insulation complies with ASTM C578 Type X.

Code Compliances

Styrofoam™ Brand Panel Core 30 complies with the following codes:

- Meets IBC/IRC requirements for foam plastic insulation. See International Code Council evaluation report ICC-ES ESR 2142
- UL Classified, See Classification Certificate D369

Contact your local DuPont sales representative or local authorities for state and local building code requirements and related acceptance.

Warranty

In the United States, a 50-year thermal limited warranty is available on Styrofoam™ Brand insulation products 1.5 inches and greater. For thickness less than 1.5 inches, other warranties may apply. Visit building.dupont.com/warranties or contact your DuPont representative for details.

HANDLING

WARNING: For Professional Use Only. Read and follow the entire Handling section and the Safety Data Sheets (SDSs, formerly MSDSs or Material Safety Data Sheets) carefully before use. The information below is designed to protect the user and allow for safe use and handling of Styrofoam™ Brand products. Follow all applicable federal, state, local and employer regulations.

Precautionary Statements

- Styrofoam™ Brand Panel Core 30 Insulation is combustible; protect from high heat sources. A protective barrier or thermal barrier may be required as specified in the appropriate building code.
- Like all cellular polymers, this product will degrade upon prolonged exposure to sunlight. A covering may be used to block ultraviolet radiation and prevent degradation. Other coverings to protect the foam from the elements and to meet applicable fire regulations may also be required.
- Due to the critical technical design aspects of many of its applications, DuPont recommends that qualified designers or consultants design your system.

- For more information on codes and compliances, consult SDS, call DuPont at 1-866-583-2583 or contact your local building inspector. DuPont can also offer general guidelines and recommendations for Styrofoam™ Brand Panel Core 30.

Shelf Life and Storage

When stored outdoors, keep insulation boards tarped or covered to protect from weather and weighted down to prevent boards from being blown around by the wind. Store above standing water.

Disposal

Dispose of any residual Styrofoam™ Brand product, coated debris, or solvent in accordance with applicable federal, state, and local government regulations.



**For more information visit us at
styrofoam.com/panelcore
or call 1-866-583-2583**

NOTICE: No freedom from any patent owned by DuPont or others is to be inferred. Because use conditions and applicable laws may differ from one location to another and may change with time, Customer is responsible for determining whether products and the information in this document are appropriate for Customer's use and for ensuring that Customer's workplace and disposal practices are in compliance with applicable laws and other government enactments. The product shown in this literature may not be available for sale and/or available in all geographies where DuPont is represented. The claims made may not have been approved for use in all countries or regions. DuPont assumes no obligation or liability for the information in this document. References to "DuPont" or the "Company" mean the DuPont legal entity selling the products to Customer unless otherwise expressly noted. NO EXPRESS WARRANTIES ARE GIVEN EXCEPT FOR ANY APPLICABLE WRITTEN WARRANTIES SPECIFICALLY PROVIDED BY DUPONT. ALL IMPLIED WARRANTIES INCLUDING THOSE OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE EXPRESSLY EXCLUDED. The buyer assumes all risks as to the use of the material. Buyer's exclusive remedy or any claim (including without limitations, negligence, strict liability, or tort) shall be limited to the refund of the purchase price of the material. Failure to strictly adhere to any recommended procedures shall release DuPont Specialty Products USA, LLC or its affiliates, of all liability with respect to the materials or the use thereof. The information herein is not intended for use by non-professional designers, applicators or other persons who do not purchase or utilize this product in the normal course of their business.

Styrofoam™ Extruded Polystyrene Foam Insulation

CAUTION: This product is combustible. Protect from high heat sources. A protective barrier or thermal barrier may be required as specified in the appropriate building code. For more information, consult (Material) Safety Data Sheet ((M)SDS), call DuPont at 1-866-583-2583 or contact your local building inspector. In an emergency, call 1-989-636-4400 in the U.S. or 1-519-339-3711 in Canada.

WARNING: Rigid foam insulation does not constitute a working walkable surface or qualify as a fall protection product.

Building and/or construction practices unrelated to building materials could greatly affect moisture and the potential for mold formation. No material supplier including DuPont can give assurance that mold will not develop in any specific system.

DuPont™, the DuPont Oval Logo, and Styrofoam™ are trademarks or registered trademarks of DuPont or its affiliates. Copyright © 2019 DuPont de Nemours Inc.