

Froth-Pak™ Foam Insulation

Two-Component, Quick-Cure, Professional Insulation Kit

FEATURES/BENEFITS

Description

Froth-Pak™ Foam Insulation* is a complete and portable two-component, quick-cure polyurethane foam that fills cavities, penetrations, cracks and expansion joints greater than 2 inches wide. Unlike one-component foam, Froth-Pak™ Insulation is chemically cured – significantly reducing curing time by dispensing, expanding and becoming tack-free in seconds.

Froth-Pak™ Insulation's industry-leading, customizable dispensing system helps ensure consistent flow rate, on-ratio application and complete dispensing of product. Uses include roof and wall junctions, wall and attic, electrical, mechanical and plumbing penetrations in the building envelope, wood bonds, rigid foam, masonry, metal, drywall and more.

With a Class-A flame spread rating, **Froth-Pak™ Insulation** can be used in a wide range of interior and exterior industrial, commercial, institutional and residential settings, reducing the potential for unwelcome moisture, mold, mildew, allergens and rot.

Ease of Use

Froth-Pak™ Insulation is:

- Chemically cured foam with significantly reduced curing time
- Able to skin over in 30–40 seconds and cure in minutes**
- Available in refillable cylinders or disposable kits
- Useful for commercial applications including spray polyurethane foam roof repair, sealing roof perimeters and parapet walls
- Useful for residential applications including roof and wall junctions; wall and attic penetrations; electrical, mechanical and plumbing penetrations and other gaps, cracks or crevices in the building envelope

Available Sizes

Froth-Pak™ Insulation is typically sold as a complete 42 lb. (Froth-Pak™ 210) or 117 lb. (Froth-Pak™ 650) portable kit that includes pressurized “A” and “B” cylinders, plus dispensing gun/hose assembly and accessories. **Froth-Pak™ Insulation** is also available in refillable, returnable cylinders for commercial applications requiring a large amount of foam. See Table 1 for yield and size information.

TABLE 1: Sizes and Theoretical Yields for Froth-Pak™ Foam Insulation

Product	Theoretical Yield, ⁽¹⁾ board ft
Kits	
Froth-Pak™ 210	210
Froth-Pak™ 650	650
Refillable Cylinders	
Froth-Pak™ 17 (gal)	2,150
Froth-Pak™ 27 (gal)	3,480
Froth-Pak™ 60 (gal)	7,160
Froth-Pak™ 120 (gal)	16,110
Froth-Pak™ 350 (gal)	45,820

¹The theoretical yield has become an industry standard for identifying certain sizes of two-component kits. Theoretical yield calculations are performed in perfect laboratory conditions, without taking into account the loss of blowing agent or the variations in application methods and types.

* Froth-Pak™ Foam Insulation is a former product of The Dow Chemical Company.

** Actual cure time will depend on temperature, foam thickness, the specific nozzle used, etc.

PROPERTIES

Review all instructions and (Material) Safety Data Sheet ((M)SDS) before use. Please contact DuPont at 1-866-583-2583 when additional guidance is required for writing specifications that include this product.

TABLE 2: Typical* Physical Properties of Froth-Pak™ Foam Insulation

Property and Test Method	Value
Flame Spread/Smoke Developed, ^{(1), (2)} ASTM E84/UL 723	25/400
Nominal Density, ASTM D1622, lb/ft ³	1.75
Thermal Resistance ⁽³⁾ per inch, ASTM C518, ft ² -h ² -°F/Btu, R-value, min.	
Initial	6.6
Aged 180 days at 75°F – 1.0"	6.0 (when sprayed as 1" thickness)
Aged 180 days at 75°F – 2.0"	12.2 (6.1/in when sprayed as 2" thickness)
Air Leakage, ASTM E283, cfm/ft ² @ 1.57 psf ASTM E2178, L/s/m ² @ 75 Pa	0 0
Water Vapor Permeance, ASTM E96 perm @ 1" thick perm @ 2" thick	6.4 3.2
Water Absorption, ASTM D2842, % by volume	3.2
Dimensional Stability, ASTM D2126, % volume change	
100°F/97% RH @ 1wk	0.7
158°F/97% RH @ 1wk	8.3
-40°F/amb RH @ 1wk	0.0
158°F/amb RH @ 1wk	3.1
Compressive Strength, ASTM D1621, lb/in ² , parallel	172
Tensile Strength, ASTM D1623, lb/in ² , parallel	32.0
Maximum Service Temperature, °F	240

¹ Tested at 2" thickness, full coverage.

² This numerical flame spread rating is not intended to reflect hazards presented by this or any other material under actual fire conditions.

³ R means resistance to heat flow. The higher the R-value, the greater the insulating power.

* These properties are typical but do not constitute specifications.

INSTALLATION

Use Conditions

- Complete operating instructions are provided with every **Froth-Pak™ Foam Insulation** purchase. Read all information and cautions before application:
- Check with local codes prior to use. If used in an exterior setting, a coating must be applied for ultraviolet (UV) protection.

Application

- Avoid overfilling restricted spaces. Chemicals exert force during reaction, and expansion of foam may result in substrate deformation.
- **Froth-Pak™ Insulation** will adhere to most surfaces and skin. Do not get foam on skin. Wear protective clothing (including long sleeves), gloves, and goggles.
- Re-entry allowed after only one hour post-application.

Curing

Cure time will depend on temperature, foam thickness, the specific nozzle used, etc. Cured foam must be mechanically removed or allowed to wear off in time.

Equipment

Each self-contained kit contains an ISO(A) cylinder, a Polyol (B) cylinder, 6 cone spray nozzles, 4 fan spray nozzles, and a 15-ft gun hose assembly (GHA).

TESTING

Applicable Standards – ASTM International

- **C203** – Standard Test Methods for Breaking Load and Flexural Properties of Block-Type Thermal Insulation
- **C273** – Standard Test Method for Shear Properties of Sandwich Core Materials
- **C518** – Standard Test Method for Steady-State Thermal Transmission Properties by Means of the Heat Flow Meter Apparatus
- **D1621** – Standard Test Method for Compressive Properties of Rigid Cellular Plastics
- **D1622** – Standard Test Method for Apparent Density of Rigid Cellular Plastics
- **D1623** – Standard Test Method for Tensile and Tensile Adhesion Properties of Rigid Cellular Plastics
- **D2842** – Standard Test Method for Water Absorption of Rigid Cellular Plastics
- **E96** – Standard Test Methods for Water Vapor Transmission of Materials
- **E283** – Standard Test Method for Determining Rate of Air Leakage Through Exterior Windows, Curtain Walls and Doors Under Specified Pressure Differences Across the Specimen
- **E2178** – Standard Test Method for Air Permeance of Building Materials

Notice

Froth-Pak™ Insulation complies with the following codes:

- Underwriters Laboratories, Inc. (UL) Classified, see Classification Certificate R7813
- National Fire Protection Association – per NFPA 286 testing, can be left exposed in non-fire-resistant-rated roof/wall junctures, maximum 6" high and 2" deep (unlimited width)

Contact your DuPont sales representative or local authorities for state and local building code requirements and related acceptances.

HANDLING

WARNING: For Professional Use Only – Read and follow the entire Handling section and the Safety Data Sheets (SDSs, formerly MSDSs or Material Safety Data Sheets) carefully before use. The information below is designed to protect the user and allow for safe use and handling of Froth-Pak™ products. Follow all applicable federal, state, local and employer regulations.

Precautionary Statements

- **Froth-Pak™ Foam Insulation** will adhere to most surfaces and skin. Do not get foam on skin. Wear protective clothing (including long sleeves), gloves, and goggles. Cured foam must be mechanically removed or allowed to wear off in time.
- **Froth-Pak™ Insulation** should not be used around heaters, furnaces, fireplaces, recessed lighting fixtures or other applications where the foam may come in contact with heat-conducting surfaces.
- Cured **Froth-Pak™ Insulation** is combustible and will burn if exposed to open flame or sparks from high-energy sources. Do not expose to temperatures above 240°F.
- Avoid overfilling restricted spaces. Chemicals exert force during reaction, and expansion of foam may result in substrate deformation.
- Froth-Pak™ spray polyurethane foam contains isocyanate, hydrofluorocarbon blowing agent and polyol. Do not breathe vapor or mist. Use only with adequate ventilation. Increased ventilation significantly reduces the potential for isocyanate exposure.
- Isocyanate is irritating to the eyes, skin and respiratory system, and may cause sensitization by inhalation or skin contact.
- Contents are under pressure.

Personal Protective Equipment (PPE)

Personal protective equipment (PPE) used during the handling of Froth-Pak™ products must at a minimum include:

- Protective clothing including long sleeves, gloves, and goggles.
- RECOMMENDED – Supplied air or an approved air-purifying respirator equipped with an organic vapor sorbent and a particulate filter to maintain exposure levels below ACGIH, OSHA, WEEL or other applicable limits
- IF ATMOSPHERIC LEVELS EXCEED THE LEVEL FOR WHICH AN AIR-PURIFYING RESPIRATOR IS EFFECTIVE – A positive-pressure, air-supplying respirator such as an air line or self-contained breathing apparatus.

Disposal

Dispose of any residual Froth-Pak™ product, coated debris, or solvent in accordance with applicable federal, state, and local government regulations.



**For more information visit us at
frothpak.com/insulation
or call 1-866-583-2583**

NOTICE: No freedom from any patent owned by DuPont or others is to be inferred. Because use conditions and applicable laws may differ from one location to another and may change with time, Customer is responsible for determining whether products and the information in this document are appropriate for Customer's use and for ensuring that Customer's workplace and disposal practices are in compliance with applicable laws and other government enactments. The product shown in this literature may not be available for sale and/or available in all geographies where DuPont is represented. The claims made may not have been approved for use in all countries or regions. DuPont assumes no obligation or liability for the information in this document. References to "DuPont" or the "Company" mean the DuPont legal entity selling the products to Customer unless otherwise expressly noted. NO EXPRESS WARRANTIES ARE GIVEN EXCEPT FOR ANY APPLICABLE WRITTEN WARRANTIES SPECIFICALLY PROVIDED BY DUPONT. ALL IMPLIED WARRANTIES INCLUDING THOSE OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE EXPRESSLY EXCLUDED. The buyer assumes all risks as to the use of the material. Buyer's exclusive remedy or any claim (including without limitations, negligence, strict liability, or tort) shall be limited to the refund of the purchase price of the material. Failure to strictly adhere to any recommended procedures shall release DuPont Specialty Products USA, LLC or its affiliates, of all liability with respect to the materials or the use thereof. The information herein is not intended for use by non-professional designers, applicators or other persons who do not purchase or utilize this product in the normal course of their business.

CAUTION: This product is combustible. Protect from high heat sources. A protective barrier or thermal barrier may be required as specified in the appropriate building code. For more information, consult (Material) Safety Data Sheet ((M)SDS), call DuPont at 1-866-583-2583 or contact your local building inspector. In an emergency, call 1-989-636-4400 in the U.S. or 1-519-339-3711 in Canada.

WARNING: Rigid foam insulation does not constitute a working walkable surface or qualify as a fall protection product.

FROTH -PAK™ Spray Polyurethane Foam contains isocyanate, hydrofluorocarbon blowing agent and polyol. Read the instructions and Material Safety Data Sheets carefully before use. Wear protective clothing (including long sleeves), gloves, goggles or safety glasses, and proper respiratory protection. Building and/or construction practices unrelated to building materials could greatly affect moisture and the potential for mold formation. No material supplier including DuPont can give assurance that mold will not develop in any specific system.

DuPont™, the DuPont Oval Logo, and Froth-Pak™ are trademarks or registered trademarks of DuPont or its affiliates. Copyright © 2019 DuPont de Nemours Inc.