



THIXON™ 423 Blue 1.7

Description THIXON™ 423 Blue 1.7 is a vulcanizing adhesive which can be used as a one-coat adhesive or as a covercoat adhesive over THIXON™ 403/404 adhesive primer for bonding castable polyurethane to various substrates. THIXON™ 423 can also be used as a one-coat adhesive for bonding thermoplastic polyurethanes to metal. THIXON™ 423 can also be used as a protective coating for metal, polyurethane, epoxy, polyester and fiberglass compounds.

Benefits & Features Good one-coat system for Thermal Plastic Urethane to metal bonding, which come pre-diluted to minimize the need to blend or prepare adhesive prior to application to metal or other substrates.

Uncured Properties	Nominal Value	Unit	Test Method
Color	Blue		
Solids Content			
-- 1	14	%	
-- 2	16 to 18	%	ASTM D2369
Density	0.912 to 0.948	g/cm ³	ASTM D1475
Dry Film Density	0.95	g/cm ³	
VOC Content	6.10	lb/gal	
Flash Point ³	-4.00	°C	
Viscosity ⁴ (25°C, Brookfield RVT)	0.074 to 0.13	Pa·s	ASTM D1084
Viscosity (25°C)	25 to 34	sec	Zahn Cup 2
Theoretical Coverage ⁵	18.5	m ² /l	
Recommended Film Thickness	15	µm	
Recommended Film Thickness Range	15 to 50	µm	
Shelf Life ⁶ (25°C)	24	month	

Elastomer

Castable Urethanes with the use of THIXON™ 403/404 primers or Themoplastic Urethane (TPU)

Substrate

CRS, Phosphate or grit blast pre-treated CRS, Aluminum, Stainless Steel, fiberglass, polyester, nylon, rayon fibers, etc.

Surface Prep

Review Dow 's rubber-to-substrate bonding agent application guide or contact your account manager.

Mix Instructions

Pre-diluted and mixing may be required to make sure blue dye disperses evenly for consistent coating color.

Application Technique

Brush: for brush applications use undiluted. Brush on a heavy wet film of THIXON™ 423 without brushing excessively. To obtain the required film thickness, brush on two coats. Dip - For dip applications, dilute 3 parts THIXON™ 423 with 1 part diluent. To obtain a film thickness of 1 mil, dip twice.

Drying the Film

Dry the film of THIXON™ 423 before continuing. At normal room temperature, dry for 30 to 45 minutes. At lower temperatures, dry longer. The drying time can be shortened by force drying approximately 5 to 10 minutes at 120 to 160°F. Do not dry at temperatures above 180°F.

Molding and Curing

Most molding and curing methods. Use a cure temperature between 190 to 350°F.

Pre-Bake Resistance

For the best results, prebake the coated metals for ½ to 3 hours at 200 to 300°F, depending on the weight of the metal. This product can withstand prebaking in forced air convection ovens, with proper ventilation, for up to 16 hours at 250°F.

Dry Film Stability

Excellent dry film stability. Inserts which have been coated can be stored for several weeks before use, if they are protected from airborne contaminants.

Clean-up

Equipment clean up should be done using recommended dilution solvents.

Packaging/Sizes Available

Drums, pails and gallon cans.

Storage & Stability

The shelf life of this material is assured for 24 months (from the date of manufacture) at temperatures below 78°F in an unopened container.

Toxicity and Safety Information

Read the Safety Data Sheet before using this material. Toxicity and safety information is included in the SDS.

Food Contact Applications

Dow Automotive products are not approved for direct or indirect food contact or drinking water applications. If your applications include food contact or drinking water requirements, please contact your Dow representative. For more information on the regulatory status of this product, please refer to the SDS for this product.

Notes

These are typical properties only and are not to be construed as specifications. Users should confirm results by their own tests.

¹ By volume

² Non-volatile solids by weight

³ SetaFlash Closed Cup

⁴ Spindle #1, @ 20 RPM

⁵ Applied at a dry film thickness of 15 microns/0.6 mils

⁶ Unopened

Product Stewardship

The Dow Chemical Company and its subsidiaries ("Dow") has a fundamental concern for all who make, distribute, and use its products, and for the environment in which we live. This concern is the basis for our Product Stewardship philosophy by which we assess the safety, health, and environmental information on our products and then take appropriate steps to protect employee and public health and our environment. The success of our Product Stewardship program rests with each and every individual involved with Dow products — from the initial concept and research, to manufacture, use, sale, disposal, and recycle of each product.

Customer Notice

Dow strongly encourages its customers to review both their manufacturing processes and their applications of Dow products from the standpoint of human health and environmental quality to ensure that Dow products are not used in ways for which they are not intended or tested. Dow personnel are available to answer your questions and to provide reasonable technical support. Dow product literature, including safety data sheets, should be consulted prior to use of Dow products. Current safety data sheets are available from Dow.

Medical Applications Policy

NOTICE REGARDING MEDICAL APPLICATION RESTRICTIONS: Dow will not knowingly sell or sample any product or service ("Product") into any commercial or developmental application that is intended for:

- long-term or permanent contact with internal bodily fluids or tissues. "Long-term" is contact which exceeds 72 continuous hours;
- use in cardiac prosthetic devices regardless of the length of time involved ("cardiac prosthetic devices" include, but are not limited to, pacemaker leads and devices, artificial hearts, heart valves, intra-aortic balloons and control systems, and ventricular bypass-assisted devices);
- use as a critical component in medical devices that support or sustain human life; or
- use specifically by pregnant women or in applications designed specifically to promote or interfere with human reproduction.

Dow requests that customers considering use of Dow products in medical applications notify Dow so that appropriate assessments may be conducted. Dow does not endorse or claim suitability of its products for specific medical applications. It is the responsibility of the medical device or pharmaceutical manufacturer to determine that the Dow product is safe, lawful, and technically suitable for the intended use. **DOW MAKES NO WARRANTIES, EXPRESS OR IMPLIED, CONCERNING THE SUITABILITY OF ANY DOW PRODUCT FOR USE IN MEDICAL APPLICATIONS.**

Disclaimer

NOTICE: No freedom from infringement of any patent owned by Dow or others is to be inferred. Because use conditions and applicable laws may differ from one location to another and may change with time, the Customer is responsible for determining whether products and the information in this document are appropriate for the Customer's use and for ensuring that the Customer's workplace and disposal practices are in compliance with applicable laws and other governmental enactments. Dow assumes no obligation or liability for the information in this document. **NO WARRANTIES ARE GIVEN; ALL IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE ARE EXPRESSLY EXCLUDED.**

NOTICE: If products are described as "experimental" or "developmental": (1) product specifications may not be fully determined; (2) analysis of hazards and caution in handling and use are required; (3) there is greater potential for Dow to change specifications and/or discontinue production; and (4) although Dow may from time to time provide samples of such products, Dow is not obligated to supply or otherwise commercialize such products for any use or application whatsoever.

NOTICE: This data is based on information Dow believes to be reliable, as demonstrated in controlled laboratory testing. They are offered in good faith, but without guarantee, as conditions and method of use of Dow products are beyond Dow's control. Dow recommends that the prospective user determine the suitability of these materials and suggestions before adopting them on a commercial scale.

To the best of our knowledge, the information contained herein is accurate and reliable as of the date of publication, however we do not assume any liability for the accuracy and completeness of such information.

Additional Information

North America		Europe/Middle East	+800-3694-6367
U.S. & Canada:	1-800-441-4369		+31-11567-2626
	1-989-832-1426	Italy:	+800-783-825
Mexico:	+1-800-441-4369		
Latin America		South Africa	+800-99-5078
Argentina:	+54-11-4319-0100		
Brazil:	+55-11-5188-9000		
Colombia:	+57-1-219-6000	Asia Pacific	+800-7776-7776
Mexico:	+52-55-5201-4700		+603-7965-5392

www.dowautomotive.com

This document is intended for use within North America

Published: 2015-05-15

© 2018 The Dow Chemical Company

