



- CMU WALL
- BRICK VENEER
- DUPONT™ SEALANT FOR TYVEK® FLUID APPLIED SYSTEM *
- MECHANICAL FASTENER
- DUPONT™ TYVEK® FLUID APPLIED WB
- END DAM
- DUPONT™ THRU-WALL FLASHING WITH 1/4" DRIP EDGE
- LOOSE-LAID STEEL LINTEL
- BACKER ROD AND SEALANT BY OTHERS
- WINDOW FRAME
- GYPSUM BOARD
- DUPONT™ TYVEK® FLUID APPLIED FLASHING AND JOINT COMPOUND (2" ONTO FACE OF WALL)
- DUPONT™ SEALANT FOR TYVEK® FLUID APPLIED SYSTEM (USE BACKER ROD AS NECESSARY)

NOTE
 1) INTERIOR VAPOR RETARDER MAY BE REQUIRED IN SOME REGIONS.
 2) THIS INFORMATION IS PROVIDED BY DUPONT AS REFERENCE ONLY; PLEASE CONSULT LOCAL BUILDING CODES, REGULATIONS AND LAWS TO DETERMINE THE APPROPRIATE CONSTRUCTION METHODS AND MATERIALS NEEDED.

* DUPONT™ SEALANT FOR TYVEK® FLUID APPLIED SYSTEM OR DUPONT™ TYVEK® FLUID APPLIED FLASHING AND JOINT COMPOUND MAY BE USED.

SCALE: NOT TO SCALE
 REVISION DATE: 4/28/10
 DRAWING: FA-B-W100h

STOREFRONT WINDOW HEAD - METHOD 1
 BRICK VENEER / CMU WALL / FLUID APPLIED FLASHING

