

MINERAL FIBER INSULATION  
(VAPOR PERMEABLE)

DUPONT™ TYVEK®  
FLUID APPLIED WB

BRICK VENEER

SEALANT  
BY OTHERS

WINDOW FRAME

DUPONT™ STRAIGHTFLASH™  
(2" ONTO FACE OF WALL)

DUPONT™ SEALANT FOR TYVEK®  
FLUID APPLIED SYSTEM  
(USE BACKER ROD AS NECESSARY)

GYPSUM BOARD

CMU WALL

**NOTE**

- 1) INTERIOR VAPOR RETARDER MAY BE REQUIRED IN SOME REGIONS.
- 2) THIS INFORMATION IS PROVIDED BY DUPONT AS REFERENCE ONLY; PLEASE CONSULT LOCAL BUILDING CODES, REGULATIONS AND LAWS TO DETERMINE THE APPROPRIATE CONSTRUCTION METHODS AND MATERIALS NEEDED.

SCALE: NOT TO SCALE

REVISION DATE: 4/28/10

DRAWING: FA-BX-W101j

## STOREFRONT WINDOW JAMB - METHOD 2

BRICK VENEER / EXTERIOR INSULATION / CMU WALL / SELF-ADHERED FLASHING



**Tyvek.**

FLUID APPLIED WB