

# **SAFETY DATA SHEET**

# DDP SPECIALTY ELECTRONIC MATERIALS US 9, LLC

Product name: MOLYKOTE® G-0051 FM White EP Bearing Issue Date: 02/25/2020

Grease

Print Date: 06/23/2023

DDP SPECIALTY ELECTRONIC MATERIALS US 9, LLC encourages and expects you to read and understand the entire (M)SDS, as there is important information throughout the document. We expect you to follow the precautions identified in this document unless your use conditions would necessitate other appropriate methods or actions.

# 1. IDENTIFICATION

Product name: MOLYKOTE® G-0051 FM White EP Bearing Grease

Recommended use of the chemical and restrictions on use

Identified uses: Lubricants and lubricant additives

**COMPANY IDENTIFICATION** 

DDP SPECIALTY ELECTRONIC MATERIALS US 9, LLC 974 Centre Road Wilmington DE 19805 UNITED STATES

Customer Information Number: 833-338-7668

SDSQuestion-NA@dupont.com

**EMERGENCY TELEPHONE NUMBER** 

**24-Hour Emergency Contact:** 1-800-424-9300 **Local Emergency Contact:** 800-424-9300

# 2. HAZARDS IDENTIFICATION

### **Hazard classification**

GHS classification in accordance with 29 CFR 1910.1200 Not a hazardous substance or mixture.

#### Other hazards

No data available

# 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical nature: Organic grease

This product is a mixture.

Component CASRN Concentration

White mineral oil (petroleum)	8042-47-5	>= 69.0 - <= 85.0 %
Aluminum hydroxide benzoate stearate	54326-11-3	>= 6.0 - <= 7.0 %
Zinc oxide	1314-13-2	>= 4.0 - <= 6.0 %

## 4. FIRST AID MEASURES

# Description of first aid measures

General advice:

If potential for exposure exists refer to Section 8 for specific personal protective equipment.

**Inhalation:** Move person to fresh air; if effects occur, consult a physician.

Skin contact: Wash off with plenty of water.

**Eye contact:** Flush eyes thoroughly with water for several minutes. Remove contact lenses after the initial 1-2 minutes and continue flushing for several additional minutes. If effects occur, consult a physician, preferably an ophthalmologist.

Ingestion: No emergency medical treatment necessary.

#### Most important symptoms and effects, both acute and delayed:

Aside from the information found under Description of first aid measures (above) and Indication of immediate medical attention and special treatment needed (below), any additional important symptoms and effects are described in Section 11: Toxicology Information.

#### Indication of any immediate medical attention and special treatment needed

**Notes to physician:** No specific antidote. Treatment of exposure should be directed at the control of symptoms and the clinical condition of the patient.

# 5. FIREFIGHTING MEASURES

# **Extinguishing media**

**Suitable extinguishing media:** Water spray. Alcohol-resistant foam. Carbon dioxide (CO2). Dry chemical.

Unsuitable extinguishing media: None known...

#### Special hazards arising from the substance or mixture

**Hazardous combustion products:** Carbon oxides. Metal oxides.

**Unusual Fire and Explosion Hazards:** Exposure to combustion products may be a hazard to health..

#### Advice for firefighters

Page 2 of 15

**Fire Fighting Procedures:** Collect contaminated fire extinguishing water separately. This must not be discharged into drains.. Contain fire water run-off if possible. Fire water run-off, if not contained, may cause environmental damage..

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. Use water spray to cool unopened containers. Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Remove undamaged containers from fire area if it is safe to do so. Evacuate area.

**Special protective equipment for firefighters:** Wear self-contained breathing apparatus for firefighting if necessary.. Use personal protective equipment..

# 6. ACCIDENTAL RELEASE MEASURES

**Personal precautions, protective equipment and emergency procedures:** Follow safe handling advice and personal protective equipment recommendations.

**Environmental precautions:** Do not release the product to the aquatic environment above defined regulatory levels. Prevent further leakage or spillage if safe to do so. Retain and dispose of contaminated wash water. Local authorities should be advised if significant spillages cannot be contained.

**Methods and materials for containment and cleaning up:** Wipe up or scrape up and contain for salvage or disposal. Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable. For large spills, provide dyking or other appropriate containment to keep material from spreading. If dyked material can be pumped, Sections 13 and 15 of this SDS provide information regarding certain local or national requirements. See sections: 7, 8, 11, 12 and 13.

# 7. HANDLING AND STORAGE

**Precautions for safe handling:** Take care to prevent spills, waste and minimize release to the environment. Handle in accordance with good industrial hygiene and safety practice. Use only with adequate ventilation. See Engineering measures under EXPOSURE CONTROLS/PERSONAL PROTECTION section.

**Conditions for safe storage:** Keep in properly labelled containers. Store in accordance with the particular national regulations.

Do not store with the following product types: Strong oxidizing agents. Unsuitable materials for containers: None known.

# 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

# **Control parameters**

If exposure limits exist, they are listed below. If no exposure limits are displayed, then no values are applicable.

Component	Regulation	Type of listing	Value
White mineral oil (petroleum)	OSHA P0	TWA	5 mg/m3
	OSHA Z-1	TWA Mist	5 mg/m3

	ACGIH	TWA Inhalable particulate matter	5 mg/m3
	Further information: URT in a human carcinogen		tation; A4: Not classifiable as
	CAL PEL	PEL particulate	5 mg/m3
	Further information: (I): As s	sampled by method that does	
Aluminum hydroxide	ACGIH	TWA Inhalable	10 mg/m3
benzoate stearate		particulate matter	
	Further information: LRT irr: Lower Respiratory Tract irritation; J: Does not include stearates of toxic metals.; A4: Not classifiable as a human carcinogen; varies: varies		
	ACGIH	TWA Respirable	3 mg/m3
		particulate matter	
	Further information: LRT irr	: Lower Respiratory Tract irrit	tation; J: Does not include
			an carcinogen; varies: varies
Zinc oxide	ACGIH	1	2 mg/m3
		particulate matter	
		ume fever: metal fume fever	
	ACGIH	STEL Respirable	10 mg/m3
		particulate matter	
		ume fever: metal fume fever	
	OSHA Z-1	TWA total dust	15 mg/m3
	OSHA Z-1	TWA respirable	5 mg/m3
		fraction	
	OSHA P0	TWA Total	10 mg/m3
	OSHA PO	TWA Respirable	5 mg/m3
		fraction	9
	OSHA Z-1	TWA	5 mg/m3
	OSHA PO	TWA	5 mg/m3
	OSHA PO	STEL	10 mg/m3
	OSHA PO	TWA Total dust	10 mg/m3
	OSHA PO	TWA respirable dust	5 mg/m3
	SONATO	fraction	3 mg/m3
	OSHA P0	TWA Fumes	5 mg/m2
			5 mg/m3
	OSHA PO	STEL Fumes	10 mg/m3
	NIOSH REL	TWA Dust	5 mg/m3
	NIOSH REL	TWA Fumes	5 mg/m3
	NIOSH REL	ST Fumes	10 mg/m3
	NIOSH REL	C Dust	15 mg/m3
	OSHA Z-1	TWA Fumes	5 mg/m3

Although some of the components of this product may have exposure guidelines, no exposure would be expected under normal handling conditions due to the physical state of the material.

# **Exposure controls**

**Engineering controls:** Use local exhaust ventilation, or other engineering controls to maintain airborne levels below exposure limit requirements or guidelines. If there are no applicable exposure limit requirements or guidelines, general ventilation should be sufficient for most operations. Local exhaust ventilation may be necessary for some operations.

# Individual protection measures

Eye/face protection: Use safety glasses (with side shields).

Skin protection

Page 4 of 15

Hand protection: Use gloves chemically resistant to this material when prolonged or frequently repeated contact could occur. Examples of preferred glove barrier materials include: Chlorinated polyethylene. Neoprene. Nitrile/butadiene rubber ("nitrile" or "NBR"). Polyethylene. Ethyl vinyl alcohol laminate ("EVAL"). Polyvinyl alcohol ("PVA"). Viton. Examples of acceptable glove barrier materials include: Butyl rubber. Natural rubber ("latex"). Polyvinyl chloride ("PVC" or "vinyl"). NOTICE: The selection of a specific glove for a particular application and duration of use in a workplace should also take into account all relevant workplace factors such as, but not limited to: Other chemicals which may be handled, physical requirements (cut/puncture protection, dexterity, thermal protection), potential body reactions to glove materials, as well as the instructions/specifications provided by the glove supplier.

Other protection: Wear clean, body-covering clothing.

**Respiratory protection:** Respiratory protection should be worn when there is a potential to exceed the exposure limit requirements or guidelines. If there are no applicable exposure limit requirements or guidelines, wear respiratory protection when adverse effects, such as respiratory irritation or discomfort have been experienced, or where indicated by your risk assessment process. For most conditions no respiratory protection should be needed; however, if discomfort is experienced, use an approved air-purifying respirator.

The following should be effective types of air-purifying respirators: Organic vapor cartridge.

# 9. PHYSICAL AND CHEMICAL PROPERTIES

**Appearance** 

Physical state Grease
Color white
Odor slight

Odor Threshold

pH

Not applicable

Melting point/range

No data available

No data available

No data available

Not applicable

Not applicable

Flash point closed cup 215 °C (419 °F)

Evaporation Rate (Butyl Acetate Not applicable

= 1)

Flammability (solid, gas) Not classified as a flammability hazard

Lower explosion limitNo data availableUpper explosion limitNo data availableVapor PressureNot applicableRelative Vapor Density (air = 1)No data available

Relative Density (water = 1) 0.89

Water solubility

Partition coefficient: n
No data available

No data available

octanol/water

Auto-ignition temperatureNo data availableDecomposition temperatureNo data availableDynamic ViscosityNot applicableKinematic ViscosityNot applicable

Product name: MOLYKOTE® G-0051 FM White EP Bearing Grease

Explosive properties Not explosive

**Oxidizing properties** The substance or mixture is not classified as oxidizing.

Molecular weightNo data availableParticle sizeNo data available

NOTE: The physical data presented above are typical values and should not be construed as a specification.

# 10. STABILITY AND REACTIVITY

**Reactivity:** Not classified as a reactivity hazard.

Chemical stability: Stable under normal conditions.

Possibility of hazardous reactions: Can react with strong oxidizing agents.

Conditions to avoid: None known.

Incompatible materials: Oxidizing agents

#### **Hazardous decomposition products**

No hazardous decomposition products are known.

#### 11. TOXICOLOGICAL INFORMATION

Toxicological information appears in this section when such data is available.

# **Acute toxicity**

#### Acute oral toxicity

Product test data not available. Refer to component data.

#### Acute dermal toxicity

Product test data not available. Refer to component data.

# Acute inhalation toxicity

Product test data not available. Refer to component data.

# Skin corrosion/irritation

Product test data not available. Refer to component data.

#### Serious eye damage/eye irritation

Product test data not available. Refer to component data.

#### Sensitization

Product test data not available. Refer to component data.

Page 6 of 15

# **Specific Target Organ Systemic Toxicity (Single Exposure)**

Product test data not available. Refer to component data.

# Specific Target Organ Systemic Toxicity (Repeated Exposure)

Product test data not available. Refer to component data.

#### Carcinogenicity

Product test data not available. Refer to component data.

### **Teratogenicity**

Product test data not available. Refer to component data.

# Reproductive toxicity

Product test data not available. Refer to component data.

#### Mutagenicity

Product test data not available. Refer to component data.

#### **Aspiration Hazard**

Product test data not available. Refer to component data.

#### COMPONENTS INFLUENCING TOXICOLOGY:

#### White mineral oil (petroleum)

#### Acute oral toxicity

LD50, Rat, > 5,000 mg/kg OECD Test Guideline 401

#### Acute dermal toxicity

LD50, Rabbit, > 2,000 mg/kg OECD Test Guideline 402 No deaths occurred at this concentration.

#### Acute inhalation toxicity

LC50, Rat, male and female, 4 Hour, dust/mist, > 5 mg/l OECD Test Guideline 403

#### Skin corrosion/irritation

Prolonged contact is essentially nonirritating to skin.

Repeated contact may cause skin irritation with local redness.

#### Serious eye damage/eye irritation

May cause slight temporary eye irritation.

Corneal injury is unlikely.

#### Sensitization

Did not cause allergic skin reactions when tested in guinea pigs.

For respiratory sensitization:

No relevant data found.

# **Specific Target Organ Systemic Toxicity (Single Exposure)**

Available data are inadequate to determine single exposure specific target organ toxicity.

### **Specific Target Organ Systemic Toxicity (Repeated Exposure)**

Based on available data, repeated exposures are not anticipated to cause additional significant adverse effects.

#### Carcinogenicity

Did not cause cancer in laboratory animals.

#### **Teratogenicity**

Did not cause birth defects in laboratory animals.

#### Reproductive toxicity

In animal studies, did not interfere with reproduction.

#### Mutagenicity

In vitro genetic toxicity studies were negative.

# Aluminum hydroxide benzoate stearate

#### Acute oral toxicity

For similar material(s): LD50, Rat, female, > 2,000 mg/kg OECD Test Guideline 420 No deaths occurred at this concentration.

#### **Acute dermal toxicity**

LD50, Rat, male and female, > 2,000 mg/kg OECD Test Guideline 402 No deaths occurred at this concentration.

# Acute inhalation toxicity

The LC50 has not been determined.

#### Skin corrosion/irritation

Brief contact is essentially nonirritating to skin.

#### Serious eye damage/eye irritation

May cause moderate eye irritation.

Corneal injury is unlikely.

#### Sensitization

For skin sensitization:

For similar material(s):

Did not demonstrate the potential for contact allergy in mice.

For respiratory sensitization:

No relevant data found.

#### **Specific Target Organ Systemic Toxicity (Single Exposure)**

Evaluation of available data suggests that this material is not an STOT-SE toxicant.

# Specific Target Organ Systemic Toxicity (Repeated Exposure)

For similar material(s):

Based on available data, repeated exposures are not anticipated to cause significant adverse effects.

# **Teratogenicity**

No relevant data found.

### Reproductive toxicity

No relevant data found.

# Mutagenicity

For similar material(s): In vitro genetic toxicity studies were negative.

#### **Aspiration Hazard**

Based on physical properties, not likely to be an aspiration hazard.

#### **Zinc oxide**

#### Acute oral toxicity

LD50, Rat, > 5,000 mg/kg

#### Acute dermal toxicity

The dermal LD50 has not been determined.

#### Acute inhalation toxicity

LC50, Rat, 4 Hour, dust/mist, > 5 mg/l No deaths occurred at this concentration.

#### Skin corrosion/irritation

Prolonged contact is essentially nonirritating to skin.

# Serious eye damage/eye irritation

May cause slight temporary eye irritation.

Corneal injury is unlikely.

#### **Sensitization**

For skin sensitization:

No relevant data found.

#### For respiratory sensitization:

No relevant data found.

# **Specific Target Organ Systemic Toxicity (Single Exposure)**

Available data are inadequate to determine single exposure specific target organ toxicity.

# Specific Target Organ Systemic Toxicity (Repeated Exposure)

In animals, effects have been reported on the following organs:

Luna.

In humans, effects have been reported on the following organs:

Respiratory tract.

#### Carcinogenicity

Available data are inadequate to evaluate carcinogenicity.

#### **Teratogenicity**

No relevant data found.

# Reproductive toxicity

In animal studies, did not interfere with reproduction. In animal studies, did not interfere with fertility.

#### Mutagenicity

In vitro genetic toxicity studies were negative in some cases and positive in other cases.

#### **Aspiration Hazard**

Based on physical properties, not likely to be an aspiration hazard.

# 12. ECOLOGICAL INFORMATION

Ecotoxicological information appears in this section when such data is available.

#### **Toxicity**

# White mineral oil (petroleum)

# Acute toxicity to fish

Material is practically non-toxic to aquatic organisms on an acute basis (LC50/EC50/EL50/LL50 >100 mg/L in the most sensitive species tested). LL50, Oncorhynchus mykiss (rainbow trout), static test, 96 Hour, > 100 mg/l, OECD Test Guideline 203

#### Acute toxicity to aquatic invertebrates

LL50, Daphnia magna (Water flea), static test, 48 Hour, > 100 mg/l, OECD Test Guideline 202

# Acute toxicity to algae/aquatic plants

NOEC, Pseudokirchneriella subcapitata (green algae), 72 Hour, 100 mg/l, OECD Test Guideline 201

## Chronic toxicity to fish

NOEC, Oncorhynchus mykiss (rainbow trout), 28 d, 1,000 mg/l

# Chronic toxicity to aquatic invertebrates

NOEC, Daphnia magna (Water flea), 21 d, 1,000 mg/l

#### Aluminum hydroxide benzoate stearate

# Acute toxicity to fish

Material is practically non-toxic to aquatic organisms on an acute basis (LC50/EC50/EL50/LL50 >100 mg/L in the most sensitive species tested).

For similar material(s):

LL50, Oncorhynchus mykiss (rainbow trout), semi-static test, 96 Hour, > 100 mg/l, OECD Test Guideline 203

#### Acute toxicity to aquatic invertebrates

For similar material(s):

EL50, Daphnia magna (Water flea), static test, 48 Hour, > 100 mg/l, OECD Test Guideline 202

# Acute toxicity to algae/aquatic plants

For similar material(s):

EL50, Pseudokirchneriella subcapitata (green algae), static test, 72 Hour, Growth rate, > 100 mg/l, OECD Test Guideline 201

# Zinc oxide

#### Acute toxicity to fish

Material is very highly toxic to aquatic organisms on an acute basis (LC50/EC50 <0.1 mg/L in the most sensitive species).

LC50, Oncorhynchus mykiss (rainbow trout), static test, 96 Hour, 0.14 - 1.1 mg/l

LC50, Danio rerio (zebra fish), 96 Hour, 1 - 10 mg/l

#### Acute toxicity to aquatic invertebrates

EC50, Daphnia magna (Water flea), 48 Hour, 1 - 10 mg/l

# Acute toxicity to algae/aquatic plants

IC50, Selenastrum capricornutum (green algae), 72 Hour, Growth rate, 0.136 mg/l

## Toxicity to bacteria

Based on data from similar materials

EC50, 3 Hour, 5.2 mg/l, OECD Test Guideline 209

#### Chronic toxicity to fish

NOEC, Danio rerio (zebra fish), 32 d, mortality, >= 0.540 mg/l

#### Chronic toxicity to aquatic invertebrates

NOEC, Daphnia magna (Water flea), 21 d, number of offspring, 0.04 mg/l

# Persistence and degradability

# White mineral oil (petroleum)

**Biodegradability:** Based on stringent OECD test guidelines, this material cannot be considered as readily biodegradable; however, these results do not necessarily mean that the material is not biodegradable under environmental conditions.

10-day Window: Fail **Biodegradation:** 0 - 24 % **Exposure time:** 28 d

Method: OECD Test Guideline 301B or Equivalent

Theoretical Oxygen Demand: 3.50 mg/mg

#### **Photodegradation**

Test Type: Half-life (indirect photolysis)

**Sensitization:** OH radicals **Atmospheric half-life:** 1.291 d

Method: Estimated.

# Aluminum hydroxide benzoate stearate

Biodegradability: Material is readily biodegradable. Passes OECD test(s) for ready

biodegradability.

For similar material(s): 10-day Window: Pass

Biodegradation: 79 % Exposure time: 28 d

Method: OECD Test Guideline 301B

#### Zinc oxide

**Biodegradability:** Biodegradability is not applicable to inorganic substances.

# **Bioaccumulative potential**

# White mineral oil (petroleum)

**Bioaccumulation:** Bioconcentration potential is high (BCF > 3000 or Log Pow between 5 and

Partition coefficient: n-octanol/water(log Pow): 5.18 Measured

Bioconcentration factor (BCF): 1,900 Fish

# Aluminum hydroxide benzoate stearate

Bioaccumulation: No relevant data found.

Zinc oxide

**Bioaccumulation:** Partitioning from water to n-octanol is not applicable.

Bioconcentration factor (BCF): 177 Fish

Mobility in soil

# White mineral oil (petroleum)

Potential for mobility in soil is low (Koc between 500 and 2000).

Partition coefficient (Koc): 510 Estimated.

#### Aluminum hydroxide benzoate stearate

No relevant data found.

#### Zinc oxide

No relevant data found.

# 13. DISPOSAL CONSIDERATIONS

Disposal methods: DO NOT DUMP INTO ANY SEWERS, ON THE GROUND, OR INTO ANY BODY OF WATER. All disposal practices must be in compliance with all Federal, State/Provincial and local laws and regulations. Regulations may vary in different locations. Waste characterizations and compliance with applicable laws are the responsibility solely of the waste generator. AS YOUR SUPPLIER, WE HAVE NO CONTROL OVER THE MANAGEMENT PRACTICES OR MANUFACTURING PROCESSES OF PARTIES HANDLING OR USING THIS MATERIAL. THE INFORMATION PRESENTED HERE PERTAINS ONLY TO THE PRODUCT AS SHIPPED IN ITS INTENDED CONDITION AS DESCRIBED IN MSDS SECTION: Composition Information. FOR UNUSED & UNCONTAMINATED PRODUCT, the preferred options include sending to a licensed, permitted: Incinerator or other thermal destruction device. For additional information, refer to: Handling & Storage Information, MSDS Section 7 Stability & Reactivity Information, MSDS Section 10 Regulatory Information, MSDS Section 15

**Treatment and disposal methods of used packaging:** Empty containers should be recycled or otherwise disposed of by an approved waste management facility. Waste characterizations and compliance with applicable laws are the responsibility solely of the waste generator. Do not re-use containers for any purpose.

# 14. TRANSPORT INFORMATION

DOT

Not regulated for transport

Classification for SEA transport (IMO-IMDG):

Proper shipping name ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID,

N.O.S.(Zinc oxide)

UN number UN 3077

Class 9
Packing group III

Marine pollutant Zinc oxide

Transport in bulk Consult IMO regulations before transporting ocean bulk

according to Annex I or II of MARPOL 73/78 and the

**IBC or IGC Code** 

## Classification for AIR transport (IATA/ICAO):

**Proper shipping name** Environmentally hazardous substance, solid, n.o.s. (Zinc

oxide)

UN number UN 3077

Class 9
Packing group III

This information is not intended to convey all specific regulatory or operational requirements/information relating to this product. Transportation classifications may vary by container volume and may be influenced by regional or country variations in regulations. Additional transportation system information can be obtained through an authorized sales or customer service representative. It is the responsibility of the transporting organization to follow all applicable laws, regulations and rules relating to the transportation of the material.

# 15. REGULATORY INFORMATION

Superfund Amendments and Reauthorization Act of 1986 Title III (Emergency Planning and Community Right-to-Know Act of 1986) Sections 311 and 312

No SARA Hazards

# Superfund Amendments and Reauthorization Act of 1986 Title III (Emergency Planning and Community Right-to-Know Act of 1986) Section 313

The following components are subject to reporting levels established by SARA Title III, Section 313:

Components CASRN
Zinc oxide 1314-13-2

# Comprehensive Environmental Response, Compensation, and Liability Act of 1980 (CERCLA) Section 103

This material does not contain any components with a CERCLA RQ.

#### Pennsylvania Right To Know

The following chemicals are listed because of the additional requirements of Pennsylvania law:

Components	CASRN
White mineral oil (petroleum)	8042-47-5
Calcium Carbonate	471-34-1
Aluminum hydroxide benzoate stearate	54326-11-3
Zinc oxide	1314-13-2

# **United States TSCA Inventory (TSCA)**

All components of this product are in compliance with the inventory listing requirements of the U.S. Toxic Substances Control Act (TSCA) Chemical Substance Inventory.

# 16. OTHER INFORMATION

# **Hazard Rating System**

0/

#### **NFPA**

	Health	Flammability	Instability
	0	1	0
Н	MIS		
	Health	Flammability	Physical Hazard

#### Revision

Identification Number: 4052324 / A776 / Issue Date: 02/25/2020 / Version: 7.0 Most recent revision(s) are noted by the bold, double bars in left-hand margin throughout this document.

0

Legend

Legena	
ACGIH	USA. ACGIH Threshold Limit Values (TLV)
С	Ceiling value not be exceeded at any time.
CAL PEL	California permissible exposure limits for chemical contaminants (Title 8, Article
	107)
NIOSH REL	USA. NIOSH Recommended Exposure Limits
OSHA P0	USA. OSHA - TABLE Z-1 Limits for Air Contaminants - 1910.1000
OSHA Z-1	USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air
	Contaminants
PEL	Permissible exposure limit
ST	STEL - 15-minute TWA exposure that should not be exceeded at any time during
	a workday
STEL	Short-term exposure limit
TWA	8-hour time weighted average
ST STEL	Permissible exposure limit STEL - 15-minute TWA exposure that should not be exceeded at any time durin a workday Short-term exposure limit

# Full text of other abbreviations

AICS - Australian Inventory of Chemical Substances; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation: DOT - Department of Transportation: DSL - Domestic Substances List (Canada): ECx - Concentration associated with x% response: EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO -International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO -International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 -Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No

Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

#### **Information Source and References**

This SDS is prepared by Product Regulatory Services and Hazard Communications Groups from information supplied by internal references within our company.

DDP SPECIALTY ELECTRONIC MATERIALS US 9, LLC urges each customer or recipient of this (M)SDS to study it carefully and consult appropriate expertise, as necessary or appropriate, to become aware of and understand the data contained in this (M)SDS and any hazards associated with the product. The information herein is provided in good faith and believed to be accurate as of the effective date shown above. However, no warranty, express or implied, is given. Regulatory requirements are subject to change and may differ between various locations. It is the buyer's/user's responsibility to ensure that his activities comply with all federal, state, provincial or local laws. The information presented here pertains only to the product as shipped. Since conditions for use of the product are not under the control of the manufacturer, it is the buyer's/user's duty to determine the conditions necessary for the safe use of this product. Due to the proliferation of sources for information such as manufacturer-specific (M)SDSs, we are not and cannot be responsible for (M)SDSs obtained from any source other than ourselves. If you have obtained an (M)SDS from another source or if you are not sure that the (M)SDS you have is current, please contact us for the most current version.

US