

SAFETY DATA SHEET

DDP SPECIALTY ELECTRONIC MATERIALS US 9, LLC

Product name: MOLYKOTE® Q2-3233 Bouncing Putty

Issue Date: 10/16/2018
Print Date: 06/19/2023

DDP SPECIALTY ELECTRONIC MATERIALS US 9, LLC encourages and expects you to read and understand the entire (M)SDS, as there is important information throughout the document. We expect you to follow the precautions identified in this document unless your use conditions would necessitate other appropriate methods or actions.

1. IDENTIFICATION

Product name: MOLYKOTE® Q2-3233 Bouncing Putty

Recommended use of the chemical and restrictions on use

Identified uses: Lubricants and lubricant additives

COMPANY IDENTIFICATION

DDP SPECIALTY ELECTRONIC MATERIALS US 9, LLC 974 Centre Road Wilmington DE 19805 UNITED STATES

Customer Information Number: 833-338-7668

SDSQuestion-NA@dupont.com

EMERGENCY TELEPHONE NUMBER

24-Hour Emergency Contact: 1-800-424-9300 **Local Emergency Contact:** 800-424-9300

2. HAZARDS IDENTIFICATION

Hazard classification

GHS classification in accordance with 29 CFR 1910.1200 Reproductive toxicity - Category 2

Label elements Hazard pictograms



Signal word: WARNING!

Hazards

Suspected of damaging fertility or the unborn child.

Precautionary statements

Prevention

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Wear protective gloves/ protective clothing/ eye protection/ face protection.

Response

IF exposed or concerned: Get medical advice/ attention.

Storage

Store locked up.

Disposal

Dispose of contents/ container to an approved waste disposal plant.

Other hazards

No data available

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical nature: Silicone compound

This product is a mixture.

Component	CASRN	Concentration	
Glycerol	56-81-5	>= 0.9 - <= 1.3 %	
Octamethyl Cyclotetrasiloxane	556-67-2	>= 0.75 - <= 1.01 %	

4. FIRST AID MEASURES

Description of first aid measures

General advice:

If potential for exposure exists refer to Section 8 for specific personal protective equipment.

Inhalation: Move person to fresh air; if effects occur, consult a physician.

Skin contact: Wash off with plenty of water.

Eye contact: Flush eyes thoroughly with water for several minutes. Remove contact lenses after the initial 1-2 minutes and continue flushing for several additional minutes. If effects occur, consult a physician, preferably an ophthalmologist.

Ingestion: No emergency medical treatment necessary.

Product name: MOLYKOTE® Q2-3233 Bouncing Putty

Most important symptoms and effects, both acute and delayed:

Aside from the information found under Description of first aid measures (above) and Indication of immediate medical attention and special treatment needed (below), any additional important symptoms and effects are described in Section 11: Toxicology Information.

Indication of any immediate medical attention and special treatment needed

Notes to physician: No specific antidote. Treatment of exposure should be directed at the control of symptoms and the clinical condition of the patient.

5. FIREFIGHTING MEASURES

Suitable extinguishing media: Water spray Alcohol-resistant foam Carbon dioxide (CO2) Dry chemical

Unsuitable extinguishing media: None known.

Special hazards arising from the substance or mixture

Hazardous combustion products: Boron oxides Silicon oxides Formaldehyde Carbon oxides

Unusual Fire and Explosion Hazards: Exposure to combustion products may be a hazard to health. Fire burns more vigorously than would be expected.

Advice for firefighters

Fire Fighting Procedures: Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. Use water spray to cool unopened containers. Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Remove undamaged containers from fire area if it is safe to do so. Evacuate area.

Special protective equipment for firefighters: In the event of fire, wear self-contained breathing apparatus. Use personal protective equipment.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures: Remove all sources of ignition. Use personal protective equipment. Follow safe handling advice and personal protective equipment recommendations.

Environmental precautions: Discharge into the environment must be avoided. Prevent further leakage or spillage if safe to do so. Prevent spreading over a wide area (e.g. by containment or oil barriers). Retain and dispose of contaminated wash water. Local authorities should be advised if significant spillages cannot be contained.

Methods and materials for containment and cleaning up: Soak up with inert absorbent material. Clean up remaining materials from spill with suitable absorbant. Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable. For large spills, provide dyking or other appropriate containment to keep material from spreading. If dyked material can be pumped, Sections 13 and 15 of this SDS provide information regarding certain local or national

requirements. Dispose of saturated absorbent or cleaning materials appropriately, since spontaneous heating may occur.

See sections: 7, 8, 11, 12 and 13.

7. HANDLING AND STORAGE

Precautions for safe handling: Avoid inhalation of vapour or mist. Do not swallow. Avoid contact with eyes. Avoid prolonged or repeated contact with skin. Take care to prevent spills, waste and minimize release to the environment. Handle in accordance with good industrial hygiene and safety practice.

Use only with adequate ventilation. See Engineering measures under EXPOSURE CONTROLS/PERSONAL PROTECTION section.

Conditions for safe storage: Keep in properly labelled containers. Store locked up. Store in accordance with the particular national regulations.

Do not store with the following product types: Strong oxidizing agents.

Unsuitable materials for containers: None known.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

If exposure limits exist, they are listed below. If no exposure limits are displayed, then no values are applicable.

Component	Regulation	Type of listing	Value/Notation
Glycerol	OSHA Z-1	TWA mist, respirable fraction	5 mg/m3
	OSHA Z-1	TWA mist, total dust	15 mg/m3
Octamethyl Cyclotetrasiloxane	US WEEL	TWA	10 ppm

Exposure controls

Engineering controls: Use local exhaust ventilation, or other engineering controls to maintain airborne levels below exposure limit requirements or guidelines. If there are no applicable exposure limit requirements or guidelines, general ventilation should be sufficient for most operations.

Individual protection measures

Eye/face protection: Use safety glasses (with side shields). **Skin protection**

Hand protection: Use gloves chemically resistant to this material when prolonged or frequently repeated contact could occur. Examples of preferred glove barrier materials include: Butyl rubber. Neoprene. Polyethylene. Ethyl vinyl alcohol laminate ("EVAL"). Styrene/butadiene rubber. Viton. Examples of acceptable glove barrier materials include: Chlorinated polyethylene. Natural rubber ("latex"). Nitrile/butadiene rubber ("nitrile" or "NBR"). Polyvinyl alcohol ("PVA"). Polyvinyl chloride ("PVC" or "vinyl"). NOTICE: The selection of a specific glove for a particular application and duration of use in a workplace should also take into account all relevant workplace factors such as, but not limited to: Other chemicals which may be handled, physical requirements (cut/puncture protection, dexterity, thermal protection), potential body reactions to glove materials, as well as the instructions/specifications provided by the glove supplier.

Other protection: Wear clean, body-covering clothing.

Respiratory protection: Respiratory protection should be worn when there is a potential to exceed the exposure limit requirements or guidelines. If there are no applicable exposure limit requirements or guidelines, wear respiratory protection when adverse effects, such as respiratory irritation or discomfort have been experienced, or where indicated by your risk assessment process. For most conditions no respiratory protection should be needed; however, if discomfort is experienced, use an approved air-purifying respirator. The following should be effective types of air-purifying respirators: Organic vapor cartridge.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance

Physical state viscous liquid

Color white Odor none

Odor Threshold

pH

No data available

No data available

Melting point/range

No data available

Freezing point

No data available

No data available

No data available

> 35 °C (> 95 °F)

Flash point closed cup >101.1 °C (214.0 °F)

Evaporation Rate (Butyl Acetate No data available

= 1)

Flammability (solid, gas)

Lower explosion limit

Upper explosion limit

Vapor Pressure

Relative Vapor Density (air = 1)

Not applicable

No data available

No data available

No data available

Relative Density (water = 1) 1.06

Water solubility

Partition coefficient: n
No data available

No data available

octanol/water

Auto-ignition temperatureNo data availableDecomposition temperatureNo data available

Kinematic Viscosity 10 m2/s at 25 °C (77 °F)

Explosive properties Not explosive

Oxidizing properties The substance or mixture is not classified as oxidizing.

Molecular weightNo data availableParticle sizeNot applicable

NOTE: The physical data presented above are typical values and should not be construed as a specification.

10. STABILITY AND REACTIVITY

Reactivity: Not classified as a reactivity hazard.

Chemical stability: Stable under normal conditions.

Possibility of hazardous reactions: Can react with strong oxidizing agents.

Conditions to avoid: None known.

Incompatible materials: Oxidizing agents

Hazardous decomposition products: Formaldehyde.

11. TOXICOLOGICAL INFORMATION

Toxicological information appears in this section when such data is available.

Acute toxicity

Acute oral toxicity

Very low toxicity if swallowed. Harmful effects not anticipated from swallowing small amounts.

As product: Single dose oral LD50 has not been determined.

Based on information for component(s):

LD50, Rat, > 2,000 mg/kg Estimated.

Acute dermal toxicity

Prolonged skin contact is unlikely to result in absorption of harmful amounts.

As product: The dermal LD50 has not been determined.

Based on information for component(s):

LD50, Rabbit, > 2,000 mg/kg Estimated.

Acute inhalation toxicity

No adverse effects expected from single exposure.

As product: The LC50 has not been determined.

Skin corrosion/irritation

Brief contact is essentially nonirritating to skin.

Serious eye damage/eye irritation

May cause slight temporary eye irritation.

Corneal injury is unlikely.

Sensitization

For skin sensitization:

Contains component(s) which did not cause allergic skin sensitization in guinea pigs.

For respiratory sensitization:

No relevant data found.

Specific Target Organ Systemic Toxicity (Single Exposure)

Evaluation of available data suggests that this material is not an STOT-SE toxicant.

Specific Target Organ Systemic Toxicity (Repeated Exposure)

For the minor component(s):

In animals, effects have been reported on the following organs:

Kidney.

Liver.

Respiratory tract.

Female reproductive organs.

Carcinogenicity

Results from a 2 year repeated vapour inhalation exposure study to rats of octamethylcyclotetrasiloxane (D4) indicate effects (benign uterine adenomas) in the uterus of female animals. This finding occurred at the highest exposure dose (700 ppm) only. Studies to date have not demonstrated if these effects occur through pathways that are relevant to humans. Repeated exposure in rats to D4 resulted in protoporphyrin accumulation in the liver. Without knowledge of the specific mechanism leading to the protoporphyrin accumulation the relevance of this finding to humans is unknown.

Teratogenicity

No relevant data found.

Reproductive toxicity

For the minor component(s): In laboratory animal studies, effects on reproduction have been seen only at doses that produced significant toxicity to the parent animals. In animal studies, has been shown to interfere with fertility.

Mutagenicity

Contains a component(s) which were negative in in vitro genetic toxicity studies. Contains component(s) which were negative in animal genetic toxicity studies.

Aspiration Hazard

Based on physical properties, not likely to be an aspiration hazard.

COMPONENTS INFLUENCING TOXICOLOGY:

Glycerol

Acute inhalation toxicity

LC50, Rat, 4 Hour, dust/mist, > 2.75 mg/l No deaths occurred following exposure to a saturated atmosphere.

Octamethyl Cyclotetrasiloxane

Acute inhalation toxicity

LC50, Rat, male and female, 4 Hour, dust/mist, 36 mg/l OECD Test Guideline 403

12. ECOLOGICAL INFORMATION

Ecotoxicological information appears in this section when such data is available.

Toxicity

Glycerol

Acute toxicity to fish

Material is practically non-toxic to aquatic organisms on an acute basis (LC50/EC50/EL50/LL50 >100 mg/L in the most sensitive species tested). LC50, Pimephales promelas (fathead minnow), static test, 96 Hour, >= 885 mg/l, Method Not

Specified.

Acute toxicity to aquatic invertebrates

LC50, Daphnia magna (Water flea), static test, 48 Hour, 1,955 mg/l, Method Not Specified.

Acute toxicity to algae/aquatic plants

EC50, Other, static test, 192 Hour, Growth inhibition (cell density reduction), 2,900 mg/l, Method Not Specified.

Toxicity to bacteria

EC50, activated sludge, 3 Hour, > 1,000 mg/l, OECD 209 Test

Octamethyl Cyclotetrasiloxane

Acute toxicity to fish

Not expected to be acutely toxic to aquatic organisms.

No toxicity at the limit of solubility

LC50, Oncorhynchus mykiss (rainbow trout), flow-through, 96 Hour, > 0.022 mg/l

No toxicity at the limit of solubility

LC50, Cyprinodon variegatus (sheepshead minnow), flow-through, 14 d, > 0.0063 mg/l

Acute toxicity to aquatic invertebrates

No toxicity at the limit of solubility

EC50, Mysidopsis bahia (opossum shrimp), flow-through test, 96 Hour, > 0.0091 mg/l

No toxicity at the limit of solubility

EC50, Daphnia magna (Water flea), flow-through test, 48 Hour, > 0.015 mg/l

Acute toxicity to algae/aquatic plants

No toxicity at the limit of solubility

ErC50, Pseudokirchneriella subcapitata (green algae), 72 Hour, Growth rate, > 0.022 mg/l

Chronic toxicity to fish

No toxicity at the limit of solubility

NOEC, Oncorhynchus mykiss (rainbow trout), 93 d, >= 0.0044 mg/l

Chronic toxicity to aquatic invertebrates

No toxicity at the limit of solubility

NOEC, Daphnia magna (Water flea), 21 d, >= 0.0079 mg/l

Persistence and degradability

Glycerol

Biodegradability: Material is readily biodegradable. Passes OECD test(s) for ready

biodegradability.

10-day Window: Not applicable **Biodegradation:** 63 %

Exposure time: 14 d

Method: OECD Test Guideline 301C or Equivalent

Page 8 of 12

Theoretical Oxygen Demand: 1.22 mg/mg

Octamethyl Cyclotetrasiloxane

Biodegradability: Material is expected to biodegrade very slowly (in the environment). Fails

to pass OECD/EEC tests for ready biodegradability.

10-day Window: Not applicable **Biodegradation:** 3.7 %

Exposure time: 28 d

Method: OECD Test Guideline 310

Stability in Water (1/2-life)

Hydrolysis, DT50, 69.3 - 144 Hour, pH 7, Half-life Temperature 24.6 °C, OECD Test Guideline 111

Photodegradation

Atmospheric half-life: 16 d

Method: Estimated.

Bioaccumulative potential

Glycerol

Bioaccumulation: Bioconcentration potential is low (BCF < 100 or Log Pow < 3). **Partition coefficient:** n-octanol/water(log Pow): -1.76 at 20 °C Measured

Octamethyl Cyclotetrasiloxane

Bioaccumulation: Bioconcentration potential is high (BCF > 3000 or Log Pow between 5 and 7).

Partition coefficient: n-octanol/water(log Pow): 6.49 Measured

Bioconcentration factor (BCF): 12,400 Pimephales promelas (fathead minnow) Measured

Mobility in soil

Glycerol

Potential for mobility in soil is very high (Koc between 0 and 50).

Given its very low Henry's constant, volatilization from natural bodies of water or moist soil is not expected to be an important fate process.

Partition coefficient (Koc): 1 Estimated.

Octamethyl Cyclotetrasiloxane

Expected to be relatively immobile in soil (Koc > 5000).

13. DISPOSAL CONSIDERATIONS

Disposal methods: DO NOT DUMP INTO ANY SEWERS, ON THE GROUND, OR INTO ANY BODY OF WATER. All disposal practices must be in compliance with all Federal, State/Provincial and local laws and regulations. Regulations may vary in different locations. Waste characterizations and compliance with applicable laws are the responsibility solely of the waste generator. AS YOUR SUPPLIER, WE HAVE NO CONTROL OVER THE MANAGEMENT PRACTICES OR MANUFACTURING PROCESSES OF PARTIES HANDLING OR USING THIS MATERIAL. THE INFORMATION PRESENTED HERE PERTAINS ONLY TO THE PRODUCT AS SHIPPED IN ITS INTENDED CONDITION AS DESCRIBED IN MSDS SECTION: Composition Information. FOR

Page 9 of 12

UNUSED & UNCONTAMINATED PRODUCT, the preferred options include sending to a licensed, permitted: Recycler. Reclaimer. Incinerator or other thermal destruction device. For additional information, refer to: Handling & Storage Information, MSDS Section 7 Stability & Reactivity Information, MSDS Section 15

Treatment and disposal methods of used packaging: Empty containers should be recycled or otherwise disposed of by an approved waste management facility. Waste characterizations and compliance with applicable laws are the responsibility solely of the waste generator. Do not re-use containers for any purpose.

14. TRANSPORT INFORMATION

DOT

Not regulated for transport

Classification for SEA transport (IMO-IMDG):

Not regulated for transport Consult IMO regulations before transporting ocean bulk

Transport in bulk according to Annex I or II of MARPOL 73/78 and the IBC or IGC Code

Classification for AIR transport (IATA/ICAO):

Not regulated for transport

This information is not intended to convey all specific regulatory or operational requirements/information relating to this product. Transportation classifications may vary by container volume and may be influenced by regional or country variations in regulations. Additional transportation system information can be obtained through an authorized sales or customer service representative. It is the responsibility of the transporting organization to follow all applicable laws, regulations and rules relating to the transportation of the material.

15. REGULATORY INFORMATION

Superfund Amendments and Reauthorization Act of 1986 Title III (Emergency Planning and Community Right-to-Know Act of 1986) Sections 311 and 312
Reproductive toxicity

Superfund Amendments and Reauthorization Act of 1986 Title III (Emergency Planning and Community Right-to-Know Act of 1986) Section 313

This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

Comprehensive Environmental Response, Compensation, and Liability Act of 1980 (CERCLA) Section 103

This material does not contain any components with a CERCLA RQ.

Pennsylvania Right To Know

The following chemicals are listed because of the additional requirements of Pennsylvania law:

Components
Dimethyl siloxane, hydroxy-terminated polymers with boric acid
Silicon dioxide
Castor oil derivative
Siloxanes and silicones, dimethyl
Glycerol

CASRN
104780-67-8
7631-86-9
Not available
63148-62-9
56-81-5

California Prop. 65

This product does not contain any chemicals known to State of California to cause cancer, birth defects, or any other reproductive harm.

United States TSCA Inventory (TSCA)

All components of this product are in compliance with the inventory listing requirements of the U.S. Toxic Substances Control Act (TSCA) Chemical Substance Inventory.

16. OTHER INFORMATION

Hazard Rating System

NFPA

	Health	Flammability	Instability
	0	1	0
н	MIS		

	Health	Flammability	Physical Hazard
	Λ*	1	0

^{* =} Chronic Effects (See Hazards Identification)

Revision

Identification Number: 1578766 / A776 / Issue Date: 10/16/2018 / Version: 6.0 Most recent revision(s) are noted by the bold, double bars in left-hand margin throughout this document.

Legend

OSHA Z-1	USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants	
TWA	8-hour time weighted average	
US WEEL	USA. Workplace Environmental Exposure Levels (WEEL)	

Full text of other abbreviations

AICS - Australian Inventory of Chemical Substances; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x%

growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration: ICAO - International Civil Aviation Organization: IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO -International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO -International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 -Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program: NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA -Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA -Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Information Source and References

This SDS is prepared by Product Regulatory Services and Hazard Communications Groups from information supplied by internal references within our company.

DDP SPECIALTY ELECTRONIC MATERIALS US 9, LLC urges each customer or recipient of this (M)SDS to study it carefully and consult appropriate expertise, as necessary or appropriate, to become aware of and understand the data contained in this (M)SDS and any hazards associated with the product. The information herein is provided in good faith and believed to be accurate as of the effective date shown above. However, no warranty, express or implied, is given. Regulatory requirements are subject to change and may differ between various locations. It is the buyer's/user's responsibility to ensure that his activities comply with all federal, state, provincial or local laws. The information presented here pertains only to the product as shipped. Since conditions for use of the product are not under the control of the manufacturer, it is the buyer's/user's duty to determine the conditions necessary for the safe use of this product. Due to the proliferation of sources for information such as manufacturer-specific (M)SDSs, we are not and cannot be responsible for (M)SDSs obtained from any source other than ourselves. If you have obtained an (M)SDS from another source or if you are not sure that the (M)SDS you have is current, please contact us for the most current version.

US