


DuPont™ Cyrel® EASY ESX

Built-in flat top dot digital plate for high quality printing

Applications

- Flexible packaging
- Tag and Label
- Folding cartons
- Beverage cartons



DuPont™ Cyrel® EASY ESX is the built-in flat top dot digital plate designed for the highest quality printing of halftones, linework and solids. Cyrel® EASY ESX has a smooth surface ideally suited for the micro-screening of solids.

Product Features and Benefits

- A plate that is based on a completely new polymer that delivers higher ink transfer and resolution.
- Ideally suited for extended gamut printing.
- The flat top dot shape compresses less, providing a more consistent and stable print surface.
- Higher latitude and better uniformity reduces press make ready time.
- The smaller shape flat top dot allows higher resolution and a very wide tonal range for crisper sharper printing results.
- The EASY ESX's smooth surface is perfect for special print effects based upon micro-screening.
- The simplified workflow reduces errors in the exposure/ laminate step.

Printing Ink and Solvent Compatibility

Cyrel® EASY ESX plates offer excellent compatibility with solvent-based, water-based inks and UV inks.

Process of Use

Expose the plate through the back to establish the floor and maximize sensitivity. Back exposure varies according to relief required. Remove the protective coversheet, and image the plate with the Cyrel® Digital Imager (CDI). Expose the front of the plate surface. Process the plate in the Cyrel® solvent processor to remove unexposed polymer. Finish the plate in a light finisher to eliminate surface tackiness.

Mounting

DuPont™ Cyrel® Microflex mounting devices are recommended for mounting Cyrel® EASY ESX plates. The double sided adhesive should first be applied to the cylinder or sleeve – not the plate – to ensure easier and precise laydown. The polyester base will maintain accurate register even with large plates.

Storage – Raw Material

Store unexposed plates in a cool area (4-32° C, 40-90° F), away from direct sources of heat. Humidity control is not required. Cyrel® EASY ESX is foam interleaved to provide maximum protection of the plate after manufacture, and during transportation and storage. Plates should be stacked flat. Plates should not be exposed to direct sunlight or excessive white light. Continuous exposure to very high ozone concentrations should be avoided.

Handling – Raw Material

Like all photopolymer plates, Cyrel® EASY ESX plates should be handled under UV free light; e.g., fluorescent tubes covered with amber sleeves.

Storage – Finished Plates

After printing, plates should be thoroughly cleaned with a compatible solvent before storing. They may be stored on cylinders, sleeves or demounted and stored flat.

DuPont™ Cyrel® EASY ESX

Built-in flat top dot digital plate for high quality printing

Sizes Available	Thickness	Durometer	Image Reproduction	Min. Positive Line Width	Min. Isolated Dot Size	Relief Depth
Cyrel® EASY ESX 45	1.14 mm (0.045")	74-76 Sh A	1-98% @ 190 lpi (75 L/cm)	0.10 mm (4 mil)	0.15 mm (150 micron)	0.60 mm
Cyrel® EASY ESX 67	1.70 mm (0.067")	65-67 Sh A	1-98% @ 190 lpi (75 L/cm)	0.10 mm (4 mil)	0.15 mm (150 micron)	0.70 mm
Cyrel® EASY ESX 100	2.54 mm (0.10")	58-60 Sh A	1-98% @ 190 lpi (75 L/cm)	0.10 mm (4 mil)	0.15 mm (150 micron)	0.90 mm
Cyrel® EASY ESX 112	2.84 mm (0.112")	53-55 Sh A	1-98% @ 150 lpi (60 L/cm)	0.20 mm (8 mil)	0.20 mm (200 micron)	0.95 mm

DuPont Advanced Printing brings together leading technologies and products for the printing and package printing industries. DuPont™ Cyrel® is one of the world's leading flexographic platemaking systems in digital and conventional formats, including DuPont™ Cyrel® brand photopolymer plates (analog and digital), Cyrel® platemaking equipment, Cyrel® round sleeves, Cyrel® plate mounting systems and the revolutionary Cyrel® FAST thermal system.

For more information on DuPont™ Cyrel® or other DuPont products, please visit our website.



cyrel.com/na

The information provided in this data sheet corresponds to our knowledge on the subject at the date of its publication. It may be subject to revision as new knowledge and experience becomes available. This information is not intended to substitute for any testing you may need to conduct to determine for yourself the suitability of our products for your particular purposes. Since we cannot anticipate all variations in end-use and disposal conditions, DuPont makes no warranties and assumes no liability in connection with any use of this information. It is intended for use by persons having technical skill, at their own discretion and risk. Nothing in this publication is to be considered as a license to operate under or a recommendation to infringe any patent right. DuPont™, the DuPont Oval Logo, and Cyrel® are trademarks or registered trademarks of DuPont or its affiliates. Copyright © 2019 DuPont de Nemours Inc. All rights reserved.

PDS-NA0061-EN (08/19)