

DuPont™ Cyrel® 1000 ECLF

Exposure, Light Finisher and Post Exposure Unit

DuPont™ Cyrel® 1000 ECLF can expose, post-expose and finish high quality photopolymer plates up to a format of 36" x 48" (900 x 1,200 mm).

Benefits

- Maximum plate size 36" x 48" (900 x 1,200 mm)
- Light integrator controlled exposure
- Clamshell design
- Outstanding vacuum draw down
- Anodized temperature controlled exposure bed
- Optimum productivity

Features

The Exposure section is a clamshell design holding 24 UV-A fluorescent tubes with built-in reflectors. One yellow control tube illuminates the exposure bed for inspection of the plate surface. Unique to this exposure unit is the anodized temperature controlled bed, closed loop system that controls the exposure bed temperature, which translates into predictable and consistent exposures. The unit is fitted with a light integrator that compensates for the decrease in light output as the tubes age. To meet the demanding needs of high quality plates, the user can easily customize the 25 basic exposure set-ups.

Each tube is constantly monitored by a light guide, giving the operator a visual indication. There are three counters imbedded in the PLC to keep track of the number of hours the UV-A and UV-C tubes have been in operation.

The Post Exposure and Light Finisher section hold 19 UV-C and 20 UV-A tubes. The PLC allows the user to perform post exposure and finishing simultaneously. The post exposure and finisher section has 25 basic set-ups that can be easily customized by the user.



DuPont™ Cyrel® 1000 ECLF

Exposure, Light Finisher and Post Exposure Unit

Technical Data

General	Details	Other Notes
Equipment Name	DuPont™ Cyrel® 1000 ECLF	Cooled exposure, post exposure and light finisher
SAP Article Number	MH74451A	
Plate Thickness	0.019" to 0.27"	0.5 mm to 7.0 mm
Max. Nominal Plate Width	36" (900 mm)	
Max. Nominal Plate Length	48" (1,200 mm)	
UV-A Tubes Wave Length	360 nm – 380 nm	
UV-C Tubes Wave Length	254 nm	
Electrical (Field Configurable)	370 / 440 Volt – 50 / 60 hz 208 / 240 Volt – 50 / 60 hz	3Ph / N / PE 3Ph / PE
Power (nominal)	10 kW	
Current (Nominal Load)	16 Amp @ 400 Volt; 26 Amp @ 230 Volt	
Connecting Wires	400 Volt configuration; 230 Volt configuration	5 x 4 mm ² ; 4 x 4 mm ²
Grounding	< 0.1 Ω	
Exhaust (Light Finisher)	Ø 5.5" (140 mm)	800 m ³ / h (min)
Environmental Data	Temperature range: 63°F to 82°F (17°C to 28°C)	Relative humidity from 10% to 80% non-condensing
Compressed Air Supply	NA	
Dimensions	Uncrated	Crated
L	61.0" (1,550 mm)	65.0" (1,650 mm)
W	70.9" (1,800 mm)	74.8" (1,900 mm)
H	41.8" (1,060 mm)	59.0" (1,500 mm)
H (open)	72.9" (1,850 mm)	
Weight	1,764 lbs (700 kg)	2,138 lbs (970 kg)
Color	DuPont Grey & DuPont Red	

The DuPont Industrial Solutions portfolio of products includes the DuPont™ Cyrel® brand of photopolymer plates (analog and digital), Cyrel® platemaking equipment, Cyrel® round sleeves and the revolutionary Cyrel® FAST thermal system.



cyrel.com/na

For more information on DuPont™ Cyrel® or other DuPont products, please visit our website.

The information provided in this data sheet corresponds to our knowledge on the subject at the date of its publication. It may be subject to revision as new knowledge and experience becomes available. This information is not intended to substitute for any testing you may need to conduct to determine for yourself the suitability of our products for your particular purposes. Since we cannot anticipate all variations in end-use and disposal conditions, DuPont makes no warranties and assumes no liability in connection with any use of this information. It is intended for use by persons having technical skill, at their own discretion and risk. Nothing in this publication is to be considered as a license to operate under or a recommendation to infringe any patent right.

DuPont™, the DuPont Oval Logo, and all products, unless otherwise noted, denoted with ™, ® or ® are trademarks, service marks or registered trademarks of affiliates of DuPont de Nemours, Inc. Copyright © 2021 DuPont de Nemours Inc. All rights reserved.

EDS-NA0002-EN (03/21)