

# DuPont™ Cyrel® 2000 ECLF

Exposure & Light Finisher

**DuPont™ Cyrel® 2000 ECLF exposes, post-exposes and finishes high quality photopolymer plates up to a maximum format of 47" x 60" (1,200 x 1,530 mm).**

## Benefits

- Maximum plate size 47" x 60" (1,200 x 1,530 mm)
- Clamshell design
- Anodized temperature controlled exposure bed
- Light integrator controlled exposure
- Outstanding vacuum draw down
- Optimum productivity

## Features

The exposure section is a clamshell design holding 38 UV-A fluorescent tubes with built-in reflectors. One yellow control tube illuminates the exposure bed for inspection of the plate surface. The unit is fitted with a light integrator that compensates for the decrease in light output as the tubes age. To meet the demanding needs of high quality plates, the user can easily customize the 25 basic exposure set-ups.

Each fluorescent tube is constantly monitored by a light guide, giving the operator a visual on/off indication. There are three time counters imbedded in the touch screen control panel to keep track of the number of hours the UV-A and UV-C tubes have been in operation.

The post exposure and light finisher section hold 26 UV-C and 27 UV-A tubes. The control panel allows the user to perform post exposure and finishing in a preferred sequence, or simultaneously. The post exposure and finisher section has 25 basic set-ups that can be easily customized.



# DuPont™ Cyrel® 2000 ECLF

Exposure & Light Finisher

## Technical Data

General	Details	Other Notes
<b>Equipment Name</b>	DuPont™ Cyrel® 2000 ECLF	Cooled exposure, post exposure and light finisher
<b>SAP Article Number</b>	MH99533	
<b>Plate Thickness</b>	0.019" to 0.27"	0.5 mm to 7.0 mm
<b>Max. Nominal Plate Width</b>	47" (1,200 mm)	
<b>Max. Nominal Plate Length</b>	60" (1,530 mm)	
<b>UV-A Tubes Wave Length</b>	360 nm – 380 nm	38 tubes (exposure); 27 tubes (light finisher)
<b>UV-C Tubes Wave Length</b>	254 nm	
<b>Electrical (Field Configurable)</b>	370 / 440 Volt – 50 / 60 hz 208 / 240 Volt – 50 / 60 hz	3Ph / N / PE 3Ph / PE
<b>Power (Nominal)</b>	10 kW	
<b>Current (Nominal Load)</b>	16 Amp @ 400 Volt; 26 Amp @ 230 Volt	
<b>Connecting Wires</b>	400 Volt configuration; 230 Volt configuration	5 x 10 mm <sup>2</sup> ; 4 x 10 mm <sup>2</sup>
<b>Grounding</b>	≤ 0.1 Ω	Ground bar to equipment frame and to electrical supply ground
<b>Exhaust</b>	Ø 6.3" (160 mm)	1500 m <sup>3</sup> / h (min)
<b>Environmental Data</b>	Temperature range: 63°F to 82°F (17°C to 28°C)	Relative humidity 20% to 85% non-condensing
<b>Compressed Air Supply</b>	7 bar minimum	80 psi min
<b>Dimensions</b>	<b>Uncrated</b>	<b>Crated</b>
<b>D</b>	68.0" (1,820 mm)	78.8" (2,000 mm)
<b>W</b>	104.0" (2,620 mm)	113.0" (2,870 mm)
<b>H</b>	43.0" (1,100 mm)	59.5" (1,510 mm)
<b>H (open)</b>	94.0" (2,450 mm)	
<b>Weight</b>	2,205 lbs (1,000 kg)	1,500 kg (3,307 lbs)
<b>Color</b>	DuPont Grey & DuPont Red	

DuPont Industrial Solutions brings together leading technologies and products for the printing and package printing industries. DuPont™ Cyrel® is one of the world's leading flexographic platemaking systems in digital and conventional formats, including DuPont™ Cyrel® brand photopolymer plates (analog and digital), Cyrel® platemaking equipment, Cyrel® round sleeves, Cyrel® plate mounting systems and the revolutionary Cyrel® FAST thermal system.



[cyrel.com/na](http://cyrel.com/na)

For more information on DuPont™ Cyrel® or other DuPont products, please visit our website.

The information provided in this data sheet corresponds to our knowledge on the subject at the date of its publication. It may be subject to revision as new knowledge and experience becomes available. This information is not intended to substitute for any testing you may need to conduct to determine for yourself the suitability of our products for your particular purposes. Since we cannot anticipate all variations in end-use and disposal conditions, DuPont makes no warranties and assumes no liability in connection with any use of this information. It is intended for use by persons having technical skill, at their own discretion and risk. Nothing in this publication is to be considered as a license to operate under or a recommendation to infringe any patent right.

DuPont™, the DuPont Oval Logo, and all products, unless otherwise noted, denoted with ™, ® or ® are trademarks, service marks or registered trademarks of affiliates of DuPont de Nemours, Inc. Copyright © 2021 DuPont de Nemours Inc. All rights reserved.

EDS-NA0010-EN (03/21)