



SAFETY DATA SHEET

ROHM AND HAAS ELECTRONIC MATERIALS LLC

Product name: CYCLOTENE™ 3022 - 63 Advanced Electronics Resin

Issue Date: 11/15/2023

Print Date: 11/21/2023

ROHM AND HAAS ELECTRONIC MATERIALS LLC encourages and expects you to read and understand the entire (M)SDS, as there is important information throughout the document. We expect you to follow the precautions identified in this document unless your use conditions would necessitate other appropriate methods or actions.

1. IDENTIFICATION

Product name: CYCLOTENE™ 3022 - 63 Advanced Electronics Resin

Recommended use of the chemical and restrictions on use

Identified uses: For industrial use: use in the electronic packaging of semiconductor devices

Uses advised against: We recommend that you use this product in a manner consistent with the listed use. If your intended use is not consistent with the stated use, please contact your sales or technical service representative.

COMPANY IDENTIFICATION

ROHM AND HAAS ELECTRONIC MATERIALS LLC
455 FOREST STREET
MARLBOROUGH MA 01752
UNITED STATES

Customer Information Number:

833-338-7668
SDSQuestion-NA@dupont.com

EMERGENCY TELEPHONE NUMBER

24-Hour Emergency Contact: 1-800-424-9300

Local Emergency Contact: 800-424-9300

2. HAZARDS IDENTIFICATION

Hazard classification

GHS classification in accordance with 29 CFR 1910.1200

Flammable liquids - Category 3

Skin irritation - Category 2

Eye irritation - Category 2A

Specific target organ toxicity - single exposure - Category 3

Aspiration hazard - Category 1

Short-term (acute) aquatic hazard - Category 2

Long-term (chronic) aquatic hazard - Category 2

Label elements

Hazard pictograms



Signal word: **DANGER!**

Hazards

Flammable liquid and vapour.
May be fatal if swallowed and enters airways.
Causes skin irritation.
Causes serious eye irritation.
May cause respiratory irritation.
Toxic to aquatic life with long lasting effects.

Precautionary statements

Prevention

Keep away from heat/ sparks/ open flames/ hot surfaces. No smoking.
Keep container tightly closed.
Ground/bond container and receiving equipment.
Use explosion-proof electrical/ ventilating/ lighting equipment.
Use only non-sparking tools.
Take precautionary measures against static discharge.
Avoid breathing mist or vapours.
Wash skin thoroughly after handling.
Use only outdoors or in a well-ventilated area.
Avoid release to the environment.
Wear protective gloves/ eye protection/ face protection.

Response

IF SWALLOWED: Immediately call a POISON CENTER/ doctor.
IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower.
IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/ doctor if you feel unwell.
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
Do NOT induce vomiting.
If skin irritation occurs: Get medical advice/ attention.
If eye irritation persists: Get medical advice/ attention.
Take off contaminated clothing and wash before reuse.
In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.
Collect spillage.

Storage

Store in a well-ventilated place. Keep container tightly closed.
Store in a well-ventilated place. Keep cool.
Store locked up.

Disposal

Dispose of contents/ container to an approved waste disposal plant.

Other hazards

No data available

3. COMPOSITION/INFORMATION ON INGREDIENTS

This product is a mixture.

Component	CASRN	Concentration
B-Staged divinylsiloxane-bis-benzocyclobutene resin	124221-30-3	>= 60.0 - <= 66.0 %
1,3,5-Trimethylbenzene	108-67-8	>= 30.0 - <= 40.0 %
Quinoline, 1,2-dihydro-2,2,4-trimethyl-, homopolymer	26780-96-1	>= 0.1 - <= 5.0 %
1,2,4-Trimethylbenzene	95-63-6	>= 0.1 - <= 1.0 %

Note

The specific chemical identity and/or exact percentage (concentration) of composition has been withheld as a trade secret.

4. FIRST AID MEASURES

Description of first aid measures

General advice:

First Aid responders should pay attention to self-protection and use the recommended protective clothing (chemical resistant gloves, splash protection). If potential for exposure exists refer to Section 8 for specific personal protective equipment.

Inhalation: Move person to fresh air; if effects occur, consult a physician.

Skin contact: Remove material from skin immediately by washing with soap and plenty of water. Remove contaminated clothing and shoes while washing. Seek medical attention if irritation persists. Wash clothing before reuse. Discard items which cannot be decontaminated, including leather articles such as shoes, belts and watchbands. Suitable emergency safety shower facility should be available in work area.

Eye contact: Flush eyes thoroughly with water for several minutes. Remove contact lenses after the initial 1-2 minutes and continue flushing for several additional minutes. If effects occur, consult a physician, preferably an ophthalmologist. Suitable emergency eye wash facility should be available in work area.

Ingestion: Do not induce vomiting. Call a physician and/or transport to emergency facility immediately.

Most important symptoms and effects, both acute and delayed:

Aside from the information found under Description of first aid measures (above) and Indication of immediate medical attention and special treatment needed (below), any additional important symptoms and effects are described in Section 11: Toxicology Information.

Indication of any immediate medical attention and special treatment needed

Notes to physician: The decision of whether to induce vomiting or not should be made by a physician. If lavage is performed, suggest endotracheal and/or esophageal control. Danger from lung aspiration must be weighed against toxicity when considering emptying the stomach. No specific antidote. Treatment of exposure should be directed at the control of symptoms and the clinical condition of the patient. Skin contact may aggravate preexisting dermatitis.

5. FIREFIGHTING MEASURES

Suitable extinguishing media: Water fog or fine spray. Dry chemical fire extinguishers. Carbon dioxide fire extinguishers. Foam. General purpose synthetic foams (including AFFF type) or protein foams are preferred if available. Alcohol resistant foams (ATC type) may function.

Unsuitable extinguishing media: No data available

Special hazards arising from the substance or mixture

Hazardous combustion products: During a fire, smoke may contain the original material in addition to combustion products of varying composition which may be toxic and/or irritating. Combustion products may include and are not limited to: Carbon monoxide. Carbon dioxide. Combustion products may include trace amounts of: Aromatic hydrocarbons.

Unusual Fire and Explosion Hazards: Container may vent and/or rupture due to fire. Violent steam generation or eruption may occur upon application of direct water stream to hot liquids. Electrically ground and bond all equipment. Flammable mixtures of this product are readily ignited even by static discharge. Vapors are heavier than air and may travel a long distance and accumulate in low lying areas. Ignition and/or flash back may occur. Dense smoke is produced when product burns.

Advice for firefighters

Fire Fighting Procedures: Keep people away. Isolate fire and deny unnecessary entry. Stay upwind. Keep out of low areas where gases (fumes) can accumulate. Use water spray to cool fire exposed containers and fire affected zone until fire is out and danger of reignition has passed. Fight fire from protected location or safe distance. Consider the use of unmanned hose holders or monitor nozzles. Do not use direct water stream. May spread fire. Eliminate ignition sources. Burning liquids may be moved by flushing with water to protect personnel and minimize property damage. Avoid accumulation of water. Product may be carried across water surface spreading fire or contacting an ignition source. Contain fire water run-off if possible. Fire water run-off, if not contained, may cause environmental damage. Review the "Accidental Release Measures" and the "Ecological Information" sections of this (M)SDS.

Special protective equipment for firefighters: Wear positive-pressure self-contained breathing apparatus (SCBA) and protective fire fighting clothing (includes fire fighting helmet, coat, trousers, boots, and gloves). If protective equipment is not available or not used, fight fire from a protected location or safe distance.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures: Isolate area. Keep unnecessary and unprotected personnel from entering the area. Vapor explosion hazard. Keep out of sewers. Ventilate area of leak or spill. Keep upwind of spill. Keep personnel out of low areas. No smoking in area. Eliminate all sources of ignition in vicinity of spill or released vapor to avoid fire or explosion. See Section 10 for more specific information. Refer to section 7, Handling, for additional precautionary measures. Use appropriate safety equipment. For additional information, refer to Section 8, Exposure Controls and Personal Protection.

Environmental precautions: Material may float on water and any runoff may create an explosion or fire hazard if ignited. Prevent from entering into soil, ditches, sewers, waterways and/or groundwater. See Section 12, Ecological Information.

Methods and materials for containment and cleaning up: Contain spilled material if possible. Large spills: Pump with explosion-proof equipment. If available, use foam to smother or suppress. Use non-sparking tools in cleanup operations. Small spills: Absorb with materials such as: Sand. Sawdust. Collect in suitable and properly labeled containers. See Section 13, Disposal Considerations, for additional information.

7. HANDLING AND STORAGE

Precautions for safe handling: Avoid contact with eyes, skin, and clothing. Avoid breathing vapor. Do not swallow. Wash thoroughly after handling. Keep away from heat, sparks and flame. Keep container closed. Use with adequate ventilation. No smoking, open flames or sources of ignition in handling and storage area. Vapors are heavier than air and may travel a long distance and accumulate in low lying areas. Ignition and/or flash back may occur. Electrically ground and bond all equipment. Use of non-sparking or explosion-proof equipment may be necessary, depending upon the type of operation. Containers, even those that have been emptied, can contain vapors. Do not cut, drill, grind, weld, or perform similar operations on or near empty containers. See Section 8, EXPOSURE CONTROLS AND PERSONAL PROTECTION.

Conditions for safe storage: Minimize sources of ignition, such as static build-up, heat, spark or flame. See Section 10 for more specific information.

Storage stability

Storage temperature: <= 40 °C (<= 104 °F)

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

If exposure limits exist, they are listed below. If no exposure limits are displayed, then no values are applicable.

Component	Regulation	Type of listing	Value
1,3,5-Trimethylbenzene	ACGIH	TWA	10 ppm
	NIOSH REL	TWA	125 mg/m3 25 ppm
	OSHA P0	TWA	125 mg/m3 25 ppm

1,2,4-Trimethylbenzene	ACGIH	TWA	25 ppm
	CAL PEL	PEL	125 mg/m3 25 ppm
	OSHA P0	TWA	125 mg/m3 25 ppm
	ACGIH	TWA	10 ppm
Further information: A4: Not classifiable as a human carcinogen			

Exposure controls

Engineering measures: Use engineering controls to maintain airborne level below exposure limit requirements or guidelines. If there are no applicable exposure limit requirements or guidelines, use only with adequate ventilation. Local exhaust ventilation may be necessary for some operations.

Individual protection measures

Eye/face protection: Use safety glasses (with side shields). If exposure causes eye discomfort, use a full-face respirator.

Skin protection

Hand protection: Use gloves chemically resistant to this material. Examples of preferred glove barrier materials include: Polyethylene. Ethyl vinyl alcohol laminate ("EVAL"). Viton. Polyvinyl chloride ("PVC" or "vinyl"). Styrene/butadiene rubber. Polyvinyl alcohol ("PVA"). Examples of acceptable glove barrier materials include: Butyl rubber. Neoprene. Chlorinated polyethylene. Natural rubber ("latex"). Nitrile/butadiene rubber ("nitrile" or "NBR"). NOTICE: The selection of a specific glove for a particular application and duration of use in a workplace should also take into account all relevant workplace factors such as, but not limited to: Other chemicals which may be handled, physical requirements (cut/puncture protection, dexterity, thermal protection), potential body reactions to glove materials, as well as the instructions/specifications provided by the glove supplier.

Other protection: Use protective clothing chemically resistant to this material. Selection of specific items such as face shield, boots, apron, or full body suit will depend on the task.

Respiratory protection: Respiratory protection should be worn when there is a potential to exceed the exposure limit requirements or guidelines. If there are no applicable exposure limit requirements or guidelines, wear respiratory protection when adverse effects, such as respiratory irritation or discomfort have been experienced, or where indicated by your risk assessment process.

The following should be effective types of air-purifying respirators: Organic vapor cartridge.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance

Physical state	Liquid.
Color	Yellow
Odor	Aromatic
Odor Threshold	No test data available
pH	Not applicable
Melting point/range	Not applicable
Freezing point	No test data available
Boiling point (760 mmHg)	162 °C (324 °F) <i>Literature</i>
Flash point	closed cup 44 °C (111 °F) <i>Literature</i> (setaflash)
Evaporation Rate (Butyl Acetate = 1)	No test data available
Flammability (solid, gas)	No

Lower explosion limit	0.88 % vol <i>Literature</i>
Upper explosion limit	6.1 % vol <i>Literature</i>
Vapor Pressure	3.3 hPa at 25 °C (77 °F) <i>Literature</i>
Relative Vapor Density (air = 1)	4.1 <i>Literature</i>
Relative Density (water = 1)	0.99 at 25 °C (77 °F)
Water solubility	<i>Literature</i>
Partition coefficient: n-octanol/water	This product is a mixture. See Section 12 for individual component data.
Auto-ignition temperature	559 °C (1,038 °F) <i>Literature</i>
Decomposition temperature	No test data available
Kinematic Viscosity	870 mm ² /s at 25 °C (77 °F) <i>Supplier</i>
Explosive properties	No data available
Oxidizing properties	No data available
Molecular weight	No test data available

NOTE: The physical data presented above are typical values and should not be construed as a specification.

10. STABILITY AND REACTIVITY

Reactivity: Not classified as a reactivity hazard.

Chemical stability: Stable under recommended storage conditions. See Storage, Section 7. Unstable at elevated temperatures.

Possibility of hazardous reactions: Can occur. Can react with itself at temperatures above 100°C (212°F).

Conditions to avoid: Avoid temperatures above 40°C (104°F). Can react with itself at temperatures above 100°C (212°F). Active ingredient decomposes at elevated temperatures. Avoid static discharge.

Incompatible materials: Avoid contact with: Strong oxidizers.

Hazardous decomposition products: Decomposition products depend upon temperature, air supply and the presence of other materials.

11. TOXICOLOGICAL INFORMATION

Toxicological information appears in this section when such data is available.

Acute toxicity

Acute oral toxicity

Low toxicity if swallowed. Small amounts swallowed incidentally as a result of normal handling operations are not likely to cause injury; however, swallowing larger amounts may cause injury.
Single dose oral LD50 has not been determined.

Acute dermal toxicity

Prolonged skin contact is unlikely to result in absorption of harmful amounts.
The dermal LD50 has not been determined.

Acute inhalation toxicity

Prolonged exposure is not expected to cause adverse effects. Vapor may cause irritation of the upper respiratory tract (nose and throat).
The LC50 has not been determined.

Skin corrosion/irritation

Brief contact may cause slight skin irritation with local redness.
Prolonged contact may cause moderate skin irritation with local redness.
May cause drying and flaking of the skin.

Serious eye damage/eye irritation

May cause eye irritation.
Vapor may cause eye irritation experienced as mild discomfort and redness.

Sensitization

A component in this mixture has caused allergic skin reactions in humans.

For respiratory sensitization:
No specific, relevant data available for assessment.

Specific Target Organ Systemic Toxicity (Single Exposure)

May cause respiratory irritation.

Specific Target Organ Systemic Toxicity (Repeated Exposure)

For the component(s) tested:
Based on available data, repeated exposures are not anticipated to cause significant adverse effects.

Carcinogenicity

No relevant data found.

Teratogenicity

Contains component(s) which did not cause birth defects in animals; other fetal effects occurred only at doses toxic to the mother.

Reproductive toxicity

In animal studies on component(s), effects on reproduction were seen only at doses that produced significant toxicity to the parent animals.

Mutagenicity

For the component(s) tested: In vitro genetic toxicity studies were negative. Animal genetic toxicity studies were negative.

Aspiration Hazard

May be fatal if swallowed and enters airways.

COMPONENTS INFLUENCING TOXICOLOGY:

B-Staged divinylsiloxane-bis-benzocyclobutene resin

Acute oral toxicity

Single dose oral LD50 has not been determined.

Acute dermal toxicity

The dermal LD50 has not been determined.

Acute inhalation toxicity

The LC50 has not been determined.

1,3,5-Trimethylbenzene

Acute oral toxicity

Information given is based on data obtained from similar substances. LD50, Rat, 6,000 mg/kg
EC Directive 92/69/EEC B.1 Acute Toxicity (Oral)

Acute dermal toxicity

Information given is based on data obtained from similar substances. LD50, Rat, > 2,000
mg/kg

Acute inhalation toxicity

An LC50/inhalation/4h/rat could not be determined because no mortality of rats was observed
at the maximum achievable concentration. Respiratory effects. Information given is based on
data obtained from similar substances. LC50, Rat, 4 Hour, vapour, > 10.2 mg/l

Quinoline, 1,2-dihydro-2,2,4-trimethyl-, homopolymer

Acute oral toxicity

LD50, Rat, > 2,000 mg/kg

Acute dermal toxicity

LD50, Rabbit, > 5,100 mg/kg Estimated.

Acute inhalation toxicity

The LC50 has not been determined.

1,2,4-Trimethylbenzene

Acute oral toxicity

LD50, Rat, > 3,400 mg/kg

Acute dermal toxicity

LD50, Rabbit, > 3,160 mg/kg

Acute inhalation toxicity

LC50, Rat, 4 Hour, vapour, 18 mg/l

12. ECOLOGICAL INFORMATION

Ecotoxicological information appears in this section when such data is available.

Toxicity

B-Staged divinylsiloxane-bis-benzocyclobutene resin

Acute toxicity to fish

No relevant data found.

1,3,5-Trimethylbenzene

Acute toxicity to fish

LC50, Carassius auratus (goldfish), 96 Hour, 12.52 mg/l

Acute toxicity to aquatic invertebrates

LC50, Daphnia magna (Water flea), 48 Hour, 6 mg/l, OECD Test Guideline 202

Acute toxicity to algae/aquatic plants

EC50, Desmodesmus subspicatus (green algae), 48 Hour, 53 mg/l

EC10, Desmodesmus subspicatus (green algae), 48 Hour, 16 mg/l

Chronic toxicity to fish

NOEC, 30 d, 0.277 mg/l

Chronic toxicity to aquatic invertebrates

NOEC, Daphnia magna (Water flea), 21 d, 0.4 mg/l

Quinoline, 1,2-dihydro-2,2,4-trimethyl-, homopolymer

Acute toxicity to fish

Material is slightly toxic to aquatic organisms on an acute basis (LC50/EC50 between 10 and 100 mg/L in the most sensitive species tested).

LC50, Pimephales promelas (fathead minnow), 96 Hour, 64 mg/l, OECD Test Guideline 203 or Equivalent

Acute toxicity to aquatic invertebrates

EC50, Daphnia magna (Water flea), 24 Hour, > 1,000 mg/l

Acute toxicity to algae/aquatic plants

EL50, Desmodesmus subspicatus (green algae), 72 Hour, > 100 mg/l, Directive 67/548/EEC, Annex V, C.3.

Toxicity to bacteria

EC50, Bacteria, 3 Hour, > 10,000 mg/l

1,2,4-Trimethylbenzene

Acute toxicity to fish

Material is moderately toxic to aquatic organisms on an acute basis (LC50/EC50 between 1 and 10 mg/L in the most sensitive species tested).

LC50, Pimephales promelas (fathead minnow), flow-through test, 96 Hour, 7.7 mg/l

Acute toxicity to aquatic invertebrates

EC50, Daphnia magna (Water flea), 48 Hour, 3.6 mg/l

Acute toxicity to algae/aquatic plants

EC50, Desmodesmus subspicatus (green algae), 96 Hour, 2.356 mg/l

Persistence and degradability

B-Staged divinylsiloxane-bis-benzocyclobutene resin

Biodegradability: No relevant data found.

1,3,5-Trimethylbenzene

Biodegradability: Not readily biodegradable.

10-day Window: Fail

Biodegradation: 61 %

Exposure time: 28 d

Method: OECD Test Guideline 301

Theoretical Oxygen Demand: 3.19 mg/mg

Photodegradation

Test Type: Half-life (indirect photolysis)

Sensitization: OH radicals

Atmospheric half-life: 3.7 Hour

Method: Estimated.

Quinoline, 1,2-dihydro-2,2,4-trimethyl-, homopolymer

Biodegradability: Material is not readily biodegradable according to OECD/EEC guidelines.

10-day Window: Not applicable

Biodegradation: 0 %

Exposure time: 28 d

Method: OECD Test Guideline 301C or Equivalent

1,2,4-Trimethylbenzene

Biodegradability: Material is ultimately biodegradable (reaches > 70% mineralization in OECD test(s) for inherent biodegradability).

Biodegradation: 100 %

Exposure time: 1 d

Theoretical Oxygen Demand: 3.19 mg/mg

Photodegradation

Test Type: Half-life (indirect photolysis)

Sensitization: OH radicals

Atmospheric half-life: 0.641 d

Method: Estimated.

Bioaccumulative potential

B-Staged divinylsiloxane-bis-benzocyclobutene resin

Bioaccumulation: No bioconcentration is expected because of the relatively high molecular weight (MW greater than 1000).

1,3,5-Trimethylbenzene

Bioaccumulation: Bioaccumulation is unlikely.

Partition coefficient: n-octanol/water(log Pow): 3.42 at 20 °C

Quinoline, 1,2-dihydro-2,2,4-trimethyl-, homopolymer

Bioaccumulation: Bioconcentration potential is low (BCF less than 100 or log Pow greater than 7).

Partition coefficient: n-octanol/water(log Pow): 1.2 - 7.7

1,2,4-Trimethylbenzene

Bioaccumulation: Bioconcentration potential is moderate (BCF between 100 and 3000 or Log Pow between 3 and 5).

Partition coefficient: n-octanol/water(log Pow): 3.63 Measured

Bioconcentration factor (BCF): 33 - 275 Cyprinus carpio (Carp) 56 d Measured

Mobility in soil

B-Staged divinylsiloxane-bis-benzocyclobutene resin

No relevant data found.

1,3,5-Trimethylbenzene

Potential for mobility in soil is low (Koc between 500 and 2000).

Partition coefficient (Koc): 741.65 Estimated.

Quinoline, 1,2-dihydro-2,2,4-trimethyl-, homopolymer

No relevant data found.

1,2,4-Trimethylbenzene

Potential for mobility in soil is low (Koc between 500 and 2000).

Partition coefficient (Koc): 720 Estimated.

13. DISPOSAL CONSIDERATIONS

Disposal methods: DO NOT DUMP INTO ANY SEWERS, ON THE GROUND, OR INTO ANY BODY OF WATER. All disposal practices must be in compliance with all Federal, State/Provincial and local laws and regulations. Regulations may vary in different locations. Waste characterizations and compliance with applicable laws are the responsibility solely of the waste generator. AS YOUR SUPPLIER, WE HAVE NO CONTROL OVER THE MANAGEMENT PRACTICES OR MANUFACTURING PROCESSES OF PARTIES HANDLING OR USING THIS MATERIAL. THE INFORMATION PRESENTED HERE PERTAINS ONLY TO THE PRODUCT AS SHIPPED IN ITS INTENDED CONDITION AS DESCRIBED IN MSDS SECTION: Composition Information. FOR UNUSED & UNCONTAMINATED PRODUCT, the preferred options include sending to a licensed, permitted: Incinerator or other thermal destruction device.

Contaminated packaging: Containers, even those that have been emptied, can contain vapors. Do not cut, drill, grind, weld, or perform similar operations on or near empty containers.

14. TRANSPORT INFORMATION

DOT

Proper shipping name	Resin solution
UN number	UN 1866
Class	3

Packing group III

Classification for SEA transport (IMO-IMDG):

Proper shipping name RESIN SOLUTION
UN number UN 1866
Class 3
Packing group III
Marine pollutant 1,3,5-Trimethylbenzene
Transport in bulk Consult IMO regulations before transporting ocean bulk
according to Annex I or II
of MARPOL 73/78 and the
IBC or IGC Code

Classification for AIR transport (IATA/ICAO):

Proper shipping name Resin solution
UN number UN 1866
Class 3
Packing group III

This information is not intended to convey all specific regulatory or operational requirements/information relating to this product. Transportation classifications may vary by container volume and may be influenced by regional or country variations in regulations. Additional transportation system information can be obtained through an authorized sales or customer service representative. It is the responsibility of the transporting organization to follow all applicable laws, regulations and rules relating to the transportation of the material.

15. REGULATORY INFORMATION

Superfund Amendments and Reauthorization Act of 1986 Title III (Emergency Planning and Community Right-to-Know Act of 1986) Sections 311 and 312

Fire Hazard
Acute Health Hazard
Chronic Health Hazard
Flammable (gases, aerosols, liquids, or solids)
Skin corrosion or irritation
Serious eye damage or eye irritation
Specific target organ toxicity (single or repeated exposure)
Aspiration hazard

Superfund Amendments and Reauthorization Act of 1986 Title III (Emergency Planning and Community Right-to-Know Act of 1986) Section 313

This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

California Prop. 65

This product does not contain any chemicals known to State of California to cause cancer, birth defects, or any other reproductive harm.

United States TSCA Inventory (TSCA)

All components of this product are in compliance with the Active inventory listing requirements of the U.S. Toxic Substances Control Act (TSCA) Chemical Substance Inventory.

16. OTHER INFORMATION

Revision

Identification Number: 81723 / 1304 / Issue Date: 11/15/2023 / Version: 7.0

Most recent revision(s) are noted by the bold, double bars in left-hand margin throughout this document.

Legend

ACGIH	USA. ACGIH Threshold Limit Values (TLV)
CAL PEL	California permissible exposure limits for chemical contaminants (Title 8, Article 107)
NIOSH REL	USA. NIOSH Recommended Exposure Limits
OSHA P0	USA. Table Z-1-A Limits for Air Contaminants (1989 vacated values)
PEL	Permissible exposure limit
TWA	8-hour time weighted average

Full text of other abbreviations

AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European

Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TECl - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Information Source and References

This SDS is prepared by Product Regulatory Services and Hazard Communications Groups from information supplied by internal references within our company.

ROHM AND HAAS ELECTRONIC MATERIALS LLC urges each customer or recipient of this (M)SDS to study it carefully and consult appropriate expertise, as necessary or appropriate, to become aware of and understand the data contained in this (M)SDS and any hazards associated with the product. The information herein is provided in good faith and believed to be accurate as of the effective date shown above. However, no warranty, express or implied, is given. Regulatory requirements are subject to change and may differ between various locations. It is the buyer's/user's responsibility to ensure that his activities comply with all federal, state, provincial or local laws. The information presented here pertains only to the product as shipped. Since conditions for use of the product are not under the control of the manufacturer, it is the buyer's/user's duty to determine the conditions necessary for the safe use of this product. Due to the proliferation of sources for information such as manufacturer-specific (M)SDSs, we are not and cannot be responsible for (M)SDSs obtained from any source other than ourselves. If you have obtained an (M)SDS from another source or if you are not sure that the (M)SDS you have is current, please contact us for the most current version.

US