

Medical lubricant coatings you can rely on





Products and features

Liveo™ 360 Medical Fluid

- Silicone lubricant for glass, plastics, rubbers, metals
- Water repellent/hydrophobic
- Can be spray-applied undiluted
- Can be diluted in solvents for bath treatment
- Pyrogen controlled
- Tested to meet all the requirements of the Dimethicone NF monograph — and, depending on the fluid's viscosity, the "Dimeticone" and the "Silicone Oil Used as a Lubricant" European Pharmacopoeia (Ph. Eur.) monographs
- Certificate of Suitability held for both Ph. Eur. monographs, and a Drug Master File is maintained with the United States FDA



Liveo™ 365, 35% Dimethicone NF Emulsion

- Aqueous siliconization emulsion that contains 35% Liveo™ 360 Medical Fluid, 350 cSt
- Avoids the use of flammable and/or ozone-depleting organic solvents

Liveo™ 366, 35% Dimethicone NF Emulsion

- Waterborne silicone fluid for lubrication and siliconization of glass, metals, plastics, rubbers
- Not formulated with OPE surfactant
- Not formulated with parabens
- Contains 35% NF Dimethicone

Liveo™ MDX4-4159, 50% Medical Grade Dispersion

- Functional silicone capable of bonding with many substrates
- Especially suited for siliconization of metals (e.g., needles and cutting edges)
- Cures at room temperature on exposure to atmospheric moisture
- Applied by wiping or dip-coating with a diluted solution

Liveo™ Q7-9180 Silicone Fluid*

- Volatile linear silicone fluid
- Diluent for Liveo™ 360 Medical Fluid and Liveo™ MDX4-4159 50% Medical Grade Dispersion
- Non-ozone depleting
- Cleaning agent for medical materials and equipment

Supporting you and your medical materials

DuPont™ Liveo™ can help you meet your functional, regulatory and processing needs with both well-established and next-generation medical materials that offer excellent performance.

For many years, DuPont™ Liveo™ has supported the healthcare industry with a comprehensive range of high-quality silicone coating materials. We are also committed to supplying these products, providing technical expertise and supporting the advancement of these applications and innovations in the years to come.

	Benefits	Product Description	Typical Applications
Liveo™ 360 Medical Fluid*	<ul style="list-style-type: none"> • High water repellency/hydrophobicity • Excellent lubricating characteristics • Manufactured in a dedicated healthcare facility 	Clear, colorless polydimethylsiloxane (PDMS) liquid	<ul style="list-style-type: none"> • Siliconization lubricant • Hydrophobic lubricant for glass, metals, plastics, rubbers • Demolding agent
Liveo™ 365, 35% Dimethicone NF Emulsion	<ul style="list-style-type: none"> • Excellent lubricating and release characteristics • Manufactured in a dedicated healthcare facility 	White, liquid emulsion containing 35% National Formulary Dimethicone	<ul style="list-style-type: none"> • Waterborne silicone fluid for lubrication and siliconization of glass, metals, plastics, rubbers • Hydrophobic lubricant for medical materials and parenteral containers
Liveo™ 366, 35% Dimethicone NF Emulsion¹	<ul style="list-style-type: none"> • Excellent lubricating and release characteristics • Not formulated with OPE surfactant¹ • Not formulated with parabens • Manufactured in a dedicated healthcare facility 	White, liquid emulsion containing 35% National Formulary Dimethicone	<ul style="list-style-type: none"> • Waterborne silicone fluid for lubrication and siliconization of glass, metals, plastics, rubbers • Hydrophobic lubricant for medical materials and parenteral containers
Liveo™ MDX4-4159, 50% Medical Grade Dispersion	<ul style="list-style-type: none"> • High adhesion to metal, providing durability • Cures at room temperature between 55 to 60% relative humidity • Manufactured in a dedicated healthcare facility 	Colorless to slightly hazy liquid aminofunctional silicone dispersion with 50% active silicone ingredients	<ul style="list-style-type: none"> • Lubricant for cutting edges and needles

Liveo™ Q7-9180 Silicone Fluid*	<ul style="list-style-type: none"> • High volatility • High spreadability • Non-ozone depleting 	Clear, colorless, high-purity volatile methylsiloxane fluid	<ul style="list-style-type: none"> • Diluting solvent for Liveo™ 360 Medical Fluid and Liveo™ MDX4-4159, 50% Medical Grade Dispersion • Medical materials cleaning solvent • Equipment cleaning solvent
---------------------------------------	--	---	--

Product Viscosity	Regulatory Status					
	FDA Drug Master File	European Technical File**	Conform to NF Monograph Req. for Dimethicone NF	Conform to Ph. Eur. Monograph Req. for Dimeticone	Conform to Ph. Eur. Monograph Req. for Silicone Oil Used as Lubricant	VOC Exempted in U.S. by EPA
20 cSt	•	•	•	•	•	•
100 cSt	•	•	•	•	•	•
350 cSt	•	•	•	•	•	•
1,000 cSt	•	•	•	•	•	•
12,500 cSt	•	•	•	•	•	•
0.65 cSt	•	•	•	•	•	•
1 cSt	•	•	•	•	•	•

Physical Properties							
Viscosity at 25°C (77°F), mm ² ·s ⁻¹	Specific Gravity at 25°C (77°F)	Drying Rate Similar to	Color, APHA	Acid No., BPB (Bromophenyl Blue)	Refractive Index at 25°C (77°F)	Flash Point, closed cup, °C (°F)	pH
20	0.951		<15	<0.02	1.4018	>100 (>212)	
100	0.967		<15	<0.02	1.4032	>100 (>212)	
350	0.971		<15	<0.02	1.4042	>100 (>212)	
1,000	0.972		<15	<0.02	1.4046	>100 (>212)	
12,500	-		<15	<0.02	1.4047	>100 (>212)	
	0.99	Water					5.0
	0.99	Water					5.0
130		Mineral Spirits			1.4089	13.3 (56)	
0.65	0.76	Acetone				-3 (27)	
1	0.82	Isopropanol				34 (93)	

¹ One emulsifier used in Liveo™ 365, 35% Dimethicone NF Emulsion has recently been added to the REACH Authorisation List (Annex XIV). For more information: <https://echa.europa.eu/authorisation-list>. The list at the link above includes the OPE class listed there as "4-(1,1,3,3-tetramethylbutyl)phenol, ethoxylated" [covering well defined substances and UVCB substances, polymers and homologues]

* Not intended for human injection.
** DuPont has the capability to provide Safety Data Sheets as needed to meet requirements.

Product properties are nominal and not to be used for specification writing.



Focusing on what matters most to you

You want a responsive and flexible global supplier with the material and service support you need to succeed. That's why we provide:

- Consistent quality and safety of materials
- Stability and reliability as a material supplier
- Innovative solutions and collaboration with you
- Supportive regulatory practices
- Unique silicones, with properties that make them suitable for many healthcare applications

Consistent quality

From lot to lot, year after year, you can be sure the products you order from DuPont will live up to their specifications.

Many DuPont materials for healthcare, including those described in this brochure, are manufactured in a dedicated, FDA-registered (CFN 1816403) and inspected facility that uses appropriate current Good Manufacturing Practices (cGMPs) for the intended applications.

Special attention is given to producing products that meet the highest quality standards. This is achieved through:

- An integrated supply chain and full documentation (from raw material testing through production, to final testing and lot sample retention) to ensure complete traceability of our materials
- Meticulous control and documentation of change, as well as a policy of notifying customers of all significant changes
- Rigorous procedures for cleanliness to ensure high product purity



To learn more about DuPont's healthcare solutions visit:
www.dupont.com/healthcare.html

For country-level information, visit:
www.dupont.com/corporate-functions/our-company/global-locations.html

CAUTION: DO NOT USE DUPONT MATERIALS IN MEDICAL APPLICATIONS INVOLVING PERMANENT IMPLANTATION IN THE HUMAN BODY OR PERMANENT CONTACT WITH INTERNAL BODILY FLUIDS OR TISSUES. DO NOT USE DUPONT MATERIALS IN MEDICAL APPLICATIONS INVOLVING BRIEF OR TEMPORARY IMPLANTATION IN THE HUMAN BODY OR PERMANENT CONTACT WITH INTERNAL BODILY FLUIDS OR TISSUES UNLESS THE MATERIAL HAS BEEN PROVIDED DIRECTLY BY DUPONT UNDER A CONTRACT THAT EXPRESSLY ACKNOWLEDGES THE CONTEMPLATED USE.

The information, suggestions and data contained herein are intended only as an informational guide to assist you in making preliminary selections of materials and are not intended to be all-inclusive or final. Because DuPont cannot anticipate or control the many different conditions under which this information, data, suggestions or materials may be used, DuPont does not guarantee the applicability or the accuracy of this information or the suitability of the information, data, suggestions, or materials in any given situation. The information, data, or suggestions are not intended to substitute for any testing you may need to conduct to determine for yourself the suitability of a particular material for a particular purpose. DuPont makes no guarantee of results and assumes no obligation or liability whatsoever in connection with this information. Such information, data or suggestions are to be used and relied upon at user's own discretion and risk. DuPont makes no warranties, express or implied, and disclaims any and all direct and indirect liability for damages or losses resulting from or relating to the use of any information, suggestion, data, or materials described herein. Statements concerning the use of the products or formulations described herein are not to be construed as recommending the infringement of any patent, copyright, designs or other intellectual property and no liability for infringement arising out of such use is assumed by DuPont. None of this information is to be considered as a license to operate under, or recommendation to infringe, any patents.

DuPont reserves the right not to sell Special Control and Premium Control products for selected applications.

Although these products are tested against certain USP Class VI and ISO 10993 standards, DuPont makes no representation or warranty of suitability of its products for particular healthcare or medical applications or any other representations or warranties based on such testing.

The information set forth herein is furnished free of charge and is based on technical data that DuPont believes to be reliable. It is intended for use by persons having technical skill at their own discretion and risk. DuPont makes no warranties, express or implied, and assumes no liability in connection with any use of this information.

DuPont™, the DuPont Oval Logo, and all products, unless otherwise noted, denoted with ™, SM or ® are trademarks, service marks or registered trademarks of affiliates of DuPont de Nemours, Inc.

© 2020 DuPont de Nemours, Inc. All rights reserved.

Form Number: 001-20408-CDP0820