



SAFETY DATA SHEET

DDP Specialty Electronic Materials US,
LLC

Product name: BETAPRIME™ Clear Advanced Glass Primer

Issue Date: 10/24/2023

Print Date: 10/07/2024

DDP Specialty Electronic Materials US, LLC encourages and expects you to read and understand the entire (M)SDS, as there is important information throughout the document. We expect you to follow the precautions identified in this document unless your use conditions would necessitate other appropriate methods or actions.

1. IDENTIFICATION

Product name: BETAPRIME™ Clear Advanced Glass Primer

Recommended use of the chemical and restrictions on use

Identified uses: A primer - For use in automotive applications.

COMPANY IDENTIFICATION

DDP Specialty Electronic Materials US,
LLC
974 Centre Road, Building 730,
Wilmington DE 19805
UNITED STATES

Customer Information Number:

833-338-7668

SDSQuestion-NA@dupont.com

EMERGENCY TELEPHONE NUMBER

24-Hour Emergency Contact: 1-800-424-9300

Local Emergency Contact: 1-800-424-9300

2. HAZARDS IDENTIFICATION

Hazard classification

This product is hazardous under the criteria of the Hazardous Products Regulation (HPR) as implemented under the Workplace Hazardous Materials Information System (WHMIS 2015).

Flammable liquids - Category 2

Skin irritation - Category 2

Skin sensitisation - Sub-category 1B

Specific target organ toxicity - single exposure - Category 3

Aspiration hazard - Category 1

Label elements

Hazard pictograms



Signal word: **DANGER!**

Hazards

Highly flammable liquid and vapour.
May be fatal if swallowed and enters airways.
Causes skin irritation.
May cause an allergic skin reaction.
May cause drowsiness or dizziness.

Precautionary statements

Prevention

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
Keep container tightly closed.
Ground and bond container and receiving equipment.
Use explosion-proof electrical/ ventilating/ lighting equipment.
Use non-sparking tools.
Take action to prevent static discharges.
Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray.
Wash skin thoroughly after handling.
Use only outdoors or in a well-ventilated area.
Contaminated work clothing should not be allowed out of the workplace.
Wear protective gloves/ protective clothing/ eye protection/ face protection.

Response

IF SWALLOWED: Immediately call a POISON CENTER/ doctor.
IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water.
IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/ doctor if you feel unwell.
Do NOT induce vomiting.
If skin irritation or rash occurs: Get medical advice/ attention.
In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

Storage

Store in a well-ventilated place. Keep container tightly closed.
Store in a well-ventilated place. Keep cool.
Store locked up.

Disposal

Dispose of contents/ container to an approved waste disposal plant.

Other hazards

No data available

3. COMPOSITION/INFORMATION ON INGREDIENTS

This product is a mixture.

Component	CASRN	Concentration (w/w)
Heptane	142-82-5	> 85.0 - < 95.0 %
3-Mercaptopropyltrimethoxysilane	4420-74-0	< 10.0 %
Titanium, Tetrakis(2-ethyl-1,3-hexanediolato)-	5575-43-9	< 10.0 %
N-(3-(Trimethoxysilyl) propyl)-1,2-ethanediamine	1760-24-3	< 5.0 %

4. FIRST AID MEASURES

Description of first aid measures

General advice:

First Aid responders should pay attention to self-protection and use the recommended protective clothing (chemical resistant gloves, splash protection). If potential for exposure exists refer to Section 8 for specific personal protective equipment.

Inhalation: Move person to fresh air. If not breathing, give artificial respiration; if by mouth to mouth use rescuer protection (pocket mask, etc). If breathing is difficult, oxygen should be administered by qualified personnel. Call a physician or transport to a medical facility.

Skin contact: Remove material from skin immediately by washing with soap and plenty of water. Remove contaminated clothing and shoes while washing. Seek medical attention if irritation persists. Wash clothing before reuse. Discard items which cannot be decontaminated, including leather articles such as shoes, belts and watchbands. Suitable emergency safety shower facility should be immediately available.

Eye contact: Flush eyes thoroughly with water for several minutes. Remove contact lenses after the initial 1-2 minutes and continue flushing for several additional minutes. If effects occur, consult a physician, preferably an ophthalmologist. Suitable emergency eye wash facility should be available in work area.

Ingestion: Do not induce vomiting. Call a physician and/or transport to emergency facility immediately.

Most important symptoms and effects, both acute and delayed:

Aside from the information found under Description of first aid measures (above) and Indication of immediate medical attention and special treatment needed (below), any additional important symptoms and effects are described in Section 11: Toxicology Information.

Indication of any immediate medical attention and special treatment needed

Notes to physician: Maintain adequate ventilation and oxygenation of the patient. If lavage is performed, suggest endotracheal and/or esophageal control. Danger from lung aspiration must be weighed against toxicity when considering emptying the stomach. The decision of whether to induce vomiting or not should be made by a physician. Exposure may increase "myocardial irritability". Do not administer sympathomimetic drugs such as epinephrine unless absolutely necessary. No specific antidote. Treatment of exposure should be directed at the control of symptoms and the clinical condition of the patient. Skin contact may aggravate preexisting dermatitis.

5. FIREFIGHTING MEASURES

Suitable extinguishing media: Water fog or fine spray. Dry chemical fire extinguishers. Carbon dioxide fire extinguishers. Foam. Alcohol resistant foams (ATC type) are preferred. General purpose synthetic foams (including AFFF) or protein foams may function, but will be less effective.

Unsuitable extinguishing media: Do not use direct water stream. Straight or direct water streams may not be effective to extinguish fire.

Special hazards arising from the substance or mixture

Hazardous combustion products: During a fire, smoke may contain the original material in addition to combustion products of varying composition which may be toxic and/or irritating. Combustion products may include and are not limited to: Carbon monoxide. Carbon dioxide.

Unusual Fire and Explosion Hazards: Container may vent and/or rupture due to fire. Electrically ground and bond all equipment. Flammable mixtures of this product are readily ignited even by static discharge. Vapors are heavier than air and may travel a long distance and accumulate in low lying areas. Ignition and/or flash back may occur. Flammable mixtures may exist within the vapor space of containers at room temperature. Flammable concentrations of vapor can accumulate at temperatures above flash point; see Section 9.

Advice for firefighters

Fire Fighting Procedures: Keep people away. Isolate fire and deny unnecessary entry. Stay upwind. Keep out of low areas where gases (fumes) can accumulate. Water may not be effective in extinguishing fire. Use water spray to cool fire exposed containers and fire affected zone until fire is out and danger of reignition has passed. Burning liquids may be extinguished by dilution with water. Do not use direct water stream. May spread fire. Eliminate ignition sources. Move container from fire area if this is possible without hazard. Burning liquids may be moved by flushing with water to protect personnel and minimize property damage. Avoid accumulation of water. Product may be carried across water surface spreading fire or contacting an ignition source.

Special protective equipment for firefighters: Wear positive-pressure self-contained breathing apparatus (SCBA) and protective fire fighting clothing (includes fire fighting helmet, coat, trousers, boots, and gloves). If protective equipment is not available or not used, fight fire from a protected location or safe distance.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures: Isolate area. Keep unnecessary and unprotected personnel from entering the area. Keep personnel out of low areas. Keep upwind of spill. Ventilate area of leak or spill. No smoking in area. Eliminate all sources of ignition in vicinity of spill or released vapor to avoid fire or explosion. Vapor explosion hazard. Keep out of sewers. For large spills, warn public of downwind explosion hazard. Check area with

combustible gas detector before reentering area. Ground and bond all containers and handling equipment. Refer to section 7, Handling, for additional precautionary measures. Use appropriate safety equipment. For additional information, refer to Section 8, Exposure Controls and Personal Protection.

Environmental precautions: Spills or discharge to natural waterways is likely to kill aquatic organisms. Prevent from entering into soil, ditches, sewers, waterways and/or groundwater. See Section 12, Ecological Information.

Methods and materials for containment and cleaning up: Contain spilled material if possible. Absorb with materials such as: Cat litter. Sand. Sawdust. Ground and bond all containers and handling equipment. Pump with explosion-proof equipment. If available, use foam to smother or suppress. Collect in suitable and properly labeled containers. See Section 13, Disposal Considerations, for additional information.

7. HANDLING AND STORAGE

Precautions for safe handling: Keep away from heat, sparks and flame. Do not get in eyes. Avoid contact with skin and clothing. Avoid prolonged or repeated contact with skin. Avoid breathing vapor. Do not swallow. Wash thoroughly after handling. Keep container closed. Use only with adequate ventilation. No smoking, open flames or sources of ignition in handling and storage area. Ignition sources can include and are not limited to pilot lights, flames, smoking, sparks, heaters, electrical equipment, and static discharges. Electrically bond and ground all containers, personnel and equipment before transfer or use of material. Use of non-sparking or explosion-proof equipment may be necessary, depending upon the type of operation. Containers, even those that have been emptied, can contain vapors. Do not cut, drill, grind, weld, or perform similar operations on or near empty containers. Vapors are heavier than air and may travel a long distance and accumulate in low lying areas. Ignition and/or flash back may occur. Never use air pressure for transferring product unless a risk assessment has been conducted that includes consideration of the flammability of the product. See Section 8, EXPOSURE CONTROLS AND PERSONAL PROTECTION.

Conditions for safe storage: Minimize sources of ignition, such as static build-up, heat, spark or flame. Keep container closed. Flammable mixtures may exist within the vapor space of containers at room temperature.

Storage stability

Storage temperature:

> 5 - < 35 °C

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

If exposure limits exist, they are listed below. If no exposure limits are displayed, then no values are applicable.

Consult local authorities for recommended exposure limits.

Component	Regulation	Type of listing	Value
Heptane	ACGIH	TWA	400 ppm
	Further information: CNS impair: Central Nervous System impairment; URT irr: Upper Respiratory Tract irritation		
	ACGIH	STEL	500 ppm

	Further information: CNS impair: Central Nervous System impairment; URT irr: Upper Respiratory Tract irritation		
	Dow IHG	TWA	100 ppm
	CA BC OEL	TWA	400 ppm
	CA BC OEL	STEL	500 ppm
	CA AB OEL	TWA	1,640 mg/m3 400 ppm
	CA AB OEL	STEL	2,050 mg/m3 500 ppm
3-Mercaptopropyltrimethoxysilane	Dow IHG	TWA	0.1 ppm
	Further information: SKIN: Absorbed via skin		

Exposure controls

Engineering measures: Use engineering controls to maintain airborne level below exposure limit requirements or guidelines. If there are no applicable exposure limit requirements or guidelines, use only in enclosed systems or with local exhaust ventilation. Exhaust systems should be designed to move the air away from the source of vapor/aerosol generation and people working at this point. Lethal concentrations may exist in areas with poor ventilation.

Individual protection measures

Eye/face protection: Use safety glasses (with side shields).

Skin protection

Hand protection: Use gloves chemically resistant to this material. Examples of preferred glove barrier materials include: Viton. Polyethylene. Neoprene. Chlorinated polyethylene. Nitrile/butadiene rubber ("nitrile" or "NBR"). Polyvinyl alcohol ("PVA"). Ethyl vinyl alcohol laminate ("EVAL"). Examples of acceptable glove barrier materials include: Butyl rubber. Polyvinyl chloride ("PVC" or "vinyl"). Avoid gloves made of: Natural rubber ("latex"). **NOTICE:** The selection of a specific glove for a particular application and duration of use in a workplace should also take into account all relevant workplace factors such as, but not limited to: Other chemicals which may be handled, physical requirements (cut/puncture protection, dexterity, thermal protection), potential body reactions to glove materials, as well as the instructions/specifications provided by the glove supplier.

Other protection: Use protective clothing chemically resistant to this material. Selection of specific items such as face shield, boots, apron, or full body suit will depend on the task.

Respiratory protection: Respiratory protection should be worn when there is a potential to exceed the exposure limit requirements or guidelines. If there are no applicable exposure limit requirements or guidelines, use an approved respirator. Selection of air-purifying or positive-pressure supplied-air will depend on the specific operation and the potential airborne concentration of the material. For emergency conditions, use an approved positive-pressure self-contained breathing apparatus. In confined or poorly ventilated areas, use an approved self-contained breathing apparatus or positive pressure air line with auxiliary self-contained air supply.

The following should be effective types of air-purifying respirators: Organic vapor cartridge.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance

Physical state

liquid

Color

Colorless to yellow

Odor

Solvent

Odor Threshold

No test data available

pH

Substance/mixture is non-soluble (in water).

Melting point/range	No test data available
Freezing point	No test data available
Boiling point (760 mmHg)	No test data available
Flash point	-10.56 °C <i>ASTM D-3278</i>
Evaporation Rate (Butyl Acetate = 1)	No test data available
Flammability (solid, gas)	Flammable liquid
Lower explosion limit	No test data available
Upper explosion limit	No test data available
Vapor Pressure	No test data available
Relative Vapor Density (air = 1)	No test data available
Relative Density (water = 1)	0.713 <i>ASTM D1475</i>
Water solubility	Not applicable
Partition coefficient: n-octanol/water	No data available
Auto-ignition temperature	No data available
Decomposition temperature	No test data available
Kinematic Viscosity	No test data available
Explosive properties	No test data available
Oxidizing properties	No test data available
Molecular weight	No test data available
Volatile Organic Compounds	5.62 lb/gal <i>EPA Method No. 24</i> (typical value)

NOTE: The physical data presented above are typical values and should not be construed as a specification.

10. STABILITY AND REACTIVITY

Reactivity: No dangerous reaction known under conditions of normal use.

Chemical stability: Stable under recommended storage conditions. See Storage, Section 7.

Possibility of hazardous reactions: Polymerization will not occur.

Conditions to avoid: Exposure to elevated temperatures can cause product to decompose. Avoid static discharge.

Incompatible materials: Avoid contact with: Acids. Bases. Oxidizers.

Hazardous decomposition products: Decomposition products depend upon temperature, air supply and the presence of other materials.

11. TOXICOLOGICAL INFORMATION

Toxicological information appears in this section when such data is available.

Acute toxicity

Acute oral toxicity

Product test data not available. Refer to component data.

Acute dermal toxicity

Prolonged or widespread skin contact may result in absorption of harmful amounts. The dermal LD50 has not been determined.

Acute inhalation toxicity

In confined or poorly ventilated areas, vapor can readily accumulate and can cause unconsciousness and death. Symptoms of excessive exposure may be anesthetic or narcotic effects; dizziness and drowsiness may be observed. May cause respiratory irritation and central nervous system depression. Symptoms may include headache, dizziness and drowsiness, progressing to incoordination and unconsciousness. Excessive exposure may increase sensitivity to epinephrine and increase myocardial irritability (irregular heartbeats). May cause nausea and vomiting. The LC50 has not been determined.

Skin corrosion/irritation

Brief contact may cause skin irritation with local redness.
May cause burning sensation.
May cause itching.
May cause drying and flaking of the skin.
May stain skin.

Serious eye damage/eye irritation

May cause eye irritation.

Sensitization

For skin sensitization:
A component in this mixture has been shown to be a skin sensitizer.

For respiratory sensitization:
No relevant data found.

Specific Target Organ Systemic Toxicity (Single Exposure)

Contains component(s) which are classified as specific target organ toxicant, single exposure, category 3.

Specific Target Organ Systemic Toxicity (Repeated Exposure)

Contains component(s) which have been reported to cause effects on the following organs in animals:
Kidney.
Liver
adrenal gland
Urinary tract.
Heptane is part of a mixture which caused polyneuropathy. However, there is no clear evidence that heptane causes peripheral nervous system effects.

Carcinogenicity

No relevant data found.

Teratogenicity

Contains component(s) which did not cause birth defects or any other fetal effects in lab animals.

Reproductive toxicity

Contains component(s) which did not interfere with reproduction in animal studies.

Mutagenicity

Contains component(s) which were negative in some in vitro genetic toxicity studies and positive in others. Contains component(s) which were negative in some animal genetic toxicity studies and positive in others.

Aspiration Hazard

Aspiration into the lungs may occur during ingestion or vomiting, causing lung damage or even death due to chemical pneumonia.

COMPONENTS INFLUENCING TOXICOLOGY:

Heptane

Acute oral toxicity

Information given is based on data obtained from similar substances. LD50, Rat, > 5,000 mg/kg OECD Test Guideline 401

Acute dermal toxicity

Information given is based on data obtained from similar substances. LD50, Rabbit, > 2,000 mg/kg OECD Test Guideline 402

Acute inhalation toxicity

LC50, Rat, 4 Hour, vapour, > 29.29 mg/l OECD Test Guideline 403

3-Mercaptopropyltrimethoxysilane

Acute oral toxicity

Swallowing may result in irritation of the mouth, throat, and gastrointestinal tract. Contains a component(s) which hydrolyzes to methanol. Methanol is highly toxic to humans and may cause central nervous system effects, visual disturbances up to blindness, metabolic acidosis, and degenerative damage to other organs including liver, kidney, and heart.

LD50, Rat, male, 914 mg/kg

LD50, Rat, female, 758 mg/kg

Acute dermal toxicity

LD50, Rat, 2,348 mg/kg

Acute inhalation toxicity

Contains a component(s) which hydrolyzes to methanol. Inhalation of methanol may cause effects ranging from headache, narcosis and visual impairment to metabolic acidosis, blindness, and even death.

The LC50 has not been determined.

Titanium, Tetrakis(2-ethyl-1,3-hexanediolato)-

Acute oral toxicity

LD50, Rat, > 3,000 mg/kg No deaths occurred at this concentration.

Acute dermal toxicity

The dermal LD50 has not been determined.

Acute inhalation toxicity

The LC50 has not been determined.

N-(3-(Trimethoxysilyl) propyl)-1,2-ethanediamine**Acute oral toxicity**

LD50, Rat, male and female, 2,295 mg/kg OPPTS 870.1100

Acute dermal toxicity

LD50, Rabbit, > 2,000 mg/kg No deaths occurred at this concentration.

Acute inhalation toxicity

LC50, Rat, 4 Hour, dust/mist, 1.49 - 2.44 mg/l OECD Test Guideline 403

12. ECOLOGICAL INFORMATION

Ecotoxicological information appears in this section when such data is available.

Toxicity**Heptane****Acute toxicity to fish**

LC50, Oncorhynchus mykiss (rainbow trout), 96 Hour, 5.738 mg/l

Acute toxicity to aquatic invertebrates

LC50, Americamysis bahia (Opossum shrimp), 96 Hour, 0.1 mg/l

Acute toxicity to algae/aquatic plants

EC50, Pseudokirchneriella subcapitata (green algae), 72 Hour, 4.338 mg/l

NOEC, Pseudokirchneriella subcapitata (green algae), 72 Hour, 0.97 mg/l

Chronic toxicity to fish

NOEC, Oncorhynchus mykiss (rainbow trout), 28 d, 1.284 mg/l

Chronic toxicity to aquatic invertebrates

NOEC, Daphnia magna (Water flea), 21 d, 0.17 mg/l

3-Mercaptopropyltrimethoxysilane**Acute toxicity to fish**

Material is moderately toxic to aquatic organisms on an acute basis (LC50/EC50 between 1 and 10 mg/L in the most sensitive species tested).

LC50, Pimephales promelas (fathead minnow), 96 Hour, 253 mg/l

Acute toxicity to aquatic invertebrates

EC50, Daphnia magna (Water flea), 48 Hour, 4.0 mg/l

Acute toxicity to algae/aquatic plants

ErC50, Scenedesmus subspicatus, 72 Hour, 931 mg/l

Toxicity to bacteria

IC50, Bacteria, 16 Hour, 850 mg/l

Titanium, Tetrakis(2-ethyl-1,3-hexanediolato)-

Acute toxicity to fish

No relevant data found.

N-(3-(Trimethoxysilyl) propyl)-1,2-ethanediamine

Acute toxicity to fish

Material is toxic to aquatic organisms (LC50/EC50/IC50 between 1 and 10 mg/L in the most sensitive species).

For the hydrolysis product(s)

LC50, zebra fish (*Brachydanio rerio*), 96 Hour, 597 mg/l

Acute toxicity to aquatic invertebrates

For the hydrolysis product(s)

EC50, *Daphnia magna* (Water flea), 48 Hour, 81 mg/l

Acute toxicity to algae/aquatic plants

For the hydrolysis product(s)

ErC50, *Pseudokirchneriella subcapitata* (green algae), 72 Hour, Growth rate inhibition, 8.8 mg/l

For the hydrolysis product(s)

NOEC, *Pseudokirchneriella subcapitata* (green algae), 72 Hour, Growth rate inhibition, 3.1 mg/l

Toxicity to bacteria

For the hydrolysis product(s)

EC50, *Pseudomonas putida*, 16 Hour, Growth inhibition, 67 mg/l

Chronic toxicity to aquatic invertebrates

For the hydrolysis product(s)

NOEC, *Daphnia magna* (Water flea), semi-static test, 21 d, number of offspring, > 1 mg/l

Toxicity to Above Ground Organisms

Material is moderately toxic to birds on an acute basis (LD50 between 51 and 500 mg/kg).

Toxicity to soil-dwelling organisms

NOEC, *Eisenia fetida* (earthworms), 14 d, >= 1,000 mg/kg

Persistence and degradability

Heptane

Biodegradability: Readily biodegradable.

Biodegradation: 70 %

Exposure time: 10 d

Theoretical Oxygen Demand: 3.52 mg/g

3-Mercaptopropyltrimethoxysilane

Biodegradability: Biodegradation under aerobic static laboratory conditions is high (BOD20 or BOD28/ThOD > 40%).

Theoretical Oxygen Demand: 1.71 mg/mg Estimated.

Chemical Oxygen Demand: 1.73 mg/mg Estimated.

Photodegradation

Test Type: Half-life (indirect photolysis)

Sensitization: OH radicals

Atmospheric half-life: 0.229 d

Method: Estimated.

Titanium, Tetrakis(2-ethyl-1,3-hexanediolato)-

Biodegradability: No relevant data found.

Photodegradation

Test Type: Half-life (indirect photolysis)

Sensitization: OH radicals

Atmospheric half-life: 0.48 d

Method: Estimated.

N-(3-(Trimethoxysilyl) propyl)-1,2-ethanediamine

Biodegradability: Based on stringent OECD test guidelines, this material cannot be considered as readily biodegradable; however, these results do not necessarily mean that the material is not biodegradable under environmental conditions.

10-day Window: Fail

Biodegradation: 39 %

Exposure time: 28 d

Method: OECD Test Guideline 301A or Equivalent

Theoretical Oxygen Demand: 2.39 mg/mg Estimated.

Chemical Oxygen Demand: 1.76 mg/mg Estimated.

Biological oxygen demand (BOD)

Incubation Time	BOD
5 d	23 %
10 d	30 %
20 d	29 %

Stability in Water (1/2-life)

Hydrolysis, half-life, 0.025 Hour, pH 7

Photodegradation

Test Type: Half-life (indirect photolysis)

Sensitization: OH radicals

Atmospheric half-life: 0.088 d

Method: Estimated.

Bioaccumulative potential

Heptane

Partition coefficient: n-octanol/water(log Pow): 4.5 at 20 °C

3-Mercaptopropyltrimethoxysilane

Bioaccumulation: Bioconcentration potential is low (BCF < 100 or Log Pow < 3).

Bioconcentration potential is low (BCF < 100 or Log Pow < 3).

Partition coefficient: n-octanol/water(log Pow): 0.25 Estimated. **Partition coefficient: n-octanol/water(log Pow):** 0.25 Estimated.

Titanium, Tetrakis(2-ethyl-1,3-hexanediolato)-

Bioaccumulation: Bioconcentration potential is low (BCF < 100 or Log Pow < 3).

Partition coefficient: n-octanol/water(log Pow): 1.60 Estimated.

N-(3-(Trimethoxysilyl) propyl)-1,2-ethanediamine

Bioaccumulation: Bioconcentration potential is low (BCF < 100 or Log Pow < 3).

Partition coefficient: n-octanol/water(log Pow): < 3 estimated

Mobility in soil

Heptane

Expected to be relatively immobile in soil (Koc > 5000).

Partition coefficient (Koc): 2040 - 16000 Estimated.

3-Mercaptopropyltrimethoxysilane

Potential for mobility in soil is slight (Koc between 2000 and 5000).

Partition coefficient (Koc): 2577 Estimated.

Potential for mobility in soil is slight (Koc between 2000 and 5000).

Partition coefficient (Koc): 2577 Estimated.

Titanium, Tetrakis(2-ethyl-1,3-hexanediolato)-

Potential for mobility in soil is very high (Koc between 0 and 50).

Partition coefficient (Koc): 10 Estimated.

N-(3-(Trimethoxysilyl) propyl)-1,2-ethanediamine

Expected to be relatively immobile in soil (Koc > 5000).

Given its very low Henry's constant, volatilization from natural bodies of water or moist soil is not expected to be an important fate process.

Partition coefficient (Koc): > 5000 Estimated.

13. DISPOSAL CONSIDERATIONS

Disposal methods: DO NOT DUMP INTO ANY SEWERS, ON THE GROUND, OR INTO ANY BODY OF WATER. All disposal practices must be in compliance with all Federal, State/Provincial and local laws and regulations. Regulations may vary in different locations. Waste characterizations and compliance with applicable laws are the responsibility solely of the waste generator. AS YOUR SUPPLIER, WE HAVE NO CONTROL OVER THE MANAGEMENT PRACTICES OR MANUFACTURING PROCESSES OF PARTIES HANDLING OR USING THIS MATERIAL. THE INFORMATION PRESENTED HERE PERTAINS ONLY TO THE PRODUCT AS SHIPPED IN ITS INTENDED CONDITION AS DESCRIBED IN MSDS SECTION: Composition Information. FOR UNUSED & UNCONTAMINATED PRODUCT, the preferred options include sending to a licensed, permitted: Incinerator or other thermal destruction device.

Treatment and disposal methods of used packaging: Empty containers should be recycled or otherwise disposed of by an approved waste management facility. Waste characterizations and compliance with applicable laws are the responsibility solely of the waste generator. Do not re-use containers for any purpose.

14. TRANSPORT INFORMATION

TDG

Proper shipping name	HEPTANES SOLUTION
UN number	UN 1206
Class	3
Packing group	II
Marine pollutant	Heptane

Classification for SEA transport (IMO-IMDG):

Proper shipping name	HEPTANES SOLUTION
UN number	UN 1206
Class	3
Packing group	II
Marine pollutant	Heptane
Transport in bulk according to Annex I or II of MARPOL 73/78 and the IBC or IGC Code	Consult IMO regulations before transporting ocean bulk

Classification for AIR transport (IATA/ICAO):

Proper shipping name	Heptanes solution
UN number	UN 1206
Class	3
Packing group	II

This information is not intended to convey all specific regulatory or operational requirements/information relating to this product. Transportation classifications may vary by container volume and may be influenced by regional or country variations in regulations. Additional transportation system information can be obtained through an authorized sales or customer service representative. It is the responsibility of the transporting organization to follow all applicable laws, regulations and rules relating to the transportation of the material.

15. REGULATORY INFORMATION

Canadian Domestic Substances List (DSL)

This product contains at least one substance which is not listed on the Canadian Domestic Substances List (DSL).

16. OTHER INFORMATION

Revision

Identification Number: 12018118 / A749 / Issue Date: 10/24/2023 / Version: 1.1

Most recent revision(s) are noted by the bold, double bars in left-hand margin throughout this document.

Legend

ACGIH	USA. ACGIH Threshold Limit Values (TLV)
CA AB OEL	Canada. Alberta, Occupational Health and Safety Code (table 2: OEL)
CA BC OEL	Canada. British Columbia OEL
Dow IHG	Dow Industrial Hygiene Guideline
STEL	Short-term exposure limit
TWA	8-hour Occupational exposure limit

Full text of other abbreviations

AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Information Source and References

This SDS is prepared by Product Regulatory Services and Hazard Communications Groups from information supplied by internal references within our company.

DDP Specialty Electronic Materials US, LLC urges each customer or recipient of this (M)SDS to study it carefully and consult appropriate expertise, as necessary or appropriate, to become aware of and understand the data contained in this (M)SDS and any hazards associated with the product. The information herein is provided in good faith and believed to be accurate as of the effective date shown above. However, no warranty, express or implied, is given. Regulatory requirements are subject to change and may differ between various locations. It is the buyer's/user's responsibility to ensure that his activities comply with all federal, state, provincial or local laws. The information presented here pertains only to the product as shipped. Since conditions for use of the product are not under the control of the manufacturer, it is the buyer's/user's duty to determine the conditions necessary for the safe use of this product. Due to the proliferation of sources for information such as manufacturer-specific (M)SDSs, we are not and cannot be responsible for (M)SDSs obtained from any source other than ourselves. If you have obtained an (M)SDS from another source or if you are not sure that the (M)SDS you have is current, please contact us for the most current version.

CA