

# DuPont™ Tyvek® DrainWrap™

Grooved Air and Water Barrier Engineered to Enhance Drainage



## FEATURES/BENEFITS

### Description

DuPont™ Tyvek® DrainWrap™ offers excellent drainage and durability for homes. Vertical grooves on the surface of Tyvek® DrainWrap™ make it a superior moisture barrier, engineered to channel bulk water away from wall systems and drain safely to the outside.

Combined with the superior air and water resistance, vapor permeability and strength of the Tyvek® brand, Tyvek® DrainWrap™ provides enhanced drainage behind claddings such as primed wood (all six sides), fiber cement siding, and foam board applied over flat substrates.

### Air and Water Barrier Performance

- Tyvek® DrainWrap™ helps hold out bulk water, while allowing water vapor to pass through it, promoting drying in the wall system, which can help prevent mold and water damage.
- The unique non-woven fiber structure of Tyvek® DrainWrap™ also helps prevent air movement through the walls, contributing to a more energy efficient home.
- Tyvek® DrainWrap™ is Air Barrier Association of America evaluated to exceed ABAA, ASHRAE 90.1 and IECC air leakage requirements when tested in accordance with ASTM E2357.

- Offers > 98% drainage efficiency when tested in accordance with ASTM E2273.
- Withstands up to four months (120 days) of UV exposure.

### Ease of Installation

Tyvek® DrainWrap™ is easy to install. It is pliable, so it wraps around corners with ease. It is also light weight, easier to handle, and faster to install than the average house wrap. In addition, because it's flexible, Tyvek® DrainWrap™ easily interfaces at joints, and over architectural elements.

### Available Sizes

Tyvek® DrainWrap™ is available in 9- and 10-foot width rolls for use behind a variety of claddings. This width minimizes seams and offers the potential for reduction in labor costs, compared to narrower rolls.

### High Performance Durability

Compared to other textured moisture barriers, Tyvek® DrainWrap™ provides superior performance in tests where bulk water was applied between a flat acrylic panel and the moisture barrier. When compared to Grade D building paper and #15 felt, Tyvek® DrainWrap™ provides superior sustained performance.

## Sustainable Solutions

DuPont™ Tyvek® DrainWrap™ may contribute toward LEED® points in the areas of Energy and Atmosphere (EA): Optimizing the Building Envelope and Indoor Environmental Air Quality (EQ): Construction IAQ Management Plan and Low Emitting Materials. In addition, the use of a continuous air barrier is a prerequisite for LEED® applications requiring compliance with ASHRAE 90.1-2010.

By helping to effectively seal the building envelope, Tyvek® DrainWrap™ helps to reduce the amount of energy required for heating and cooling.

## Complete System

Tyvek® DrainWrap™ can be integrated with DuPont self-adhered flashing products and Tyvek® Fluid Applied products to offer seamless protection for wall systems that require mechanically fastened and fluid applied air and water barriers.

## PROPERTIES

Review all instructions and (Material) Safety Data Sheet ((M)SDS) before use. Please contact your local DuPont™ Tyvek® Specialist before writing specifications around this product. Product properties are as follows:

Test Method	Property	Typical Value	Units
ASTM E2178 Gurley Hill (TAPPI T-460) ASTM E1677	Air Penetration Resistance	.004 >300 Type 1	cfm/ft <sup>2</sup> @1.57 psf sec/100cc -
ICC-ES AC 24 Section 6.11 ASTM E2273 ICC-ES AC 235 Section 4.5	Drainage	Pass >98 Pass	- % -
ASTM E96-00	Water Vapor Transmission	Method A 250 36	g/m <sup>2</sup> -24 hrs perms
ASTM E96-00	Water Vapor Transmission	Method B 350 50	g/m <sup>2</sup> -24 hrs perms
ATTCC 127	Water Penetration Resistance	210	cm
TAPPI T-410	Basis Weight	21	oz/yd <sup>2</sup>
ASTM D882	Breaking Strength	30/30	lbs/in
ASTM D1117	Tear Resistance (Trapezoid)	7/9	lbs
ASTM E84 Flame Spread Index Smoke Developed Index	Surface Burning Characteristics	5 25	Class A Class A
	Ultra Violet Light Exposure (UV)	120 (4)	days (months)

Test results shown represent roll averages. Individual results may vary either above or below averages due to normal manufacturing variations, while continuing to meet product specifications.



For more information visit us at  
[tyvek.com](http://tyvek.com)  
or call 1-800-448-9835

**NOTICE:** No freedom from any patent owned by DuPont or others is to be inferred. Because use conditions and applicable laws may differ from one location to another and may change with time, Customer is responsible for determining whether products and the information in this document are appropriate for Customer's use and for ensuring that Customer's workplace and disposal practices are in compliance with applicable laws and other government enactments. The product shown in this literature may not be available for sale and/or available in all geographies where DuPont is represented. The claims made may not have been approved for use in all countries or regions. DuPont assumes no obligation or liability for the information in this document. References to "DuPont" or the "Company" mean the DuPont legal entity selling the products to Customer unless otherwise expressly noted. NO EXPRESS WARRANTIES ARE GIVEN EXCEPT FOR ANY APPLICABLE WRITTEN WARRANTIES SPECIFICALLY PROVIDED BY DUPONT. ALL IMPLIED WARRANTIES INCLUDING THOSE OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE EXPRESSLY EXCLUDED. The buyer assumes all risks as to the use of the material. Buyer's exclusive remedy or any claim (including without limitations, negligence, strict liability, or tort) shall be limited to the refund of the purchase price of the material. Failure to strictly adhere to any recommended procedures shall release DuPont Specialty Products USA, LLC or its affiliates, of all liability with respect to the materials or the use thereof. The information herein is not intended for use by non-professional designers, applicators or other persons who do not purchase or utilize this product in the normal course of their business.