

DuPont™ ArmorWall™ System Benefits

Key Benefits of DuPont™ ArmorWall™ Plus Fire-Rated (FR) Structural Insulated Sheathing (SIS)

1. Continuous Insulation

DuPont™ ArmorWall™ Plus FR SIS has a high-performance, poured polyurethane insulation layer fused to the sheathing layer using patented Fusion Technology, which provides an easy way to comply with continuous insulation (ci) requirements in building codes. The thermal layer is offered in three standard thicknesses and R-Values for both ArmorWall™ Plus FR SIS and ArmorWall™ SP Plus FR SIS. Fusing the insulation to the sheathing provides superior performance and a simple solution to comply with continuous insulation requirements in building codes.

2. Fire-Resistance

Significant fire resistance of the ArmorWall™ Plus FR SIS allows many diverse assemblies with combustible and non-combustible claddings to successfully pass the NFPA 285 test criteria as required by Chapter 25 of the IBC. See our ICC-ES ESR 1442 and associated engineering judgment letters for additional information. This allows for engineering judgements to be made for most NFPA 285 tested and approved exterior finishes when used with DuPont™ ArmorWall™ System as part of a complete wall assembly. In addition, ArmorWall™ Plus FR SIS has been rigorously tested at approved third party fire labs to demonstrate ASTM E119 fire-rated assembly compliance.

3. Water-Resistive Barrier

ArmorWall™ Plus FR SIS passes ASTM E331 as a water-resistive barrier for pressure totaling two hours and complies fully with Chapter 14 of the International Building Code (IBC) for water-resistive barriers once the sheathing fasteners and seams have been properly sealed. Once these steps are completed, the structure is considered weathered and dried-in and interior construction may commence.

4. Air-Resistive Barrier

Once the sheathing fasteners and seams have been properly sealed, ArmorWall™ Plus FR SIS meets the IBC and ASTM E283 requirements for an air barrier assembly without the need for additional materials.

5. Structural Sheathing and Cladding Attachment Support

Magnesium Oxide (MgO) sheathing is fused onto the exterior face of ArmorWall™ Plus FR SIS panels to gain high strength and durability not commonly found today in traditional building enclosure products. With its ability to move the stud face to the exterior face of the sheathing, ArmorWall™ Plus FR SIS has been tested to support loads equivalent to most building cladding finishes, with minimal creep while under load.

1. Continuous Insulation



2. Fire-Resistance



3. Water-Resistive Barrier



4. Air-Resistive Barrier



5. Cladding Attachment Support



For more information visit us
at armorwall.dupont.com
or call 1-866-583-2583

NOTICE: DuPont believes this information to be reliable. It is subject to change as additional knowledge and experience are gained. It is not intended as a substitute for any testing you may conduct to determine for yourself the suitability of our products for your particular purpose. Customer is also responsible for ensuring its use of product, including workplace and disposal practices are in compliance with applicable laws and regulations. Since conditions for use are outside the control of DuPont, DuPont de Nemours, Inc. OR its affiliates MAKE NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING BUT NOT LIMITED TO WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE AND ASSUMES NO LIABILITY IN CONNECTION WITH ANY USE OF THIS INFORMATION. This information is not intended as a license to operate under or a recommendation to infringe any trademark, patent or technical information of DuPont or other persons covering any material or its use.