

Leaders of the PAK

Recommended Steps for Disposal of DuPont™ Froth-Pak™ Foam Insulation (U.S. Only) and DuPont™ Froth-Pak™ Foam Sealant Kits



IMPORTANT: Empty and vented cylinders can be disposed of as scrap, recycle steel, or ordinary industrial waste.

The following procedure must be performed in a well-ventilated area or preferably outdoors. Never puncture or incinerate cylinders.

1. Wear the same PPE (personal protective equipment) as used while applying the two-component foam (i.e., half-mask or full-face negative pressure respirator fitted with combination stacked organic vapor cartridges and P-100 particulate filters on a clean shaven face, goggles or face shield [not required if full-face respirator is used], gloves and protective clothing.)
2. Liquids (“A & B”) remaining in the DuPont™ Froth-Pak™ kits must be disposed of as solid waste material, not liquid chemicals. Steps (3 thru 10) are intended guidelines necessary to convert any residual liquids into solids prior to proper disposal.
3. Carefully dispense and depressurize liquids from the cylinders with the gun and nozzle attached. Dispense chemicals out of the cylinder(s) as foam into a waste container lined with a plastic bag until one or both components/cylinders are empty.
4. Carefully remove the nozzle from the gun and continue to depressurize the cylinder(s) by dispensing the chemical(s) into a waste container lined with a plastic bag that has adequate absorbent (e.g., sawdust, kitty litter, dry absorbent) in the bottom.
5. Carefully close both cylinder valves completely, then operate the gun trigger to empty and depressurize the hoses.
6. Lift each cylinder. The cylinder should feel empty, with no sloshing of liquid.
7. Carefully remove the hoses from the cylinders. **Use caution in case there is some residual chemical and/or pressure still in the hoses.** Place hoses in plastic bag with absorbent material as in Step 4.

8. Carefully place cylinder(s) over a waste container lined with a plastic bag. Slowly open the valves on the cylinder(s) to catch any residual material. With cylinder pointed away from face, allow pressure to completely vent. Always handle and vent cylinders in a well-ventilated area while wearing proper respiratory protection.

CAUTION: There is potential that a hose is blocked and the tank is not yet empty. If the cylinder feels heavy, appears to be under too much pressure, or contains too much material, close the valve. In this case, the cylinder needs to be disposed of as a hazardous waste and cannot be emptied using these procedures.

9. Absorb any remaining liquids collected in Step 8 with dry oil-absorbent material as in Step 4. Once mixed thoroughly, it can be disposed of as ordinary industrial waste.

10. If the waste container contains an excess amount of "A" side versus "B" side, spray a small amount of water over the waste material but not enough to have a pool of liquid. Allow container and waste material in the plastic bag to vent while protected from the weather for 24-48 hours. After this time, tie the bag loosely and dispose of the solid waste as ordinary industrial waste.

If waste contains more B side than A side, then mix the material with a stick to ensure all liquids are absorbed and dispose of as ordinary industrial waste.

11. EMPTY and VENTED cylinders can be disposed of as scrap, recycle steel, or ordinary industrial waste.

THE ABOVE INFORMATION IS PROVIDED AS A COURTESY FOR CUSTOMERS AND DUPONT BELIEVES THAT IT IS ACCURATE. HOWEVER, CUSTOMER IS ULTIMATELY RESPONSIBLE FOR DETERMINING WHETHER THE INFORMATION IN THIS DOCUMENT IS APPROPRIATE FOR CUSTOMER'S USE AND FOR ENSURING THAT CUSTOMER'S WORKPLACE AND DISPOSAL PRACTICES ARE IN COMPLIANCE WITH APPLICABLE LAWS, REGULATIONS, AND OTHER GOVERNMENT ENACTMENTS. IF A CUSTOMER HAS ANY QUESTIONS REGARDING APPLICABLE DISPOSAL PROCEDURES, IT MUST CONTACT THE APPROPRIATE GOVERNMENT OFFICIAL. DUPONT ASSUMES NO OBLIGATION OR LIABILITY FOR THE INFORMATION IN THIS DOCUMENT.



**For more information visit
building.dupont.com
or call 1-866-583-2583**

NOTICE: No freedom from any patent owned by DuPont or others is to be inferred. Because use conditions and applicable laws may differ from one location to another and may change with time, Customer is responsible for determining whether products and the information in this document are appropriate for Customer's use and for ensuring that Customer's workplace and disposal practices are in compliance with applicable laws and other government enactments. The product shown in this literature may not be available for sale and/or available in all geographies where DuPont is represented. The claims made may not have been approved for use in all countries or regions. DuPont assumes no obligation or liability for the information in this document. References to "DuPont" or the "Company" mean the DuPont legal entity selling the products to Customer unless otherwise expressly noted. NO EXPRESS WARRANTIES ARE GIVEN EXCEPT FOR ANY APPLICABLE WRITTEN WARRANTIES SPECIFICALLY PROVIDED BY DUPONT. ALL IMPLIED WARRANTIES INCLUDING THOSE OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE EXPRESSLY EXCLUDED. The buyer assumes all risks as to the use of the material. Buyer's exclusive remedy or any claim (including without limitations, negligence, strict liability, or tort) shall be limited to the refund of the purchase price of the material. Failure to strictly adhere to any recommended procedures shall release DuPont Specialty Products USA, LLC or its affiliates, of all liability with respect to the materials or the use thereof. The information herein is not intended for use by non-professional designers, applicators or other persons who do not purchase or utilize this product in the normal course of their business. DuPont Polyurethane Foam Insulation and Sealants

CAUTION: When cured, these products are combustible and will burn if exposed to open flame or sparks from high-energy sources. Do not expose to temperatures above 240°F. For more information, consult (M)SDS call DuPont at 1-866-583-2583 or contact your local building inspector. In an emergency, call 1-989-636-4400. When air sealing buildings, ensure that combustion appliances, such as furnaces, water heaters, wood burning stoves, gas stoves and gas dryers are properly vented to the outside. See website: <http://www.epa.gov/iaq/homes/hip-ventilation.html>. In Canada visit: <http://archive.nrc-cnrc.gc.ca/eng/ibp/irc/bsi/83-house-ventilation.html>.

DuPont™ Froth-Pak™ Spray Polyurethane Foam contains isocyanate, hydrofluorocarbon blowing agent and polyol. Read all instructions and (M)SDS carefully before use. Wear protective clothing and cover all skin (including long sleeves), gloves, goggles or safety glasses, and proper respiratory protection. Do not breathe vapor or mist. Use only with adequate ventilation. It is recommended that applicators and those working in the spray area wear respiratory protection. Increased ventilation significantly reduces the potential for isocyanate exposure; however, supplied air or an approved air-purifying respirator equipped with an organic vapor sorbent and a particulate filter may still be required to maintain exposure levels below ACGIH, OSHA, WEEL or other applicable limits. For situations where the atmospheric levels may exceed the level for which an air-purifying respirator is effective, use a positive-pressure, air-supplying respirator (air line or self-contained breathing apparatus). Spraying large amounts of foam indoors may require the use of a positive pressure, air-supplying respirator. Contents under pressure.

Building and/or construction practices unrelated to insulation could greatly affect moisture and the potential for mold formation. No material supplier including DuPont can give assurance that mold will not develop in any specific system.

DuPont™, the DuPont Oval Logo, and all trademarks and service marks denoted with ™, SM or ® are owned by affiliates of DuPont de Nemours, Inc. unless otherwise noted. © 2019 DuPont.

43-D100620-enNA-1019 CDP