

The DuPont™ Cavitymate™ Ultra Wall System

A 3-in-1 continuous insulation, water and air barrier solution.



The DuPont™ Cavitymate™ Ultra Wall System using Styrofoam™ Brand Cavitymate™ Ultra is a 3-in-1 continuous insulation, water and air barrier solution. It was developed in response to feedback from architects and masons in need of a **consolidated system** for cavity walls that **exceeds new energy code requirements without negatively impacting schedule**. The system uses enhanced extruded polystyrene foam (XPS- Styrofoam™ Brand) with sealed joints using Great Stuff Pro™ Gaps & Cracks Polyurethane Foam Sealant.

Thermal Layer	
High R-Value	5.6 R/inch
Water-resistive Layer	
ASTM E331	Pass – No water penetration during 2 hours of pressurized testing
ASTM C272	Water absorption: 0.3% max
Air Sealing Layer	
ASTM E2357	Code: 0.04 cfm / ft ² ; 0.01606 cfm /ft ² MAX; Improvement over code: 258%
Vapor Retarding Layer	
ASTM E96	2.18" or greater ≤ 1.0 perm


Back Up Applications	CMU Block Cavity Wall		
NFPA-285 Approved Veneers	Brick – nominal 4" min. Concrete – 2" thick min.	CMUs – 4" thick min. Natural Stone – 2" thick min.	Cast Artificial Stone – 1 ½" thick min. Terracotta cladding – 1 ¼" thick min.
UL Ratings	U902, U912		
Joint Treatments	Great Stuff™ PRO Gaps & Cracks , LiquidArmor™		
Warranty	50 Year Limited Thermal Warranty		
LEED Points	EQ Credit: 1 point EA Credit: 1-19 points 24% Preconsumer Recycled Content: 2 points		
Standard Thicknesses	1.75" = R10, 2.18" = R12, 2.5"= R14 2.75"= R15.4, 3" = 16.8, 3.5"= 19.6		

Masons have been installing Styrofoam™ Brand Cavitymate™ Insulation for over 40 years. We've simply taken it a bit further to evolve with new code requirements while keeping it in the hands of the mason.

With the DuPont™ Cavitymate™ Ultra Wall System, masons can install the continuous insulation and air/vapor barrier while installing their masonry veneer. Contrary to other methods

of air sealing, this system has fewer weather restrictions preventing contractors from delay during winter months or due to other subcontractors.

Putting the system in the hands of the mason means one trade is in control of the construction and craftsmanship of the exterior wall. This allows for fewer scaffold sequences, less trade coordination, less labor, and a streamlined critical path.



The Result:

A cost-effective and complete system for an energy efficient masonry cavity wall.



**For more information visit
building.dupont.com
 or call 1-866-583-2583**

NOTICE: No freedom from infringement of any patent owned by DuPont or others is to be inferred. Because use conditions and applicable laws may differ from one location to another and may change with time, Customer is responsible for determining whether products and the information in this document are appropriate for Customer's use and for ensuring that Customer's workplace and disposal practices are in compliance with applicable laws and other government enactments. The product shown in this literature may not be available for sale and/or available in all geographies where DuPont is represented. The claims made may not have been approved for use in all countries. DuPont assumes no obligation or liability for the information in this document. References to "DuPont" or the "Company" mean the DuPont legal entity selling the products to Customer unless otherwise expressly noted. NO WARRANTIES ARE GIVEN; ALL IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE ARE EXPRESSLY EXCLUDED. The buyer assumes all risks as to the use of the material. Buyer's exclusive remedy or any claim (including without limitations, negligence, strict liability, or tort) shall be limited to the refund of the purchase price of the material. Failure to strictly adhere to any recommended procedures shall release DuPont of all liability with respect to the materials or the use thereof. The information herein is not intended for use by non-professional designers, applicators or other persons who do not purchase or utilize this product in the normal course of their business.

CAUTION: This product is combustible and shall only be used as specified by the local building code with respect to flame spread classification and to the use of a suitable thermal barrier. For more information, consult (Material) Safety Data Sheet ((M)SDS), call DuPont at 1-866-583-2583, or contact your local building inspector. In an emergency, call 1-989-636-4400.

DuPont™, the DuPont Oval Logo, and all trademarks and service marks denoted with™, SM or ® are owned by affiliates of DuPont de Nemours, Inc. unless otherwise noted. © 2020 DuPont.