

The DuPont™ Thermax™ Wall System at a Glance



Our system eliminates the need for batt insulation, exterior gypsum and air and water resistive barriers to easily achieve the highest standards in energy efficiency.

What is the DuPont™ Thermax™ Wall System?

The DuPont™ Thermax™ Wall System is a patented system from DuPont that offers architects and design professionals efficiency at every level by integrating thermal, air, and water barriers into one system. It meets all applicable IBC and ASHRAE requirements using industry-proven products for greater results – helping to make their commercial construction business even more profitable.

Key benefits of the DuPont™ Thermax™ Wall System: Exterior insulation:

- **Saves time and money** – simplifies the construction process for faster installation.
- **Best warranties in the industry** – 15-year thermal and water-resistant warranties and a 6-month exposure warranty.
- **High performance** – provides sustainable long-term thermal protection – which adds up to multiple LEED credits.

Exterior insulation products that fit within the system:

DuPont™ Thermax™ XARMOR™ (ci) Exterior Insulation

The only DuPont™ Thermax™ insulation with a unique dark exterior facer optimized to go behind rain screen exteriors and strong enough to stand up to tough job site conditions. It's the most efficient way to achieve continuous insulation.

DuPont™ Thermax™ (ci) Exterior Insulation

Our mid-range foil facer offers mid-range durability for an insulation that continues to outperform — provided at a lower price point to give builders more flexibility.

DuPont™ Thermax™ Sheathing

A rigid foam insulation that effectively reduces condensation for exceptional moisture protection

Exterior Product Details:

Product	Damage protection	Ship-lapped edges	Custom lengths	Meets IBC fire code requirements*
DuPont™ Thermax XARMOR™ (ci) Exterior Insulation	Highest	1.55" and greater	Yes	Yes
DuPont™ Thermax™ (ci) Exterior Insulation	Mid-grade			
DuPont™ Thermax™ Sheathing	Standard	Upon request		

* Exceptions exist; contact your building science expert for specifics related to your design.

Trust DuPont™ Thermax™ Insulation from the inside, out.

DuPont also offers a full line of interior DuPont™ Thermax™ insulation products that offer high efficiency and fit any size building or budget

Key benefits

- **Increased durability** – a differentiated, reinforced core allowing flexibility without breakage in the rigid board.
- **The most fire-resistant polyisocyanurate insulation** – UL Ratings, FM 4880, Class A, and many NFPA 285 compliant assemblies.
- **Free-rise technology** – provides a homogenous core that reduces warm holes, weak points and potential water, air, or fire paths – providing a better R-value and increased dimensional stability.

Interior Products:

DuPont™ Thermax™ Heavy Duty

The most durable finish choice can be pressure washed up to 2,000 psi.

DuPont™ Thermax™ Light Duty

A mid-grade facer strength that can be pressure washed up to 1,000 psi.

DuPont™ Thermax™ White Finish

With a white-embossed surface, this mid-grade facer is aesthetically pleasing.

DuPont™ Thermax™ Metal Building Board

Ideal for metal building owners and contractors, but can be used anywhere a washable interior surface is needed.

Interior Product Details:

Product	Durability	Maintenance	Specs	Applications
DuPont™ Thermax™ Heavy Duty	A tough finish for use in moderate-impact areas	1.55" and greater	Custom with options in max length: 30' Max thickness: 3"	Insulation and interior finish system for walls and ceilings in metal, wood post frame, and concrete or masonry buildings
DuPont™ Thermax™ Light Duty	Mid-grade for light impact areas		4' x 8' / 4' x 10' / 4' x 12' (custom lengths available)	
DuPont™ Thermax™ White Finish		Upon request		
DuPont™ Thermax™ Metal Building Board	1.25 mil embossed aluminum foil facer on both sides	Foil finish exterior for easy maintenance	Thickness Range: 0.5 – 4" (custom lengths available)	Embossed, noise-reducing facer with durability and moisture control

* Exceptions exist; contact your building science expert for specifics related to your design.

† Maintain a 3-foot minimum distance.



**For more information visit
thermaxwallsystem.com
or call 1-866-583-2583**

NOTICE: No freedom from any patent owned by DuPont or others is to be inferred. Because use conditions and applicable laws may differ from one location to another and may change with time, Customer is responsible for determining whether products and the information in this document are appropriate for Customer's use and for ensuring that Customer's workplace and disposal practices are in compliance with applicable laws and other government enactments. The product shown in this literature may not be available for sale and/or available in all geographies where DuPont is represented. The claims made may not have been approved for use in all countries or regions. DuPont assumes no obligation or liability for the information in this document. References to "DuPont" or the "Company" mean the DuPont legal entity selling the products to Customer unless otherwise expressly noted. NO EXPRESS WARRANTIES ARE GIVEN EXCEPT FOR ANY APPLICABLE WRITTEN WARRANTIES SPECIFICALLY PROVIDED BY DUPONT. ALL IMPLIED WARRANTIES INCLUDING THOSE OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE EXPRESSLY EXCLUDED. The buyer assumes all risks as to the use of the material. Buyer's exclusive remedy or any claim (including without limitations, negligence, strict liability, or tort) shall be limited to the refund of the purchase price of the material. Failure to strictly adhere to any recommended procedures shall release DuPont Specialty Products USA, LLC or its affiliates, of all liability with respect to the materials or the use thereof. The information herein is not intended for use by non-professional designers, applicators or other persons who do not purchase or utilize this product in the normal course of their business.

BEFORE HANDLING OR USING THIS PRODUCT, READ AND UNDERSTAND THE MATERIAL SAFETY DATA SHEET. For more information call the DuPont Contact Center at 866-583-2583 or contact your local building inspector. For emergencies contact Chemtrec 800-424-9300, CCN (Contract Number) 7442

DuPont™, the DuPont Oval Logo, and all trademarks and service marks denoted with ™, SM or ® are owned by affiliates of DuPont de Nemours, Inc. unless otherwise noted. © 2023 DuPont.

43-D100647-enNA-0523 CDP