



OSHA standards for dry crystalline silica dust

What is crystalline silica?

Crystalline silica is a basic ingredient of the Earth's crust, found in many naturally occurring and man-made materials, including rock, soil, sand, concrete and brick. Quartz is the most common form of crystalline silica. Cristobalite and tridymite are two others.

What are the risks?

When workers crush, cut, chip, drill or grind objects containing crystalline silica, the mineral may be broken down into small particles, becoming a dry particulate inhalation hazard. Crystalline silica dust exposure is associated with foundry work, sandblasting, hydraulic fracturing and many other jobs. The Occupational Safety and Health Administration (OSHA) estimates that 2 million workers are exposed to silica dust in the United States.¹

Crystalline silica dust has been recognized as a serious health hazard to industrial workers for decades. Workers who are exposed to crystalline silica dust are at increased risk of developing serious health problems, including silicosis—an incurable lung illness—as well as lung cancer, chronic obstructive pulmonary disease (COPD) and other respiratory diseases—even kidney disease.

What are the standards?

OSHA established exposure limits for crystalline silica more than 40 years ago. In June 2016, two new OSHA standards for crystalline silica came into effect: one for maritime and general industry and the other for the construction industry.

The new standards establish a permissible exposure limit of 50 micrograms of respirable crystalline silica per cubic meter of air (50 µg/m³) as an eight-hour time-weighted average in all industries covered by the rule.²

The 2016 standards include additional provisions to help protect employees, including requirements for exposure assessment, exposure control methods, respiratory protection, medical surveillance, hazard communication and recordkeeping.

While respiratory protection is the only personal protective equipment (PPE) prescribed by the new standards, other forms of PPE, including protective clothing, are critical to maximizing worker protection.

Controlling the spread of crystalline silica dust

With all workplace hazards, OSHA expects employers to apply the hierarchy of exposure controls to protect workers. Employers should eliminate hazards or substitute lower-hazard alternatives first. Next, engineering solutions should be implemented, followed by administrative controls. If these controls have been applied and residual risk remains, then the use of personal protective equipment (PPE) is warranted.

In addition to on-the-job exposure, workers can unknowingly carry crystalline silica dust home on their clothes, shoes, skin, tools and vehicle interiors. Other people, especially family members, can be exposed to silica that has become embedded in auto upholstery, home furniture and clothing via shared laundry loads. Similarly, crystalline silica dust can be circulated through household air and transmitted through person-to-person contact.

OSHA has standards aimed at preventing the incidence of these so-called “take-home toxin” events. The 2016 crystalline silica standards include requirements for establishing regulated/restricted areas, engineering controls, work practices and housekeeping to contain and control crystalline silica exposure.

What protective apparel is available?

Employers can help prevent the spread of crystalline silica dust by choosing effective protective garments for workers and requiring them to don and doff apparel on-site. Employers in many industries trust protective garments made with DuPont™ Tyvek®, which are:



Soft & lightweight



Durable




Low linting



Chemically and biologically inert

With Tyvek® protective garments, protection is built into the fabric itself. The barrier extends throughout the garment and helps provide excellent protection against particles in the 1-2 µm range. (Spunbonded polypropylene fabric, by contrast, has an open structure and offers a poor barrier against particles in the 1-2 µm range.)

Tyvek® garment options include coveralls with or without respirator-fit hoods, lab coats and aprons, as well as a variety of accessories, including hoods, sleeves and skid-resistant shoe and boot covers. Tyvek® coveralls feature a comfort-fit design that improves worker mobility and makes the garments easier to put on and take off.



References:

¹[OSHA Fact Sheet](#): OSHA's Respirable Crystalline Silica Standard for Construction, 2017

²[OSHA Standard for Crystalline Silica](#): General Industry and Maritime

Tyvek® 500, Tyvek® 600 and Tyvek® 800 contain natural rubber latex which may cause allergic reactions in some sensitized individuals. Anyone who begins to exhibit an allergic response during the use of DuPont products should immediately cease using these products and should also be reported to DuPont at 1-800-441-3637 (outside the U.S. 1-302-774-1139).

This information is based upon technical data that DuPont believes to be reliable. It is subject to revision as additional knowledge and experience become available. It is the user's responsibility to determine the level of toxicity and the proper personal protective equipment needed. The information set forth herein reflects laboratory performance of fabrics, not complete garments, under controlled conditions. This information is intended for use by persons having the technical expertise to undertake evaluation under their own specific end-use conditions, at their own discretion and risk. Anyone intending to use this information should first check that the garment selected is suitable for the intended use. The end-user should discontinue use of garment if fabric becomes torn, worn or punctured, to avoid potential chemical exposure. Since conditions of use are beyond our control, DUPONT MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING BUT NOT LIMITED TO WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE AND ASSUME NO LIABILITY IN CONNECTION WITH ANY USE OF THIS INFORMATION. This information is not intended as a license to operate under or a recommendation to infringe any trademark, patent or technical information of DuPont or other persons covering any material or its use.



DuPont Personal Protection
Customer service 1 800 931 3456
safespec.dupont.com
personalprotection.dupont.com

© 2023 DuPont. All rights reserved. DuPont™, the DuPont Oval Logo, and all trademarks and service marks denoted with™, SM or ® are owned by affiliates of DuPont de Nemours, Inc. unless otherwise noted. (05/23) DSF23_2301-0163_3-7970