




PRODUCT INFORMATION

DuPont™ Tychem® 2000 Coverall. Standard Fit Hood. Stormflap. Elastic Wrists and Ankles. Storm Flap with Adhesive Closure. Taped Seams. Semi-auto locking slider zipper pull. Yellow.

ATTRIBUTES

| | |
|------------------|---|
| Full Part Number | QC127TYLxx0004yy (xx=size;yy=option code) |
| Fabric/Materials | TYCHEM® 2000 |
| Design | Coverall w/ Hood, Elastic Wrists and Ankles |
| Seam | Taped |
| Color | Yellow |
| Quantity/Box | 4 per case |
| Sizes | MD, LG, XL, 2X, 3X, 4X, 5X |
| Option Codes | 00 |



SIZE TABLE

| SIZE | SLEEVE LENGTH | CHEST WIDTH | INSEAM | FITS CHEST | FITS HEIGHT |
|------|---------------|-------------|--------|-----------------|--------------|
| MD | 33 3/4 | 24 1/4 | 27 1/2 | 35 1/4 - 38 3/4 | 5'3" - 5'7" |
| LG | 35 | 25 3/4 | 28 1/2 | 38 1/4 - 41 3/4 | 5'5" - 5'9" |
| XL | 36 1/2 | 27 1/4 | 29 | 41 1/4 - 44 3/4 | 5'8" - 6'2" |
| 2X | 38 1/4 | 28 3/4 | 30 | 44 1/4 - 47 3/4 | 6'0" - 6'4" |
| 3X | 38 1/2 | 30 1/4 | 31 | 47 1/4 - 50 3/4 | 6'2" - 6'4" |
| 4X | 39 1/2 | 32 | 32 1/2 | 50 3/4 - 54 1/4 | 6'4" - 6'7" |
| 5X | 40 1/2 | 33 1/2 | 33 1/2 | 53 3/4 - 57 1/4 | 6'7" - 6'10" |

PHYSICAL PROPERTIES

| PROPERTY | TEST METHOD | TYPICAL RESULT |
|----------------------------------|-------------|------------------------|
| Thickness (PPSH-249) | ASTM D1777 | 10 mils |
| Basis Weight | ASTM D3776 | 2.5 oz/yd ² |
| Burst Strength - Mullen. | ASTM D3786 | 68 psi |
| Tear Resistance - Trap Tear (MD) | ASTM D5587 | 6.4 lb _f |
| Tear Resistance - Trap Tear (CD) | ASTM D5587 | 5 lb _f |
| Breaking Strength - Grab (MD). | ASTM D5034 | 39 lb _f |
| Breaking Strength - Grab (CD) | ASTM D5034 | 43 lb _f |
| Wearing Apparel Flammability | 16 CFR 1610 | Class 1 |


WARNING

*Serged and bound seams are degraded by some hazardous liquid chemicals, such as strong acids, and should not be worn when these chemicals are present.
 *CAUTION: This information is based upon technical data that DuPont believes to be reliable. It is subject to revision as additional knowledge and experience are gained. DuPont makes no guarantee of results and assumes no obligation or liability in connection with this information. It is the user's responsibility to determine the level of toxicity and the proper personal protective equipment needed. The information set forth herein reflects laboratory performance of fabrics, not complete garments, under controlled conditions. It is intended for informational use by persons having technical skill for evaluation under their specific end-use conditions, at their own discretion and risk. Anyone intending to use this information should first verify that the garment selected is suitable for the intended use. In many cases, seams and closures have shorter breakthrough times and higher permeation rates than the fabric. Please contact DuPont for specific data. If fabric becomes torn, abraded or punctured, or if seams or closures fail, or if attached gloves, visors, etc. are damaged, end user should discontinue use of garment to avoid potential exposure to chemical. Since conditions of use are outside our control, we make no warranties, express or implied, including, without limitation, no warranties of merchantability or fitness for a particular use and assume no liability in connection with any use of this information. This information is not intended as a license to operate under or a recommendation to infringe any patent or technical information of DuPont or others covering any material or its use.

Cellosolve® and Selexol™ are registered trademarks of Dow Chemicals Company. Skydrol® is a registered trademark of Solutia.
 Tyvek® 500, Tyvek® 600, Tyvek® 800 products manufactured before January 2023 did contain natural rubber latex which may cause allergic reactions in some sensitized individuals. Anyone who begins to exhibit an allergic response during the use of DuPont products should immediately cease using these products. The incident should also be reported to DuPont at +1 (888) 439-2988 so that an investigation can be initiated.

DuPont™ SafeSPEC™ - We're here to help

Our powerful web-based tool can assist you with finding the appropriate DuPont garments for chemical and controlled environment hazards.



DuPont Personal Protection
SafeSPEC™

DuPont Personal Protection

DuPont Personal Protection

CREATED ON: APRIL 26, 2024

© 2024 DuPont. All rights reserved. DuPont™, the DuPont Oval Logo, and all trademarks and service marks denoted with ™, SM or ® are owned by affiliates of DuPont de Nemours, Inc. unless otherwise noted.