

# Baby Strollers and Seating



## Polymers for Strollers:

DuPont™ Performance Polymers make an excellent choice for the durability and performance of strollers and seats. Choosing the right polymers also helps to ensure the safety and comfort of young children in the stroller.

Engineering polymers help influence highly innovative designs, allowing several functions to be integrated into single parts for structural components, often replacing heavier metal parts.

Integrating functionality and using fewer but higher-performing polymers benefits users by reducing total weight. This could result in productivity and cost benefits for the manufacturer.

DuPont™ Zytel® polyamide resin with HTN can be ideal for structural parts requiring strength and stiffness, making it an excellent candidate for metal replacement. DuPont™ Delrin® acetal homopolymer is an excellent choice for moving parts and mechanisms with low friction and high strength. For energy management, suspension and dampening requirements, DuPont™ Hytrel® provides performance in innovative designs and provides long-term performance stability.

## Foldable Baby Strollers:

Through innovative designs using DuPont Performance Polymers, these strollers can be conveniently folded and unfolded with just one hand and with minimal effort. Transportation in cars or in planes becomes easier, as parents can focus on the safety and care of the child.

DuPont offers one of the broadest portfolios of engineering polymers and thermoplastic elastomers for use in a variety of applications. These materials offer benefits, including:

- Stronger structure but lighter weight
- Optimal design flexibility for a variety of stroller types
- Outstanding durability with exceptional fatigue resistance
- A smooth, comfortable ride due to resilient suspension thanks to DuPont Hytrel® TPEE elastomer

# Baby Strollers and Seating

## Mechanical Features

- High strength and stiffness
- Impact resistance
- Fatigue resistance
- Vibration dampening
- Wear and friction resistance

## Key Benefits

- Innovative design and functions
- Safety and comfort
- Durability and reliability
- Sustainability

## Products for strollers and seat components:

Typical Application	DuPont Material	Product Family	Attribute
Structural stiffness components	Zytel® 80G14	PA66	Toughen with 14% GR
	Zytel® 80G33	PA66	Toughen with 33% GR
	Zytel® 73G30T	PA6	Toughen with 30% GR
Higher stiffness components	Zytel® HTN 53G50	High Performance PA	50% GR
Mechanical/Moving components	Delrin® 900P	Homo-POM	Low viscosity
	Delrin® 500P	Homo-POM	Medium viscosity
	Delrin® 100P	Homo-POM	High viscosity
	Delrin® 500AL	Homo-POM	Medium viscosity + Enhanced wear resistance
	Delrin® 100AL	Homo-POM	High viscosity + Enhanced wear resistance
Shock & vibration absorption parts	Hytrel® 5556	TPC-ET	55D hardness thermoplastic elastomers
	Hytrel® 6356	TPC-ET	63D hardness thermoplastic elastomers
	Hytrel® 7246	TPC-ET	72D hardness thermoplastic elastomers

## Let's Talk:

We have the right materials, technology and technical resources to help you design and manufacture superior parts and systems.

## Contact Us

<https://www.dupont.com/mobility>

DuPont™, the DuPont Oval Logo, and all trademarks and service marks denoted with™, ™ or ® are owned by affiliates of DuPont de Nemours, Inc. unless otherwise noted. ©2021 DuPont.

The information set forth herein is furnished free of charge and is based on technical data that DuPont believes to be reliable and falls within the normal range of properties. It is intended for use by persons having technical skill, at their own discretion and risk. This data should not be used to establish specification limits nor used alone as the basis of design. Handling precaution information is given with the understanding that those using it will satisfy themselves that their particular conditions of use present no health or safety hazards. Since conditions of product use and disposal are outside our control, we make no warranties, express or implied, and assume no liability in connection with any use of this information. As with any product, evaluation under end-use conditions prior to specification is essential. Nothing herein is to be taken as a license to operate or a recommendation to infringe on patents.