

# DuPont™ Vespel® CP-0664 Composite Wear Coating Adds Life to V-Grooves

## Application

Jet engine designs utilize v-grooves to create air seals between the engine fan case and nacelle (Figure 1). V-grooves need to be durable to withstand corrosion and multiple impacts over the life of the engine.

## Challenges

- Major seal components are typically coated aluminum
- Coatings have to hold up to repeated impacts to avoid damage to primary metal
- V-grooves must be treated to prevent corrosion from exposure to weather and operational environments
- Components must be easily maintained in the field to maximize service time

## Solution

- Vespel® CP-0664 is a unique composite fabric coating used in a variety of aerospace applications up to 400 °F/205 °C
- Material can be pre-formed to required geometries for bonding to critical surfaces
- Fabric provides low friction and durable coating to aluminum surfaces while creating a corrosion barrier

## Features and Benefits

### Wear resistance

Vespel® CP-0664 has seen extensive use in jet engine fans and nacelles and proven itself with years of service. Wear testing has been conducted over a variety of test conditions and proven to survive from 7,500 to more than 250,000 cycles. A transfer film is created on the mating metal surface which minimizes the wear on both the metal and composite surfaces (Figure 2).

### Low friction

PTFE fibers enhance friction performance, dropping the dynamic coefficient of friction below 0.15. Higher loads only improve frictional behavior (Figure 3).




Figure 1. V-grooves are utilized in jet engine designs



Vespel® CP-0664 for v-groove coatings

### Shear strength/Impact resistance/Durability

Vespel® CP-0664 was subjected to 70 impacts with a dynamic load of more than 150 lbf with no visible damage to material or mating components.

### Corrosion resistance

Vespel® CP-0664 has unique composite construction that creates an insulating barrier between mating metal surfaces.

### Design flexibility


Material can be molded to match unique geometry of most v-groove designs. Parts can be easily bonded at initial assembly or in the field.

### Protects expensive components from wear, extending life


A lot of aluminum coatings are brittle and can be easily damaged in use or experience corrosion with exposure to normal environmental conditions. Vespel® CP-0664 has demonstrated ability to protect larger engine components and fan cases from damage that can lead to costly repairs and removal of engines from service.

### Solving a variety of problems

Vespel® CP-0664 has been used to solve a variety of problems. From v-grooves, fan blade roots, and door/cowl guides to track liners on thrust reversers. The versatility and durability allows you to think out of the box to solve wear and coating problems that are leading to costly repairs on major components.



**Figure 2.** Impact/wear test fixture with transfer film on mating surface that reduces friction and enhances durability



**Figure 3.** DuPont™ Vespel® CP-0664 Coefficient of Friction

Visit us at [vespel.com](http://vespel.com)

The information set forth herein is furnished free of charge, is based on technical data that DuPont believes to be reliable and represents typical values that fall within the normal range of properties. This information relates only to the specific material designated and may not be valid for such material used in combination with other materials or in other processes. It is intended for use by persons having technical skill, at their own discretion and risk. This information should not be used to establish specification limits nor used alone as the basis of design. Handling precaution information is given with the understanding that those using it will satisfy themselves that their conditions of use present no health or safety hazards and comply with applicable law. Since conditions of product use and disposal are outside our control, we make no warranties, express or implied, and assume no liability in connection with any use of this information. As with any product, evaluation under end use conditions prior to specification is essential. Nothing herein is to be taken as a license to operate or a recommendation to infringe on patents.

**CAUTION:** Do not use DuPont materials in medical applications involving implantation in the human body or contact with internal body fluids or tissues unless the material has been provided from DuPont under a written contract that is consistent with the DuPont policy regarding medical applications and expressly acknowledges the contemplated use. For further information, please contact your DuPont representative.

DuPont's sole warranty is that our products will meet our standard sales specifications in effect at the time of shipment. Your exclusive remedy for breach of such warranty is limited to refund of purchase price or replacement of any product shown to be other than as warranted. TO THE FULLEST EXTENT PERMITTED BY APPLICABLE LAW, DUPONT SPECIFICALLY DISCLAIMS ANY OTHER EXPRESS OR IMPLIED WARRANTY OF FITNESS FOR A PARTICULAR PURPOSE, MERCHANTABILITY, OR NON-INFRINGEMENT. DUPONT DISCLAIMS LIABILITY FOR ANY SPECIAL, INCIDENTAL, OR CONSEQUENTIAL DAMAGES.

DuPont™, the DuPont Oval Logo, and all trademarks and service marks denoted with ™, SM or ® are owned by affiliates of DuPont de Nemours, Inc. unless otherwise noted. © 2022 DuPont. All rights reserved.

Form No. VPE-A40044-00-A0822 CDP



[dupont.com](http://dupont.com)