



WATER TREATMENT AT POWER PLANT

Boiling Water Reactor Condensate Polisher and Reactor Water Clean Up Product Recommendations

The resins employed for boiling water reactor (BWR) purification must be able to purify water to a maximum degree. Any traces of organic and inorganic impurities will become visible in the pure water environment of the reactor circuits. Our IRN-grade ion exchange resins are proven to be the premier resins chosen to protect nuclear power plants throughout the world, able to maintain the purity of the BWR circuit even in extreme temperature conditions.

PRODUCT	APPLICATION	FEATURES AND RECOMMENDED USES	TYPE	MATRIX	MINIMUM TOTAL VOLUME CAPACITY (eq/L)	IONIC FORM AS SHIPPED
AMBERLITE™ IRN99 H	CPP	AMBERLITE™ IRN99 H Resin is a premium 16% DVB uniform particle size cation resin with very high capacity and oxidative stability. The high oxidative stability reduces reactor water sulfate concentration in BWR condensate polishing. AMBERLITE™ IRN78 OH is a premium high solids uniform particle size anion resin with very high capacity. It is specifically processed to minimize organic chloride content. This pairing offers the highest capacity and lowest sulfate with less-separating characteristics.	SAC	GEL	2.50	H ⁺
AMBERLITE™ IRN78 OH	CPP		SBA	GEL	1.20	OH ⁻
AMBERLITE™ IRN150 H/OH	CPP/RWCU	Nuclear grade mixed bed composed of uniform particle size AMBERLITE™ IRN77 H and IRN78 OH Resins on a 1:1 equivalent basis.	MB	GEL/GEL	1.90/1.20	H ⁺ /OH ⁻
AMBERLITE™ IRN160 H/OH	CPP/RWCU	High capacity nuclear grade mixed bed composed of uniform particle size AMBERLITE™ IRN97 H and IRN78 OH Resins on a 1:1 equivalent basis. Designed to minimize separation of anion and cation during installation and transfer in BWR condensate polishing.	MB	GEL/GEL	2.10/1.20	H ⁺ /OH ⁻
AMBERLITE™ IRN170 H/OH	CPP/RWCU	Premium nuclear grade mixed bed composed of uniform particle size AMBERLITE™ IRN99 H and IRN78 OH Resins on a 1:1 equivalent basis. Offers maximum oxidative stability and highest operating capacity to achieve the lowest reactor water sulfate concentration and longest resin life for all BWR applications.	MB	GEL/GEL	2.50/1.20	H ⁺ /OH ⁻

Key:

- CPP = Condensate Polishing Plant
- RWCU = Reactor Water Clean Up
- SBA = Strong Base Anion
- SAC = Strong Acid Cation
- MB = Mixed Bed

Powering performance worldwide.

With a large global manufacturing footprint, strong R&D expertise and technical support services and systems, we supply high market volumes with high quality. Dow partners with you, our customer, to understand unmet needs and develop tailored solutions.

● RESEARCH & DEVELOPMENT

Chauny, France*
Collegetown, PA*
Edina, MN*
Huzhou, China
Kaust Jeddah, KSA
Midland, MI*
Shanghai, China*
Tarragona, Spain**


*DW&PS Technology Center
**Global Water Technology Center

● COMMERCIAL OPERATIONS

Astana, Kazakhstan
Bangkok, Thailand
Budapest, Hungary
Dubai, UAE
Horgen, Switzerland
Johannesburg, South Africa
Kuala Lumpur, Malaysia
Moscow, Russia
Mumbai, India
Nairobi, Kenya
Rheinmünster, Germany
São Paulo, Brazil
Seoul, Korea
Sydney, Australia
Tokyo, Japan
Warsaw, Poland

● MANUFACTURING

Chauny, France
Edina, MN
Fombio, Italy
Huzhou, China
Jubail Industry City, Saudi Arabia
Menlo Park, CA
Midland, MI
Qingpu, China
Soma, Japan



Water & Process Solutions

7600 Metro Blvd.
Edina, MN 55439

For more information, contact our Customer Information Group:

Asia Pacific	+86 21 3851 4988
Europe, Middle East, Africa	+31 115 672626
Latin America	+55 11 5184 8722
North America	1-800-447-4369

dowwaterandprocess.com

WARNING: Oxidizing agents such as nitric acid attack organic ion exchange resins under certain conditions. This could lead to anything from slight resin degradation to a violent exothermic reaction (explosion). Before using strong oxidizing agents, consult sources knowledgeable in handling such materials.

NOTICE: No freedom from infringement of any patent owned by Dow or others is to be inferred. Because use conditions and applicable laws may differ from one location to another and may change with time, Customer is responsible for determining whether products and the information in this document are appropriate for Customer's use and for ensuring that Customer's workplace and disposal practices are in compliance with applicable laws and other government enactments. The product shown in this literature may not be available for sale and/or available in all geographies where Dow is represented. The claims made may not have been approved for use in all countries. Dow assumes no obligation or liability for the information in this document. References to "Dow" or the "Company" mean the Dow legal entity selling the products to Customer unless otherwise expressly noted. NO WARRANTIES ARE GIVEN EXCEPT FOR ANY SPECIFIC WARRANTY SET FORTH HEREIN; ALL IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE ARE EXPRESSLY EXCLUDED.

All information set forth herein is for informational purposes only. This information is general information and may differ from that based on actual conditions. Please note that physical properties may vary depending on certain conditions and while operating conditions stated in this document are intended to lengthen product lifespan and/or improve product performance, it will ultimately depend on actual circumstances and is in no event a guarantee of achieving any specific results. Nothing in this document should be treated as a warranty by Dow.

Printed in the U.S.A.

©™ Trademark of The Dow Chemical Company ("Dow") or an affiliated company of Dow

Form No. 177-03672-0518 CDP