



WATER TREATMENT AT POWER PLANT

# Cooling Water Blow-Down Product Recommendations

Cooling tower blowdown is often too impaired to be reused without treatment and is typically sent directly to the facility's wastewater treatment plant. This imposes a hydraulic load on the wastewater treatment system. More importantly, a tremendous amount of relatively clean water is wasted, adding significant cost and discharge compliance complexity. Dow can work with you to deliver the optimal solution for your needs, using robust, reliable, fouling-resistant filtration and purification technologies to recover and return up to 90% of blowdown water for makeup water use.

TECHNOLOGY	PRODUCT	APPLICATION	FEATURES
<b>ULTRAFILTRATION MODULE AND SKIDS</b>	DOW IntegraFlux™ SFP-2880XP Module	Suspended Solids Removal	High permeability and high mechanical strength hollow fiber Polyvinylidene fluoride (PVDF) membranes. The modules provide excellent performance, industry leading membrane area with low energy and chemical consumption. XP fiber provides up to 35% higher permeability than previous generation modules improving operating efficiencies and productivity.
	DOW™ Ultrafiltration SFP- 2880 Module		High mechanical strength hollow fiber PVDF membranes. The modules provide excellent performance with industry-leading membrane area.
	DOW IntegraPac™ IP-77XP Skid		The skids are pre-engineered, standardized and ready to assemble. Comprising of DOW IntegraPac™ modules (standard and XP fiber), auxiliary parts and piping the skids can significantly streamline design, assembly, and installation. Flexible sizing with 6-22 modules per skid.
	DOW IntegraPac™ IP-77 Skid		
<b>REVERSE OSMOSIS ELEMENTS</b>	DOW FILMTEC™ FORTILIFE™ CR 100	Demineralization from Challenging Feedwater Source	State-of-the-art solution to tackle tough fouling coupled with excellent salt rejection.
	DOW FILMTEC™ ECO PRO-400		State-of-the-art solution to deliver high salt rejection at low operating pressure reducing CAPEX and OPEX.
	DOW FILMTEC™ BW30XFR-400/34		Established high fouling resistance and fouling removal efficiency coupled with very high rejection proven at broad TDS range.
	DOW FILMTEC™ BW30XFRLE-400/34		Improved fouling resistance as well as efficiency of element's cleaning combined with low energy consumption and good water purity.
	DOW FILMTEC™ BW30-400/34		Consistent and reliable high operational performance coupled with increased productivity comparing to BW30-365.
	DOW FILMTEC™ BW30-365		Established industry reference product providing consistent, high performance and long element life with decades of proven performance.
<b>ION EXCHANGE</b>	AMBERLITE™ IRC120 Na	Softening	General-purpose, durable resin offers a good balance of capacity and strength resulting in long lifetime for co-flow regenerated systems.
	AMBERLITE™ IRC200 Na		Highest physical stability for harsh applications and co-flow regenerated systems involving appreciable oxidative potential or high temperatures.
	AMBERLITE™ IRC83 H		General-purpose high-capacity dealkalization and softening resin with improved operating capacity demonstrated in high TDS Na form operation.
	AMBERLITE™ SCAV4 Cl	Scavenging	Removal of high load hydrophilic and hydrophobic NOM at neutral to alkaline pH, with excellent resin lifetime and long, stable performance even under challenging operational conditions. It is the go-to organic scavenger for the bulk removal of NOM, and especially useful as RO pretreatment.

## Powering performance worldwide.

With a large global manufacturing footprint, strong R&D expertise and technical support services and systems, we supply high market volumes with high quality. Dow partners with you, our customer, to understand unmet needs and develop tailored solutions.

### ● RESEARCH & DEVELOPMENT

Chauny, France\*  
Collegetown, PA\*  
Edina, MN\*  
Huzhou, China  
Kaust Jeddah, KSA  
Midland, MI\*  
Shanghai, China\*  
Tarragona, Spain\*\*


\*DW&PS Technology Center  
\*\*Global Water Technology Center

### ● COMMERCIAL OPERATIONS

Astana, Kazakhstan  
Bangkok, Thailand  
Budapest, Hungary  
Dubai, UAE  
Horgen, Switzerland  
Johannesburg, South Africa  
Kuala Lumpur, Malaysia  
Moscow, Russia  
Mumbai, India  
Nairobi, Kenya  
Rheinmünster, Germany  
São Paulo, Brazil  
Seoul, Korea  
Sydney, Australia  
Tokyo, Japan  
Warsaw, Poland

### ● MANUFACTURING

Chauny, France  
Edina, MN  
Fombio, Italy  
Huzhou, China  
Jubail Industry City, Saudi Arabia  
Midland, MI  
Qingpu, China  
Soma, Japan



## Water & Process Solutions

7600 Metro Blvd.  
Edina, MN 55439

## For more information, contact our Customer Information Group:

Asia Pacific	+86 21 3851 4988
Europe, Middle East, Africa	+31 115 672626
Latin America	+55 11 5184 8722
North America	1-800-447-4369

[dowwaterandprocess.com](http://dowwaterandprocess.com)

WARNING: Oxidizing agents such as nitric acid attack organic ion exchange resins under certain conditions. This could lead to anything from slight resin degradation to a violent exothermic reaction (explosion). Before using strong oxidizing agents, consult sources knowledgeable in handling such materials.

NOTICE: No freedom from infringement of any patent owned by Dow or others is to be inferred. Because use conditions and applicable laws may differ from one location to another and may change with time, Customer is responsible for determining whether products and the information in this document are appropriate for Customer's use and for ensuring that Customer's workplace and disposal practices are in compliance with applicable laws and other government enactments. The product shown in this literature may not be available for sale and/or available in all geographies where Dow is represented. The claims made may not have been approved for use in all countries. Dow assumes no obligation or liability for the information in this document. References to "Dow" or the "Company" mean the Dow legal entity selling the products to Customer unless otherwise expressly noted. NO WARRANTIES ARE GIVEN EXCEPT FOR ANY SPECIFIC WARRANTY SET FORTH HEREIN; ALL IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE ARE EXPRESSLY EXCLUDED.

All information set forth herein is for informational purposes only. This information is general information and may differ from that based on actual conditions. Please note that physical properties may vary depending on certain conditions and while operating conditions stated in this document are intended to lengthen product lifespan and/or improve product performance, it will ultimately depend on actual circumstances and is in no event a guarantee of achieving any specific results. Nothing in this document should be treated as a warranty by Dow.

Printed in the U.S.A.

™ Trademark of The Dow Chemical Company ("Dow") or an affiliated company of Dow

Form No. 609-50292-0718 CDP