



Water Solutions



DuPont Water Solutions for Oil & Gas

Water quality is critical to improve the recovery and minimize the environmental impact of hydrocarbon production. Solids removal and salinity adjustments from the industrial water produced during this process are a major concern for oil and gas producers looking to protect their wells, lower costs, protect downstream equipment, and reduce safety and environmental issues. DuPont Water Solutions offers expertise and a growing portfolio of technologies to address the unique industrial water resource management needs of the hydrocarbon exploration and production industry.

Water technologies for onshore and offshore systems

The prevention of sulfate precipitation and souring in an injection well or reservoir is a major concern for oil and gas producers looking to effectively extract oil from wells, reduce costs, protect downstream equipment, and mitigate safety and environmental risks. Since injection water quality is critical to improve oil recovery, DuPont Water Solutions provides various solutions that can be used in various steps of injection water treatment systems for safe and reliable operation.

Products Offered for Injection Water		
Pretreatment for Particle Removal	<ul style="list-style-type: none"> • DuPont™ IntegraFlo™ Ultrafiltration • Integrated Ultrafiltration (iUF) 	<ul style="list-style-type: none"> • MEMCOR® P20N
Offshore Sulfate Removal	<ul style="list-style-type: none"> • FilmTec™ SR90-400i • FilmTec™ SR90-440i 	<ul style="list-style-type: none"> • FilmTec™ SR90HR-440i • FilmTec™ Fortilife™ SR90i
Desalination	<ul style="list-style-type: none"> • Reverse osmosis & nanofiltration elements 	
Degasification	<ul style="list-style-type: none"> • DuPont™ Ligasep™ LDM-040-LS • DuPont™ Ligasep™ LDM-120-LS 	<ul style="list-style-type: none"> • DuPont™ Ligasep™ LDM-040-HS • DuPont™ Ligasep™ LDM-120-HS

Addressing pressing needs for produced water treatment

Produced water is the water byproduct that comes out of the well with the crude oil. The composition of produced water varies widely from well to well, but typically contains soluble and non-soluble oil/organics, suspended solids, dissolved solids, and toxic heavy metals and must be treated before discharge or reinjection. DuPont offers a variety of solutions to effectively treat produced water for reuse or discharge.

Products Offered for Produced Water Treatment		
Organics / Oil Removal	<ul style="list-style-type: none"> • DuPont™ AmberLite™ ROC110 Oil-Coalescing Media • DuPont™ AmberSorb™ L493 Polymeric Adsorbent • DuPont™ AmberLite™ XAD™ 4 Polymeric Adsorbent • DuPont™ AmberLite™ XAD™ 16 Polymeric Adsorbent 	<ul style="list-style-type: none"> • DuPont™ AmberLite™ SCAV1 Ion Exchange Resin • DuPont™ AmberLite™ SCAV2 Ion Exchange Resin
Biodegradable Organics & Nutrients Removal	<ul style="list-style-type: none"> • MEMCOR® B40 	
Salinity Management	<ul style="list-style-type: none"> • FilmTec™ SW30HRLE Elements • FilmTec™ SW30XHR Elements 	<ul style="list-style-type: none"> • FilmTec™ Fortilife™ XC Elements • FilmTec™ XUS180808
Hardness Removal	<ul style="list-style-type: none"> • DuPont™ AmberLite™ IRC83 H • DuPont™ AmberLite™ HPR8300 H • DuPont™ AmberLite™ HPR1100 Na • DuPont™ AmberSep™ Chelating Resins 	<ul style="list-style-type: none"> • FilmTec™ Fortilife™ XC-N • FilmTec™ NF270 Elements • FilmTec™ NF90 Elements
Heavy Metal Removal	<ul style="list-style-type: none"> • DuPont™ AmberSep™ IRC748 UPS Chelating Resin • DuPont™ AmberSep™ 43600 Chelating Resin • DuPont™ AmberSep™ GT74 Ion Exchange Resin • DuPont™ AmberSep™ 21K XLT Ion Exchange Resin • DuPont™ AmberSep™ G26 H Ion Exchange Resin • DuPont™ AmberLite™ IRC83 H Resin 	<ul style="list-style-type: none"> • DuPont™ AmberLite™ HPR1100 Na Resin • DuPont™ AmberLite™ HPR9200 Cl • DuPont™ AmberLyst™ A21 • DuPont™ Ultrafiltration SFP Modules

Unconventional & sustainable production of hydrocarbons

Unconventional oil and gas extraction refers to extraction methods other than traditional vertical oil well pumping. Unconventional extraction processes require the use of new, often complex, methods such as developing oil sands (also known as tar sands or bituminous sands), hydraulic fracturing and directional drilling. As these processes become more popular, the exploration of these oil resources also raises environmental concerns such as groundwater contamination and overuse of scarce surface water. DuPont offers innovative water treatment technologies to minimize the environmental impact of unconventional oil and gas extraction methods.

Products Offered for Unconventional Oil & Gas Water Treatment		
Shale Oil	<ul style="list-style-type: none"> • DuPont™ AmberSorb™ L493 • DuPont™ AmberLite™ IRC83 H • DuPont™ AmberLite™ HPR8300 H • FlimTec™ Fortilife™ XC-N 	<ul style="list-style-type: none"> • FilmTec™ SW30XFR-400/34 • FlimTec™ Fortilife™ XC70 • FilmTec™ SW30XHR • FilmTec™ XUS180808
Coal Seam Gas	<ul style="list-style-type: none"> • DuPont™ IntegraFlux™ SFP-2880 • DuPont™ IntegraFlux™ SFP-2880XP • DuPont™ AmberLite™ IRC83 H • FilmTec™ SW30XFR-400/34 	<ul style="list-style-type: none"> • FilmTec™ BW30XFRLE-400/34 • FilmTec™ ECO PRO-400 • FilmTec™ Fortilife™ series • FilmTec™ XUS180808
Steam-Assisted Gravity Drainage (SAGD)	<ul style="list-style-type: none"> • DuPont™ AmberLite™ IRC83 H • DuPont™ AmberLite™ IRC120 Na • DuPont™ AmberLite™ HPR1100 Na 	<ul style="list-style-type: none"> • FilmTec™ Eco Pro™ • FilmTec™ Fortilife™ series elements

Learn more about DuPont’s product offering in the Oil & Gas industry:

Injection Water Treatment brochure



Water Treatment for Unconventional Oil & Gas Extraction Processes brochure



Produced Water Treatment brochure



Picture credits: iStock, DuPont Water Solutions



Water Solutions
dupont.com/water

© 2022 DuPont. DuPont™, the DuPont Oval Logo, and all trademarks and service marks denoted with ™, SM or ® are owned by affiliates of DuPont de Nemours, Inc. unless otherwise noted.

All information set forth herein is for informational purposes only. This information is general information and may differ from that based on actual conditions. Customer is responsible for determining whether products and the information in this document are appropriate for Customer’s use and for ensuring that Customer’s workplace and disposal practices are in compliance with applicable laws and other government enactments. The product shown in this literature may not be available for sale and/or available in all geographies where DuPont is represented. The claims made may not have been approved for use in all countries. Please note that physical properties may vary depending on certain conditions and while operating conditions stated in this document are intended to lengthen product lifespan and/or improve product performance, it will ultimately depend on actual circumstances and is in no event a guarantee of achieving any specific results. DuPont assumes no obligation or liability for the information in this document. References to “DuPont” or the “Company” mean the DuPont legal entity selling the products to Customer unless otherwise expressly noted. NO WARRANTIES ARE GIVEN; ALL IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE ARE EXPRESSLY EXCLUDED. No freedom from infringement of any patent or trademark owned by DuPont or others is to be inferred.

Form No. 45-D04090-en
 July 2022