



NOTES:

1. DETAIL IS FOR RECESSES GREATER THAN 4" DEEP. SEE SEQUENCING SHEETS FOR ADDITIONAL INSTALLATION GUIDANCE.
2. DETAIL IS FOR BUILDINGS LESS THAN 5 STORIES AND LOW-RISE MULTI-FAMILY RESIDENTIAL BUILDINGS LESS THAN 6 STORIES WHEN PERFORMANCE REQUIREMENTS DO NOT EXCEED ASTM E1677 (65 MPH EQUIVALENT STRUCTURAL LOAD AND 15 MPH EQUIVALENT WIND-DRIVEN RAIN WATER INFILTRATION), AND WINDOW/DOOR DESIGN RATINGS THAT DO NOT EXCEED DP45.
3. USE ADDITIONAL LAPS OF DUPONT™ FLASHING TAPE WITH PROPER SHINGLING AND MIN. 2" OVERLAP AS NECESSARY TO ACCOMMODATE RECESS DEPTH.
4. INTERVENING LAYER CAN BE SECOND LAYER OF DUPONT™ TYVEK® WRB, A LAYER OF GRADE D BUILDING PAPER, FELT, RIGID FOAM BOARD OR THE BACKING OF PAPER-BACKED LATH.
5. REPAIR MINOR HOLES WITH DUPONT™ TYVEK® TAPE.
6. FASTEN DUPONT™ TYVEK® WRB WITH APPROVED FASTENERS AND SPACING.
7. INTERIOR VAPOR RETARDER MAY BE REQUIRED IN SOME REGIONS.
8. LOCAL LAWS, ZONING, AND BUILDING CODES VARY AND THEREFORE GOVERN OVER MATERIAL SELECTION AND DETAILING SHOWN.
9. FOR ADDITIONAL INFORMATION REGARDING PRODUCT INSTALLATION, REFER TO THE APPLICABLE DUPONT™ INSTALLATION GUIDELINE.



SCALE: NOT TO SCALE
 REVISION DATE: 11/1/16
 DRAWING: R-CP-2173-MA

INTEGRAL FLANGED WINDOW RECESSED GREATER THAN 4" - SILL
 CEMENT PLASTER