

DuPont™ Tyvek® Fluid Applied WB+™ FAST FACTS



Q: Is it compatible with other DuPont™ Tyvek® commercial weather barrier system products?

A: Yes. Many multifamily projects require a combination of wrap and fluid applied products to meet code and budget goals. The DuPont™ Tyvek® family of commercial products includes DuPont™ Tyvek® CommercialWrap® DuPont™ Tyvek® Flashing and Joint Compound+, and DuPont™ Sealant for Tyvek® Fluid Applied System for single-vendor/single-warranty peace of mind.

DuPont™ Tyvek® Specialist Network:

Expert On-Demand Design and Field Support for Project Success

The DuPont™ Tyvek® Specialist Network is an elite team of more than 165 highly-trained field representatives that is at your service with the design and on-site consulting you need to ensure project success.

Expect your DuPont™ Tyvek® Specialist Network member to assist early in the design phase with guidance on product specification. Team members are available to go on-site at the pre-job meeting to consult on scheduling, review a DuPont™ Tyvek® Weatherization System wall mock-up, and offer any contractor training that may be required. Throughout the warranty process, project site visits are documented and become part of the warranty submittal package, helping protect the project investment.

What Other Multifamily Professionals Say about DuPont™ Tyvek® Fluid Applied WB+™

“We’re using DuPont™ Tyvek® Fluid Applied on a Greenville (S.C.) project. It’s stucco finish on wood frame, so we’re combining different DuPont™ Tyvek® products. DuPont has been very helpful in providing detailing for the transitions.”

Jason Fosselman, Project Manager
Woodfield Investments, Arlington, Va.

“Using a combination of DuPont™ Tyvek® Fluid Applied and CommercialWrap® allowed us to quickly and effectively weatherproof each substrate type, as well as transition areas. We like the ‘one-stop-shop’ approach for warranty consistency.”

Hunt Fugate, AIA, NCARB, LEED AP, Principal
Three Living Architecture, Dallas, Texas

DuPont™ Tyvek® Fluid Applied WB+™ FAQ

Q: What is DuPont™ Tyvek® Fluid Applied WB+™?

A: It’s a spray-on product that forms a long-lasting adhesive and elastic membrane on a wall assembly that controls airflow through the walls, holds out bulk water, and allows interior moisture vapor to escape, helping meet the latest building and energy codes and standards. DuPont™ Tyvek® Fluid Applied WB+™ uses advanced STPE (silyl-terminated polyether) technology, a polymer that offers several inherent advantages over older, typical acrylic and bitumen-based fluid applied air and water barrier products.

Q: Is it easy to apply using standard spray equipment?

A: Yes. DuPont™ Tyvek® Fluid Applied WB+™ is easily applied using standard, everyday spray equipment. No special high PSI spraying is required. A single 25 mil coating is recommended which offers 2 to 3 times the average of competitive products.

Q: What other product attributes help multifamily architects, owners, developers, builders, and consultants meet code, reduce project expenses, and safeguard the investment?

A: DuPont™ Tyvek® Fluid Applied WB+™ supports long open times, up to 90 minutes, for safe, no rush or waste application. The unique spout attachment reduces waste and allows for faster cleanup, saving both time and money. The product also offers low shrinkage during curing, superior elongation and recovery, nine months of UV resistance, and will not wash off the wall when exposed to liquid water (even before curing).

To Learn More

Web: multifamily.tyvek.com

Phone: **1.800.44.TYVEK**