



DUPONT PE772

STRETCHABLE ENCAPSULANT FOR WEARABLES

PRODUCT DESCRIPTION

DuPont PE772 stretchable encapsulant is used to protect low-voltage circuitry printed on elastic film and textile substrates. PE772 is a thin, stretchable protective encapsulant that possesses excellent flexibility, adhesion, and abrasion resistance. PE772 is designed for wearable electronic applications that may require repeated washing.

PRODUCT BENEFITS

- Translucent stretchable encapsulant
- Improves wash and abrasion performance of electrical circuit
- Compatible with wide variety of fabric and film substrates
- Compatible with lamination
- Compatible with PE872 conductor
- Thermal cure 100-160°C; 2-10 minutes

PROCESSING

Screen Printing Equipment

- Automatic reel-to-reel
- Semi-automatic flat-bed
- Rotary screen/cylinder screen

Substrates

- Select synthetic fabrics
- Coated fabrics & membranes
- Thermoplastic polyurethane films

Screens

- 325-200 wire/inch stainless steel mesh
- 120-77 thread/cm polyester mesh

Curing

Dry at 100-160°C for 2-10 minutes in a well-ventilated oven or conveyor dryer, where the exhaust meets environmental regulations. Drying efficiency and good print quality/thickness control help ensure best electrical and physical performance.

Table 1-Typical Physical Properties

Test	Properties
Conductor Resistivity Change After Crease (ASTM F1683, 180deg, 1 cycle, 2kg (PE872 5µm dried orint thickness on Cetus® OS5000U fabric	<5%
Flexibility Δ% After Crease over PE871 Ag (ASTM F1683, 180deg, 1 cycle, 2kg)	No Opens No Cracking
Abrasion Resistance (ASTM D3363 Pencil Hardness)	1H
Adhesion (Tape Cross Hatch) (ASTM D3359 w/3M Scotch Tape 600)	No Transfer
Clean-up Solvent	Ethylene Diacetate
Conductor	PE872

Table 2-Typical Composition Properties

Test	Properties
Color	Clear
Solids (%) @ 150°C	21-25
Viscosity (PaS) Brookfield RVT, #14 spindle, 10rpm, 25°C	40-80
Density (g/cc)	1.06
Coverage (cm ² /g @ 5µm)	600
Coverage (cm ² /g @ 10µm)	420
Dried Print Thickness (microns)	5-10
Thinner	DuPont 8260

Printed on Melinex ST505 polyester film unless stated otherwise. This table shows anticipated typical physical properties for DuPont PE772 based on specific controlled experiments in out labs and are not intended to represent the product specifications. Product specifications are available upon request.

SUBSTRATE TYPES

PE772 is appropriate for many types of thermally-stable substrates in wearable electronics applications. Due to the diverse nature of potential fabrics and films that could be considered, it is not always possible to provide detailed performance guidance. For more information, please call your local DuPont representative.



DUPONT PE772 STRETCHABLE ENCAPSULANT FOR WEARABLES

STORAGE AND SHELF LIFE

Containers should be stored, tightly sealed, in a clean, stable environment at room temperature (<25°C). Shelf life of material in unopened containers is six months from date of shipment. Some settling of solids may occur and compositions should be thoroughly mixed prior to use. Thinning with DuPont 8260 may be desired in some cases depending on printing requirements.

SAFETY AND HANDLING

Please inform the DuPont product supplier if you intend to test PE772, alone or in combination with other materials, on human skin. For Safety and Handling information pertaining to this product, read the Material Safety Data Sheet (MSDS).

FOR MORE INFORMATION ON DUPONT PE772 OR OTHER DUPONT MICROCIRCUIT MATERIALS PRODUCTS, PLEASE CONTACT YOUR LOCAL REPRESENTATIVE:

Americas

DuPont Microcircuit Materials
14 TW Alexander Drive
Research Triangle Park, NC 27709
USA
Tel +1 800 284 3382 (calls within USA)
Tel +1 919 248 5188 (calls outside USA)

Europe, Middle East & Africa

Du Pont (UK) Ltd
Coldharbour Lane
Bristol BS16 1QD
UK
Tel +44 117 931 3191

Asia

DuPont Kabushiki Kaisha
Sanno Park Tower, 11-1
Nagata-cho 2-chome
Chiyoda-ku, Tokyo 100-611
Japan
Tel +81-3-5521-8650

DuPont Taiwan Ltd
45, Hsing-Pont Road
Taoyuan, 330
Taiwan
Tel +886 3 377 3616

DuPont China Holding Company Ltd
Bldg. 11, 399 Keyuan Road
Zhangjiang Hi-Tech Park
Pudong New District
Shanghai 201203 China
Tel +86 21 6386 6366 ext. 2202

DuPont Korea Inc.
3-5th Floor, Asia tower #726
Yeoksam-dong, Gangnam-gu
Seoul 135-719, Korea
Tel +82 10 6385 5399

E.I. DuPont India Private Limited
7th Floor, Tower C, DLF Cyber Greens
Sector-25A, DLF City, Phase-III
Gurgaon 122 002 Haryana, India
Tel +91 124 409 1818

Du Pont Company (Singapore) Pte Ltd
1 HarbourFront Place, #11-01
HarbourFront Tower One
Singapore 098633
Tel +65 6586 3022

mcm.dupont.com

Copyright © 2014 DuPont. All rights reserved. The DuPont Oval Logo, DuPont™, and all DuPont products denoted with ® or ™ are registered trademarks or trademarks of E. I. du Pont de Nemours and Company or its affiliates.

This information corresponds to our current knowledge on the subject. It is offered solely to provide possible suggestions for your own experimentations. It is not intended, however, to substitute for any testing you may need to conduct to determine for yourself the suitability of our products for your particular purposes. This information may be subject to revision as new knowledge and experience becomes available. Since we cannot anticipate all variations in end-use conditions, DuPont makes no warranties, and assumes no liability in connection with any use of this information. Nothing in this publication is to be considered as a license to operate under or a recommendation to infringe any patent right.

CAUTION: Do not use in medical applications involving permanent implantation in the human body. For other medical applications, see "DuPont Medical Caution Statement," H-50102-5.

K-28728 11/14