



WATER TREATMENT AT POWER PLANT

Cooling Water Blow-Down Product Recommendations

Cooling tower blowdown is often too impaired to be reused without treatment and is typically sent directly to the facility’s wastewater treatment plant. This imposes a hydraulic load on the wastewater treatment system. More importantly, a tremendous amount of relatively clean water is wasted, adding significant cost and discharge compliance complexity. DuPont can work with you to deliver the optimal solution for your needs, using robust, reliable, fouling-resistant filtration and purification technologies to recover and return up to 90% of blowdown water for makeup water use.

| TECHNOLOGY | PRODUCT | APPLICATION | FEATURES |
|-------------------------------------|--|--|---|
| ULTRAFILTRATION MODULE AND SKIDS | IntegraFlux™ SFP-2880XP Module | Suspended Solids Removal | High permeability and high mechanical strength hollow fiber Polyvinylidene fluoride (PVDF) membranes. The modules provide excellent performance, industry leading membrane area with low energy and chemical consumption. XP fiber provides up to 35% higher permeability than previous generation modules improving operating efficiencies and productivity. |
| | DuPont™ Ultrafiltration SFP-2880 Module | | High mechanical strength hollow fiber PVDF membranes. The modules provide excellent performance with industry-leading membrane area. |
| | IntegraPac™ IP-77XP Skid | | The skids are pre-engineered, standardized and ready to assemble. Comprising of IntegraPac™ modules (standard and XP fiber), auxiliary parts and piping the skids can significantly streamline design, assembly, and installation. Flexible sizing with 6-22 modules per skid. |
| | IntegraPac™ IP-77 Skid | | |
| REVERSE OSMOSIS ELEMENTS | FilmTec™ Fortilife™ CR 100 | Demineralization from Challenging Feedwater Source | State-of-the-art solution to tackle tough fouling coupled with excellent salt rejection. |
| | FilmTec™ Eco Pro-400 | | State-of-the-art solution to deliver high salt rejection at low operating pressure reducing CAPEX and OPEX. |
| | FilmTec™ BW30XFR-400/34 | | Established high fouling resistance and fouling removal efficiency coupled with very high rejection proven at broad TDS range. |
| | FilmTec™ BW30XFRLE-400/34 | | Improved fouling resistance as well as efficiency of element’s cleaning combined with low energy consumption and good water purity. |
| | FilmTec™ BW30-400/34 | | Consistent and reliable high operational performance coupled with increased productivity comparing to BW30-365. |
| | FilmTec™ BW30-365 | | Established industry reference product providing consistent, high performance and long element life with decades of proven performance. |

www.dupont.com/water/contact-us

No freedom from infringement of any patent or trademark owned by DuPont or others is to be inferred. Because use conditions and applicable laws may differ from one location to another and may change with time, Customer is responsible for determining whether products and the information in this document are appropriate for Customer’s use and for ensuring that Customer’s workplace and disposal practices are in compliance with applicable laws and other government enactments. The product shown in this literature may not be available for sale and/or available in all geographies where DuPont is represented. The claims made may not have been approved for use in all countries. DuPont assumes no obligation or liability for the information in this document. References to “DuPont” or the “Company” mean the DuPont legal entity selling the products to Customer unless otherwise expressly noted. NO WARRANTIES ARE GIVEN; ALL IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE ARE EXPRESSLY EXCLUDED.

DuPont™, the DuPont Oval Logo, and all trademarks and service marks denoted with ™, SM or © are owned by affiliates of DuPont de Nemours Inc. unless otherwise noted. © 2020 DuPont.

