



Ion Exchange

Boiling Water Reactor

Condensate Polisher and Reactor Water Clean Up

The resins employed for boiling water reactor (BWR) purification must be able to purify water to a maximum degree. Any traces of organic and inorganic impurities will become problematic in the pure water environment of the reactor circuits. Our IRN-grade ion exchange resins are proven to be the premier resins chosen to protect nuclear power plants throughout the world, able to maintain the purity of the BWR circuit even in extreme temperature conditions.

PRODUCT	APPLICATION	FEATURES AND RECOMMENDED USES	TYPE	MATRIX	MINIMUM TOTAL VOLUME CAPACITY (eq/L)	IONIC FORM AS SHIPPED
DuPont™ AmberLite™ IRN99 H	CPP	AmberLite™ IRN99 H Resin is a premium 16% DVB uniform particle size cation resin with very high capacity and oxidative stability. The high oxidative stability reduces reactor water sulfate concentration in BWR condensate polishing.	SAC	GEL	2.50	H+
DuPont™ AmberLite™ IRN78 OH	CPP	AmberLite™ IRN78 OH is a premium high solids uniform particle size anion resin with very high capacity. It is specifically processed to minimize organic chloride content. Pairing with AmberLite™ IRN99 H offers the highest capacity and lowest sulfate with less-separating characteristics.	SBA	GEL	1.20	OH-
DuPont™ AmberLite™ IRN150 H/OH	CPP/RWCU	Nuclear grade mixed bed composed of uniform particle size AmberLite™ IRN77 H and IRN78 OH Resins on a 1:1 equivalent basis.	MB	GEL/GEL	1.90/1.20	H+/OH-
DuPont™ AmberLite™ IRN160 H/OH	CPP/RWCU	High-capacity nuclear grade mixed bed composed of uniform particle size AmberLite™ IRN97 H and IRN78 OH Resins on a 1:1 equivalent basis. Designed to minimize separation of anion and cation during installation and transfer in BWR condensate polishing.	MB	GEL/GEL	2.10/1.20	H+/OH-
DuPont™ AmberLite™ IRN170 H/OH	CPP/RWCU	Premium nuclear grade mixed bed composed of uniform particle size AmberLite™ IRN99 H and IRN78 OH Resins on a 1:1 equivalent basis. This highly recommended option offers maximum oxidative stability, the highest operating capacity to achieve the lowest reactor water sulfate concentration, the lowest separability, and the longest resin life for all BWR applications.	MB	GEL/GEL	2.50/1.20	H+/OH-

Key:

- CPP = Condensate Polishing Plant
- RWCU = Reactor Water Clean Up
- SBA = Strong Base Anion
- SAC = Strong Acid Cation
- MB = Mixed Bed

Powering performance worldwide.

With a large global manufacturing footprint, strong R&D expertise and technical support services and systems, we supply high market volumes with high quality. DuPont partners with you, our customer, to understand unmet needs and develop tailored solutions.

TECHNICAL SERVICE, RESEARCH & DEVELOPMENT

Chauny, France*
Edina, MN, USA
Huzhou, China
Hyderabad, India
KAUST Jeddah, KSA
Midland, MI, USA
Shanghai, China Singapore
Tarragona, Spain*
Wilmington, DE, USA

COMMERCIAL OPERATIONS

Astana, Kazakhstan
Bangkok, Thailand
Beijing, China
Bogota, Colombia
Buenos Aires, Argentina
Budapest, Hungary
Dubai, UAE
Chengdu, China
Delhi, India
Edina, MN, USA
Guangzhou, China
HCM City, Vietnam
Hong Kong, China
Jakarta, Indonesia
Johannesburg, South Africa
Kuala Lumpur, Malaysia
Madrid, Spain

Manila, Philippine
Melbourne, Australia
Mexico City, Mexico
Midland, MI, USA
Moscow, Russia
Mumbai, India Nairobi,
Kenya
Paris, France São
Paulo, Brazil
Seoul, Republic of Korea
Pfaeffikon, Switzerland
Shanghai, China Singapore
Surubya, Indonesia Taipei,
Taiwan Tokyo, Japan
Warsaw, Poland

MANUFACTURING

Chauny, France
Edina, MN, USA
Fombio, Italy
Huzhou, China
Jubail Industry
City, Saudi
Arabia Midland,
MI, USA
Qingpu, China
Soma, Japan



Have a question? Contact us at:

www.dupont.com/water/contact-us

All information set forth herein is for informational purposes only. This information is general information and may differ from that based on actual conditions. Customer is responsible for determining whether products and the information in this document are appropriate for Customer's use and for ensuring that Customer's workplace and disposal practices are in compliance with applicable laws and other government enactments. The product shown in this literature may not be available for sale and/or available in all geographies where DuPont is represented. The claims made may not have been approved for use in all countries. Please note that physical properties may vary depending on certain conditions and while operating conditions stated in this document are intended to lengthen product lifespan and/or improve product performance, it will ultimately depend on actual circumstances and is in no event a guarantee of achieving any specific results. DUPONT ASSUMES NO OBLIGATION OR LIABILITY FOR THE INFORMATION IN THIS DOCUMENT. References to "DuPont" or the "Company" mean the DuPont legal entity selling the products to Customer unless otherwise expressly noted. NO WARRANTIES ARE GIVEN; ALL IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE ARE EXPRESSLY EXCLUDED. No freedom from infringement of any patent or trademark owned by DuPont or others is to be inferred.

DuPont™, the DuPont Oval Logo, and all trademarks and service marks denoted with ™, SM or ® are owned by affiliates of DuPont de Nemours, Inc. unless otherwise noted. © 2023 DuPont. All right reserved